



KBPC600 THRU KBPC610

SINGLE PHASE 6.0 AMPS SILICON BRIDGE RECTIFIERS




VOLTAGE RANGE
50 to 1000 Volts
CURRENT
6.0 Amperes

FEATURES

- * Surge overload rating 200 amperes peak
- * Low forward voltage drop
- * Small size, simple installation
- * Leads solderable per MIL - STD - 202 Method 208

KBPC-6



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	KBPC 600	KBPC 601	KBPC 602	KBPC 604	KBPC 606	KBPC 608	KBPC 610	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum D. C Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_C = 50^\circ C^{(1,2)}$	$I_{F(AV)}$	6.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	200							A
Maximum Forward Voltage Drop per element @ 3.0A	V_F	1.10							V
Maximum Reverse Current at Rated @ $T_A = 25^\circ C$ D. C. Blocking Voltage per element @ $T_A = 100^\circ C$	I_R	10 500							μA μA
Operating Temperature Range	T_J	-55 to + 125							$^\circ C$
Storage Temperature Range	T_{STG}	-55 to + 150							$^\circ C$

NOTE: (1) Bolt down on heat - sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer with #6 screw
(2) Unit mounted on 5.5 x 6.0 x 0.11" thick (14 x 15 x 0.3cm) Al. Plate



RATINGS AND CHARACTERISTIC CURVES (KBPC600 THRU KBPC610)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT - PER ELEMNET




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL FORWARD CHARACTERISTICS PER ELEMNET




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS PER ELEMNET

