



## KBP200 THRU KBP210


**SINGLE PHASE 2.0 AMPS . SILICON BRIDGE RECTIFIERS**



**VOLTAGE RANGE**  
50 to 1000 Volts  
**CURRENT**  
2.0 Amperes

### FEATURES

- \* Ideal for printed circuit board
- \* High Surge Current Capability
- \* Reliable low cost construction
- \* Small size, simple installation



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	KBP 200	KBP 201	KBP 202	KBP 204	KBP 206	KBP 208	KBP 210	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum D. C Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_A = 50^\circ C$	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load(JEDEC method)	$I_{FSM}$	50							A
Maximum Forward Voltage Drop per element @ 1.0A(Note)	$V_F$	1.10							V
Maximum Reverse Current at Rated @ $T_A = 25^\circ C$ D. C. Blocking Voltage per element @ $T_A = 100^\circ C$	$I_R$	10 500							$\mu A$ $\mu A$
Operating Temperature Range	$T_J$	- 55 to + 125							$^\circ C$
Storage Temperature Range	$T_{STG}$	- 55 to + 150							$^\circ C$

NOTE: Mounted on glass - epoxy P. C. B, Soldering land  $\phi 3mm$ .



## RATINGS AND CHARACTERISTIC CURVES (KBP200 THRU KBP210)

FIG. 1-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT - PER ELEMENT




FIG. 2-TYPICAL FORWARD OUTPUT CURRENT DERATING CURVE




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS - PER ELEMENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS PER ELEMENT

