

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER


VOLTAGE RANGE 20 to 40 Volts CURRENT 1.0 Ampere

FEATURES

- * Glass passivated device
- * Ideal for surface mounted applications
- * Low leakage current
- * Metallurgically bonded construction
- * Mounting position: Any
- * Weight: 0.057 gram



DO-214AC



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	FM120M	FM140M	UNITS
Maximum Recurrent Peak Reverse Voltage	VRRM	20	40	Volts
Maximum RMS Voltage	VRMS	14	28	Volts
Maximum DC Blocking Voltage	VDC	20	40	Volts
Maximum Average Forward Rectified Current at Derating Lead Temperature	IO	1.0		Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	40		Amps
Typical Thermal Resistance (Note 1)	RθJA	50		°C/W
Typical Junction Capacitance (Note 2)	CJ	110		pF
Operating Temperature Range	TJ	-65 to + 125		°C
Storage Temperature Range	TSTG	-65 to + 150		°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	FM120M	FM140M	UNITS
Maximum Instantaneous Forward Voltage at 1.0A DC	VF	0.36	0.38	Volts
Maximum Average Reverse Current	IR	1.0		mAmps
at Rated DC Blocking Voltage		10		mAmps

NOTES : 1. Thermal Resistance (Junction to Ambient).
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
3. P.C.B Monuted with 0.2X0.2" (5.0X5.0mm²) copper pad area.

EEPW 电子產品世界
.com.cn