

M/A-COM Two-Way In-Phase Power Divider 0.4 - 400 MHz

Features

- Space Qualified version of DS-113
- Designed to meet the Stringent Reliability Standards of Space Hardware
- 50 Ohms Nominal Impedance
- Three Decade Bandwidth
- Low Loss: -0.25 Typ.

Description

M/A-COM's PD10-0041-S is a Two-Way In-Phase Power Divider designed to operate between 400 KHz and 400 MHz

Absolute Maximum Ratings¹

Parameter	Absolute Maximum
Max. Input Power	1 Watt Max.
Operating Temperature	-30°C to +85°C
Storage Temperature	-65°C to +125°C


1. Operation of this device above any one of these parameters may cause permanent damage.

Electrical Specifications, T_A = +25°C

Parameter	Frequency	Units	Min.	Max.
Insertion Loss	0.4-400 MHz	dB	-	0.75
Isolation	0.4-400 MHz	dB	25	-
Amplitude Balance	0.4-400 MHz	dB	-	0.15
Phase Balance	0.4-400 MHz	-	-	1°
VSWR	0.4-400 MHz	-	-	1.5

1. All specifications apply with a 50-Ohm source and load impedance.

FP-2



Dimensions in () are in mm.
Unless Otherwise Noted: .xxx = ±0.010 (.xx = ±0.25)
.xx = ±0.02 (.x = ±0.5)
WEIGHT (APPROX.): 0.09 OUNCES 2.5 GRAMS

Specifications subject to change without notice.

■ North America: Tel. (800) 366-2266, Fax (800) 618-8883
 ■ Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

Visit www.macom.com for additional data sheets and product information.