

IEC LEVEL 4 ESD-PROTECTED 0.75-Ω SPDT ANALOG SWITCH WITH 1.8-V COMPATIBLE INPUT LOGIC


FEATURES

- Low ON-State Resistance (0.75 Ω)
- Low Charge Injection
- Excellent ON-State Resistance Matching
- Isolation in Power-Down Mode, $V_+ = 0$
- Specified Break-Before-Make Switching
- 2.25-V to 5.5-V Power Supply (V_+)
- 6-MΩ Input Pulldown Allows Control Input (IN) to Be Unconnected
- 1.8-V Compatible Control Input Threshold Independent of V_+
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Performance Tested Per JESD 22
 - 3000-V Human-Body Model (A114-B, Class II)
 - 1000-V Charged-Device Model (C101)
- ESD Performance COM Port to GND
 - 8000-V Human-Body Model (A114-B, Class II)
 - ±8-kV Contact Discharge (IEC 61000-4-2)
 - ±15-kV Air-Gap Discharge (IEC 61000-4-2)

APPLICATIONS

- Cell Phones
- PDAs
- Portable Instrumentation
- MP3 Players
- Portable Media Players

YFP PACKAGE



TERMINAL ASSIGNMENTS

C	V_+	NC
B	COM	GND
A	IN	NO
	2	1

DESCRIPTION/ORDERING INFORMATION

The TS5A12301E is a single-pole double-throw (SPDT) analog switch that is designed to operate from 2.25 V to 5.5 V. The device offers a low ON-state resistance with an excellent channel-to-channel ON-state resistance matching, and the break-before-make feature to prevent signal distortion during the transferring of a signal from one path to another.

The device has excellent total harmonic distortion (THD) performance and consumes very low power. These features make this device suitable for portable audio applications. The control input (IN) pin can be connected to low-voltage GPIOs, allowing it to be controlled by 1.8-V signals.

The TS5A12301E has ±15-kV Air-Gap Discharge and ±8-kV Contact Discharge ESD protection for the COM port to GND, which make it compliant with the IEC Level 4 ESD standard (IEC 61000-4-2).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

ORDERING INFORMATION

T_A	PACKAGE⁽¹⁾⁽²⁾		ORDERABLE PART NUMBER	TOP-SIDE MARKING⁽³⁾
–40°C to 85°C	WCSP (DSBGA) 0.4-mm Pitch – YFP (Pb-free)	Tape and reel	TS5A12301EYFPR	___ 3W_

- (1) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.
 (2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at www.ti.com.
 (3) YFP: The actual top-side marking has three preceding characters to denote year, month, and sequence code, and one following character to designate the assembly/test site. Pin 1 identifier indicates solder-bump composition (1 = SnPb, • = Pb-free).

SUMMARY OF CHARACTERISTICS⁽¹⁾

Configuration	2:1 Multiplexer/Demultiplexer (1 × SPDT)
Number of channels	1
ON-state resistance (r_{on})	0.75 Ω max
ON-state resistance match (Δr_{on})	0.1 Ω max
ON-state resistance flatness ($r_{on(flat)}$)	0.1 Ω max
Turn-on/turn-off time (t_{ON}/t_{OFF})	110 ns/100 ns
Break-before-make time (t_{BBM})	10 ns
Charge injection (Q_C)	97 pC
Bandwidth (BW)	55 MHz
OFF isolation (O_{ISO})	–63 dB at 1 MHz
Crosstalk (X_{TALK})	–63 dB at 1 MHz
Total harmonic distortion (THD)	0.003%
Leakage current ($I_{NO(OFF)}/I_{NC(OFF)}$)	20 nA
Package option	6-pin WCSP, 0.4-mm pitch

(1) $V_+ = 5\text{ V}$, $T_A = 25^\circ\text{C}$

FUNCTION TABLE

IN	NC TO COM, COM TO NC	NO TO COM, COM TO NO
L or Open	ON	OFF
H	OFF	ON

ABSOLUTE MAXIMUM RATINGS⁽¹⁾⁽²⁾

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V_+	Supply voltage range ⁽³⁾	–0.5	6.5	V
V_{NC} V_{NO} V_{COM}	Analog voltage range ⁽³⁾⁽⁴⁾⁽⁵⁾	–0.5	$V_+ + 0.5$	V
I_{IK}	Analog port diode current $V_+ < V_{NC}, V_{NO}, V_{COM}$ or $V_{NC}, V_{NO}, V_{COM} < 0$	–50	50	mA
I_{NC} I_{NO} I_{COM}	On-state switch current On-state peak switch current ⁽⁶⁾ $V_{NC}, V_{NO}, V_{COM} = 0$ to V_+	–200 –400	200 400	mA
V_I	Digital input voltage range ⁽³⁾⁽⁴⁾	–0.5	6.5	V
I_{IK}	Digital input clamp current $V_I < 0$	–50		mA
I_+ I_{GND}	Continuous current through V_+ or GND	–100	100	mA
T_{stg}	Storage temperature range	–65	150	°C

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum
- (3) All voltages are with respect to ground, unless otherwise specified.
- (4) The input and output voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
- (5) This value is limited to 5.5 V maximum.
- (6) Pulse at 1-ms duration < 10% duty cycle

THERMAL IMPEDANCE RATINGS

			UNIT
θ_{JA}	Package thermal impedance ⁽¹⁾ YFP package	154.2	°C/W

- (1) The package thermal impedance is calculated in accordance with JESD 51-7.

ELECTRICAL CHARACTERISTICS FOR 5-V SUPPLY⁽¹⁾
 $V_+ = 4.5\text{ V to }5.5\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch								
Analog signal range	V_{COM}, V_{NO}, V_{NC}				0		V_+	V
ON-state resistance	r_{on}	V_{NO} or $V_{NC} = 2.5\text{ V}$, $I_{COM} = -100\text{ mA}$, See Figure 14	25°C Full	4.5 V		0.5 0.8	0.75	Ω
ON-state resistance match between channels	Δr_{on}	V_{NO} or $V_{NC} = 2.5\text{ V}$, $I_{COM} = -100\text{ mA}$, See Figure 14	25°C Full	4.5 V		0.05 0.1	0.1	Ω
ON-state resistance flatness	$r_{on(flat)}$	$0 \leq (V_{NO} \text{ or } V_{NC}) \leq V_+$, $I_{COM} = -100\text{ mA}$, See Figure 14 V_{NO} or $V_{NC} = 1\text{ V}, 1.5\text{ V}, 2.5\text{ V}$, $I_{COM} = -100\text{ mA}$, See Figure 14	25°C 25°C Full	4.5 V		0.15 0.1 0.25		Ω
NO, NC OFF leakage current	$I_{NO(OFF)}, I_{NC(OFF)}$	$V_{NO} = 1\text{ V}, 4.5\text{ V}$, $V_{COM} = 4.5\text{ V}, 1\text{ V}$, $V_{NC} = \text{Open}$, or $V_{NO} = 1\text{ V}, 4.5\text{ V}$, $V_{COM} = 4.5\text{ V}, 1\text{ V}$, $V_{NO} = \text{Open}$, See Figure 15	25°C Full	5.5 V	-20 -100	2	20 100	nA
	$I_{NO(PWROFF)}, I_{NC(PWROFF)}$	V_{NO} or $V_{NC} = 0\text{ to }5.5\text{ V}$, $V_{COM} = 5.5\text{V to }0$	25°C Full	0 V	-10 -10		10 10	μA
NC, NO ON leakage current	$I_{NO(ON)}$	$V_{NO} = 1\text{ V}, 4.5\text{ V}$, $V_{COM}, V_{NC} = \text{Open}$, or $V_{NC} = 1\text{ V}, 4.5\text{ V}$, $V_{COM}, V_{NO} = \text{Open}$, See Figure 16	25°C Full	5.5 V	-20 -200	2	20 200	nA
COM ON leakage current	$I_{COM(ON)}$	$V_{COM} = 1\text{ V}, 4.5\text{ V}$, V_{NO} and $V_{NC} = \text{Open}$, or $V_{COM} = 1\text{ V}, 4.5\text{ V}$, V_{NO} or $V_{NC} = \text{Open}$, See Figure 16	25°C Full	5.5 V	-20 -200	2	20 200	nA
COM OFF leakage current	$I_{COM(PWROFF)}$	V_{NO} or $V_{NC} = 0\text{ to }5.5\text{ V}$, $V_{COM} = 5.5\text{V to }0$, See Figure 15	25°C Full	0 V	-10 -10		10 10	μA
Digital Control Input (IN)								
Input logic high	V_{IH}		Full	5.5 V	1.05		5.5	V
Input logic low	V_{IL}		Full	5.5 V	0		0.65	V
Input leakage current	I_{IH}, I_{IL}	$V_I = 1.95\text{ V or }0$	Full	5.5 V	-0.05		0.5	μA
Input resistance	r_{IN}	$V_I = 1.95\text{ V}$	Full	5.5 V		6		M Ω

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

ELECTRICAL CHARACTERISTICS FOR 5-V SUPPLY (continued)
 $V_+ = 4.5\text{ V to }5.5\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic								
Turn-on time	t_{ON}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 18	25°C	5 V	110	225	ns
				Full	4.5 V		250	
Turn-off time	t_{OFF}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 18	25°C	5 V	100	215	ns
				Full	4.5 V		225	
Break-before-make time	t_{BBM}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 19	25°C	5 V	1	10	ns
				Full	4.5 V	1	20	
Charge injection	Q_C	$V_{GEN} = 0$, $R_{GEN} = 0$,	$C_L = 1\text{ nF}$, See Figure 23	25°C	5 V	97		pC
NO OFF capacitance	$C_{NO(OFF)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch OFF,	See Figure 17	25°C	5 V	28		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON,	See Figure 17	25°C	5 V	112		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 17	25°C	5 V	112		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND,	See Figure 17	25°C	5 V	3		pF
Bandwidth	BW	$R_L = 50\ \Omega$, Switch ON,	See Figure 20	25°C	5 V	55		MHz
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$,	See Figure 21	25°C	5 V	–63		dB
Crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$,	See Figure 22	25°C	5 V	–63		dB
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 50\text{ pF}$,	$f = 20\text{ Hz to }20\text{ kHz}$, See Figure 24	25°C	5 V	0.003		%
Supply								
Positive supply current	I_+	$V_I = V_+$ or GND	Full	5.5 V			10	μA

ELECTRICAL CHARACTERISTICS FOR 3.3-V SUPPLY⁽¹⁾
 $V_+ = 3\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch								
Analog signal range	V_{COM}, V_{NO}				0		V_+	V
ON-state resistance	r_{on}	V_{NO} or $V_{NC} = 2\text{ V}$, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	3 V		0.75 1.2	0.9	Ω
ON-state resistance match between channels	Δr_{on}	V_{NO} or $V_{NC} = 2\text{ V}$, 0.8 V, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	3 V		0.1 0.15	0.15	Ω
ON-state resistance flatness	$r_{on(flat)}$	$0 \leq (V_{NO} \text{ or } V_{NC}) \leq V_+$, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	3 V		0.2 0.1 0.3	0.2	Ω
NO, NC OFF leakage current	$I_{NO(OFF)}, I_{NC(OFF)}$	$V_{NO} = 1\text{ V}$, 3 V, $V_{COM} = 3\text{ V}$, 1 V, $V_{NC} = \text{Open}$, or $V_{NC} = 1\text{ V}$, 3 V, $V_{COM} = 3\text{ V}$, 1 V, $V_{NO} = \text{Open}$, Switch OFF, See Figure 15	25°C Full	3.6 V	-20 -50	2	20 50	nA
	$I_{NO(PWROFF)}, I_{NC(PWROFF)}$	V_{NO} or $V_{NC} = 0$ to 3.6 V, $V_{COM} = 3.6\text{ V to }0$	25°C Full	0 V	-10 -10		10 10	μA
NC, NO ON leakage current	$I_{NO(ON)}$	$V_{NO} = 1\text{ V}$, 3 V, V_{NC} and $V_{COM} = \text{Open}$, or $V_{NC} = 1\text{ V}$, 3 V, V_{NO} and $V_{COM} = \text{Open}$, Switch ON, See Figure 16	25°C Full	3.6 V	-20 -100	2	20 100	nA
COM ON leakage current	$I_{COM(ON)}$	$V_{COM} = 1\text{ V}$, V_{NO} and $V_{NC} = \text{Open}$, or $V_{COM} = 3\text{ V}$, V_{NO} and $V_{NC} = \text{Open}$, See Figure 16	25°C Full	3.6 V	-20 -100	2	20 100	nA
COM OFF leakage current	$I_{COM(PWROFF)}$	V_{NO} or $V_{NC} = 0$ to 3.6 V, $V_{COM} = 3.6\text{ V to }0$, See Figure 15	25°C Full	0 V	-10 -10		10 10	μA
Digital Control Input (IN)								
Input logic high	V_{IH}		Full	3.6 V	1.05		5.5	V
Input logic low	V_{IL}		Full	3.6 V	0		0.65	V
Input leakage current	I_{IH}, I_{IL}	$V_I = 1.95\text{ V or }0$	Full	3.6 V	-0.05		0.5	μA
Input resistance	r_{IN}	$V_I = 1.95\text{ V}$	Full	3.6 V		6		M Ω

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

ELECTRICAL CHARACTERISTICS FOR 3.3-V SUPPLY (continued)
 $V_+ = 3\text{ V to }3.6\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic								
Turn-on time	t_{ON}	$V_{COM} = V_+$, $R_L = 50\ \Omega$, $C_L = 35\text{ pF}$, See Figure 18	25°C	3.3 V		72	175	ns
			Full	3 V			185	
Turn-off time	t_{OFF}	$V_{COM} = V_+$, $R_L = 50\ \Omega$, $C_L = 35\text{ pF}$, See Figure 18	25°C	3.3 V		105	165	ns
			Full	3 V			170	
Break-before-make time	t_{BBM}	$V_{COM} = V_+$, $R_L = 50\ \Omega$, $C_L = 35\text{ pF}$, See Figure 19	25°C	3.3 V	1	16	30	ns
			Full	3 V	1		35	
Charge injection	Q_C	$V_{GEN} = 0$, $R_{GEN} = 0$, $C_L = 1\text{ nF}$, See Figure 23	25°C	3.3V		97		pC
NO OFF capacitance	$C_{NO(OFF)}$	$V_{NO} = V_+$ or GND, Switch OFF, See Figure 17	25°C	3.3 V		28		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON, See Figure 17	25°C	3.3 V		115		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON, See Figure 17	25°C	3.3 V		115		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND, See Figure 17	25°C	3.3 V		3		pF
Bandwidth	BW	$R_L = 50\ \Omega$, Switch ON, See Figure 20	25°C	3.3 V		54		MHz
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$, See Figure 21	25°C	3.3 V		–63		dB
Crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$, See Figure 22	25°C	3.3 V		–63		dB
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 50\text{ pF}$, $f = 20\text{ Hz to }20\text{ kHz}$, See Figure 24	25°C	3.3 V		0.004		%
Supply								
Positive supply current	I_+	$V_I = 1.95\text{ V or GND}$	25°C	3.6 V			10	μA

ELECTRICAL CHARACTERISTICS FOR 2.5-V SUPPLY⁽¹⁾
 $V_+ = 2.25\text{ V to }2.75\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch								
Analog signal range	V_{COM}, V_{NO}				0		V_+	V
ON-state resistance	r_{on}	V_{NO} or $V_{NC} = 1.8\text{ V}$, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	2.25 V	1.1	1.3	1.6	Ω
ON-state resistance match between channels	Δr_{on}	V_{NO} or $V_{NC} = 1.8\text{ V}$, 0.8 V, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	2.25 V	0.15	0.2	0.2	Ω
ON-state resistance flatness	$r_{on(flat)}$	$0 \leq (V_{NO} \text{ or } V_{NC}) \leq V_+$, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C	2.25 V	0.4			Ω
		V_{NO} or $V_{NC} = 0.8\text{ V}, 1\text{ V}, 1.8\text{ V}$, $I_{COM} = -100\text{ mA}$, Switch ON, See Figure 14	25°C Full	2.25 V	0.25	0.5	0.6	Ω
NO, NC OFF leakage current	$I_{NO(OFF)}, I_{NC(OFF)}$	$V_{NO} = 0.5\text{ V}, 2.2\text{ V}$, $V_{COM} = 2.2\text{ V}, 0.5\text{ V}$, $V_{NC} = \text{Open}$, or $V_{NC} = 0.5\text{ V}, 2.2\text{ V}$, $V_{COM} = 2.2\text{ V}, 0.5\text{ V}$, $V_{NO} = \text{Open}$, Switch OFF, See Figure 15	25°C Full	2.75 V	-20	2	20	nA
	$I_{NO(PWROFF)}, I_{NC(PWROFF)}$	V_{NO} or $V_{NC} = 0\text{ to }2.75\text{ V}$, $V_{COM} = 2.75\text{ V to }0$	25°C Full	0 V	-10		10	μA
NC, NO ON leakage current	$I_{NO(ON)}$	$V_{NO} = 0.5\text{ V}, 2.2\text{ V}$, V_{NC} and $V_{COM} = \text{Open}$, or $V_{NC} = 2.2\text{ V}, 0.5\text{ V}$, V_{NO} and $V_{COM} = \text{Open}$, Switch ON, See Figure 16	25°C Full	2.75 V	-20	2	20	nA
COM ON leakage current	$I_{COM(ON)}$	$V_{COM} = 0.5\text{ V}$, V_{NO} and $V_{NC} = \text{Open}$, or $V_{COM} = 2.2\text{ V}$, V_{NO} and $V_{NC} = \text{Open}$, Switch ON, See Figure 16	25°C Full	2.75 V	-20	2	20	nA
COM OFF leakage current	$I_{COM(PWROFF)}$	V_{NO} or $V_{NC} = 0\text{ to }2.75\text{ V}$, $V_{COM} = 2.75\text{ V to }0$, See Figure 15	25°C Full	0 V	-10		10	μA
Digital Control Input (IN)								
Input logic high	V_{IH}		Full	2.75 V	1.05		5.5	V
Input logic low	V_{IL}		Full	2.75 V	0		0.65	V
Input leakage current	I_{IH}, I_{IL}	$V_I = 1.95\text{ V or }0$	Full	2.75 V	-0.05		0.5	μA
Input resistance	r_{IN}	$V_I = 1.95\text{ V}$	Full	2.75 V		6		M Ω

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

ELECTRICAL CHARACTERISTICS FOR 2.5-V SUPPLY (continued)
 $V_+ = 2.25\text{ V to }2.75\text{ V}$, $T_A = -40^\circ\text{C to }85^\circ\text{C}$ (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic								
Turn-on time	t_{ON}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 18	25°C	2.5 V	97	170	ns
				Full	2.25 V		175	
Turn-off time	t_{OFF}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 18	25°C	2.5 V	80	155	ns
				Full	2.25 V		160	
Break-before-make time	t_{BBM}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	$C_L = 35\text{ pF}$, See Figure 19	25°C	2.5 V	5	18	ns
				Full	2.25 V	5	40	
Charge injection	Q_C	$V_{GEN} = 0$, $R_{GEN} = 0$,	$C_L = 1\text{ nF}$, See Figure 23	25°C	2.5 V	82		pC
NO OFF capacitance	$C_{NO(OFF)}$	$V_{NO} = V_+$ or GND, Switch OFF,	See Figure 17	25°C	2.5 V	29		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON,	See Figure 17	25°C	2.5 V	116		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 17	25°C	2.5 V	116		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND,	See Figure 17	25°C	2.5 V	3		pF
Bandwidth	BW	$R_L = 50\ \Omega$, Switch ON,	See Figure 20	25°C	2.5 V	54		MHz
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$,	See Figure 21	25°C	2.5 V	–63		dB
Crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $f = 1\text{ MHz}$,	See Figure 22	25°C	2.5 V	–63		dB
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 50\text{ pF}$,	$f = 20\text{ Hz to }20\text{ kHz}$, See Figure 24	25°C	2.5 V	0.008		%
Supply								
Positive supply current	I_+	$V_I = 1.95\text{ V}$ or GND	Full	2.75 V			10	μA

TYPICAL PERFORMANCE







Figure 1. r_{on} vs V_{COM} ($V_+ = 2.25$ V)Figure 2. r_{on} vs V_{COM} ($V_+ = 3$ V)Figure 3. r_{on} vs V_{COM} ($V_+ = 4.5$ V)Figure 4. Leakage Current vs Temperature ($V_+ = 5$ V)Figure 5. I_+ vs V_+ ($T_A = 25^\circ\text{C}$)

Figure 6. Control Input Thresholds

TYPICAL PERFORMANCE (continued)




Figure 7. t_{ON}/t_{OFF} vs Supply Voltage




Figure 8. t_{ON}/t_{OFF} vs Temperature




Figure 9. Charge Injection (Q_C) vs V_{COM}




Figure 10. Gain vs Frequency




Figure 11. OFF Isolation vs Frequency




Figure 12. Crosstalk vs Frequency

TYPICAL PERFORMANCE (continued)




Figure 13. Total Harmonic Distortion (THD) vs Frequency

EEPW 电子产品世界
.com.cn

PARAMETER MEASUREMENT INFORMATION




Figure 14. ON-State Resistance (r_{on})




Figure 15. OFF-State Leakage Current ($I_{COM(OFF)}$, $I_{NC(OFF)}$, $I_{COM(PWROFF)}$, $I_{NC(PWRFF)}$)






Figure 16. ON-State Leakage Current ($I_{COM(ON)}$, $I_{NC(ON)}$)


PARAMETER MEASUREMENT INFORMATION (continued)

Figure 17. Capacitance (C_I , $C_{COM(OFF)}$, $C_{COM(ON)}$, $C_{NC(OFF)}$, $C_{NC(ON)}$)

- A. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r < 5 \text{ ns}$, $t_f < 5 \text{ ns}$.
- B. C_L includes probe and jig capacitance.

Figure 18. Turn-On (t_{ON}) and Turn-Off Time (t_{OFF})

PARAMETER MEASUREMENT INFORMATION (continued)



- All input pulses are supplied by generators having the following characteristics: $\text{PRR} \leq 10\ \text{MHz}$, $Z_O = 50\ \Omega$, $t_r < 5\ \text{ns}$, $t_f < 5\ \text{ns}$.
- C_L includes probe and jig capacitance.

Figure 19. Break-Before-Make Time (t_{BBM})




Figure 20. Bandwidth (BW)

PARAMETER MEASUREMENT INFORMATION (continued)




Figure 21. OFF Isolation (O_{ISO})






Figure 22. Crosstalk (X_{TALK})

PARAMETER MEASUREMENT INFORMATION (continued)



- A. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10$ MHz, $Z_O = 50 \Omega$, $t_r < 5$ ns, $t_f < 5$ ns.
- B. C_L includes probe and jig capacitance.

Figure 23. Charge Injection (Q_C)



- A. C_L includes probe and jig capacitance.

Figure 24. Total Harmonic Distortion (THD)

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
TS5A12301EYFPR	ACTIVE	DSBGA	YFP	6	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.


Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


TAPE AND REEL INFORMATION



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadra
TS5A12301EYFPR	DSBGA	YFP	6	3000	180.0	8.4	0.9	1.3	0.6	4.0	8.0	Q1

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TS5A12301EYFPR	DSBGA	YFP	6	3000	220.0	220.0	34.0

MECHANICAL DATA

YFP (R-XBGA-N6)

DIE-SIZE BALL GRID ARRAY



- NOTES:
- All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - This drawing is subject to change without notice.
 - NanoFree™ package configuration.
 - This is a Pb-free solder ball design.

NanoFree is a trademark of Texas Instruments.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2008, Texas Instruments Incorporated