

Ultra High Precision Z-Foil Surface Mount Power Resistor in TO-220 Configuration with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$, PCR of $4 \text{ ppm}/\text{W}$ and Load Life Stability of $\pm 0.005 \%$ (50 ppm)



Any value at any tolerance available within resistance range

INTRODUCTION

The Z-Foil Technology provides a significant reduction of the resistive component's sensitivity to ambient temperature variations (TCR) and applied power changes (PCR).

Model VPR221SZ is a 4 lead kelvin connected surface mount device which provides high rated power, excellent load life stability, low Temperature Coefficient (TCR) and low Power Coefficient (PCR) - all in one resistor. $\pm 0.05 \text{ ppm}/^\circ\text{C}$. Absolute TCR removes error due to temperature gradients.

By taking advantage of the overall stability and reliability of Vishay Bulk Metal® Z-Foil resistors, designers can significantly reduce circuit errors and greatly improve overall circuit performances.

Our Application Engineering Department is available to advise and make recommendations. For non-standard technical requirements and special applications, please contact us.

TABLE 1 - TCR AND TOLERANCE		
RESISTANCE RANGE (Ω)	TIGHTEST RESISTANCE TOLERANCE	TYPICAL TCR AND MAX. SPREAD ¹⁾
0.5 to < 1	$\pm 0.05 \%$	$\pm 0.2 \text{ ppm}/^\circ\text{C} \pm 2.8 \text{ ppm}/^\circ\text{C}$
1 to < 10	$\pm 0.02 \%$	$\pm 0.2 \text{ ppm}/^\circ\text{C} \pm 2.3 \text{ ppm}/^\circ\text{C}$
10 to 500	$\pm 0.01 \%$	$\pm 0.2 \text{ ppm}/^\circ\text{C} \pm 1.8 \text{ ppm}/^\circ\text{C}$

Notes

- MIL-Range (- 55 °C to + 125 °C, + 25 °C Ref.)
- Contact Applications Engineering for other available values

FEATURES

- Temperature Coefficient of Resistance (TCR):
 - $\pm 0.05 \text{ ppm}/^\circ\text{C}$ typical (0 °C to + 60 °C)
 - $\pm 0.2 \text{ ppm}/^\circ\text{C}$ typical (- 55 °C to + 125 °C, + 25 °C Ref.) (see table 1)
- Tolerance: to $\pm 0.01 \%$
- Power Coefficient "ΔR due to self heating": 4 ppm/W typical
- Rated Power: 8 W chassis mounted (MIL-PRF-39009)
- Load Life Stability: to $\pm 0.005 \%$ at 25 °C for 2000 hours, at 1.5 W
- Resistance Range: 0.5 Ω to 500 Ω
- Electrostatic Discharge (ESD) above 25 000 Volts
- Short Time Overload $\leq 0.001 \%$ (10 ppm)
- Non Inductive, Non Capacitive Design
- Rise Time: 1 ns without ringing
- Current Noise < - 40 dB
- Thermal EMF: 0.05 $\mu\text{V}/^\circ\text{C}$ typical
- Voltage Coefficient < 0.1 ppm/V
- Non Inductive: < 0.08 μH
- Non Hot Spot Design
- Terminal Finishes available: Lead (Pb)-free Tin/Lead Alloy
- Any value available within resistance range (e.g. 1K234)
- Prototype samples available from 48 hours. For more information, please contact foil@vishay.com
- For better performances please contact us



APPLICATIONS

- Automatic Test Equipment (ATE)
- High Precision Instrumentation
- Electron Beam application
- Current Sensing applications
- Pulse applications
- Military
- Power amplifier
- Power supplies





FIGURE 1- POWER DERATING CURVE








* Pb containing terminations are not RoHS compliant, exemptions may apply



VPR221SZ (Z-Foil)

Ultra High Precision Z-Foil Surface Mount Power Resistor Vishay Foil Resistors in TO-220 Configuration with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$, PCR of $4 \text{ ppm}/\text{W}$ and Load Life Stability of $\pm 0.005 \%$ (50 ppm)



VPR221SZ (Z-Foil)



Vishay Foil Resistors Ultra High Precision Z-Foil Surface Mount Power Resistor in TO-220 Configuration with TCR of ± 0.05 ppm/°C, PCR of ± 4 ppm/W and Load Life Stability of ± 0.005 % (50 ppm)

TABLE 2 - SPECIFICATIONS	
Power Rating at + 25 °C	8 W or 3 A ¹⁾ on heat sink ²⁾ 1.5 watts in free air Further derating not necessary.
Current Noise	< 0.010 μ V (rms)/V of applied voltage (- 40 dB)
High Frequency Operation Rise Time Inductance ³⁾ (L) Capacitance (C)	0.2 ns at 1 W 0.1 μ H maximum: 0.03 μ H typical 1.0 pF maximum: 0.5 pF typical
Voltage Coefficient ⁴⁾	< 0.1 ppm/V
Operating Temperature Range	- 55 °C to + 150 °C
Maximum Working Voltage	300 V, Not to exceed power rating
Thermal EMF ⁵⁾	0.15 μ V/°C maximum (lead effect)
Weight	1.2 g maximum

Notes

1. Whichever is lower.
2. Heat sink chassis dimensions are requirements per MIL-R-39009/1B:

DIMENSIONS	inches	mm
L	6.00	152.4
W	4.00	101.6
H	2.00	50.8
T	0.04	1.0

3. Inductance (L) mainly due to the leads.
4. The resolution limit of existing test requirement (within the measurement capability of the equipment, "essentially zero").
5. μ V/°C relates to EMF due to lead temperature difference.

TABLE 3 - PERFORMANCE SPECIFICATIONS ¹⁾ MIL-PRF 39009			
TEST OR CONDITION	MIL-PRF 39009	TYPICAL Δ R	MAXIMUM Δ R
Low temperature storage 24 hours at - 55 °C	± 0.3 % + 0.01 Ω	± 0.001 % (10 ppm)	± 0.002 % (20 ppm)
Dielectric withstanding voltage 300 V AC at Atm	± 0.2 % + 0.01 Ω	± 0.001 % (10 ppm)	± 0.002 % (20 ppm)
Dielectric withstanding voltage 200 V AC at Brm	± 0.2 % + 0.01 Ω	± 0.001 % (10 ppm)	± 0.002 % (20 ppm)
Insulation resistance	> 10 ⁴ M Ω		> 10 ⁴ M Ω
Low temperature operation	± 0.3 % + 0.01 Ω	± 0.002 % (20 ppm)	± 0.008 % (80 ppm)
Short time overload 5 x rated power for 5 seconds (in air)	± 0.3 % + 0.01 Ω	± 0.001 % (10 ppm)	± 0.002 % (20 ppm)
Moisture resistance + 65 °C to - 10 °C, 90 to 98 Rh, 10 days	± 0.5 % + 0.01 Ω	± 0.005 % (50 ppm)	± 0.015 % (150 ppm)
Terminal Strength	± 0.2 % + 0.01 Ω	± 0.001 % (10 ppm)	± 0.002 % (20 ppm)
Load life 8 W at + 25 °C, 2000 hours with heat sink	± 1.0 % + 0.01 Ω	± 0.005 % (50 ppm)	± 0.015 % (150 ppm)
Load life 1.5 W at + 25 °C for 2000 hours in free air	± 1.0 % + 0.01 Ω	± 0.005 % (50 ppm)	± 0.015 % (150 ppm)
High temperature exposure + 150 °C	± 1.0 % + 0.05 Ω	± 0.005 % (50 ppm)	± 0.01 % (100 ppm)

Note

1. Measurement error ± 0.001 %




VPR221SZ (Z-Foil)

Ultra High Precision Z-Foil Surface Mount Power Resistor Vishay Foil Resistors
 in TO-220 Configuration with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$, PCR
 of $4 \text{ ppm}/\text{W}$ and Load Life Stability of $\pm 0.005 \%$ (50 ppm)

TABLE 4 - GLOBAL PART NUMBER INFORMATION

NEW GLOBAL PART NUMBER: Y2123420R220T9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y2123 420R220 T 9 L:

TYPE: VPR221SZ
 VALUE: 420.22 Ω
 ABSOLUTE TOLERANCE: $\pm 0.01 \%$
 TERMINATION: Lead (Pb)-free
 PACKAGING: Bulk

HISTORICAL PART NUMBER: VPR221SZ T 420R22 TCR0.2 T B (will continue to be used)

VPR221SZ	T	420R22	TCR0.2	T	B
MODEL	TERMINATION	OHMIC VALUE	TCR CHARACTERISTIC	ABSOLUTE TOLERANCE	PACKAGING
	T = Lead (Pb)-free none = Tin/Lead	420.22 Ω	TCR0.2	T = $\pm 0.01 \%$ Q = $\pm 0.02 \%$ A = $\pm 0.05 \%$ B = $\pm 0.1 \%$ C = $\pm 0.25 \%$ D = $\pm 0.5 \%$ F = $\pm 1.0 \%$	B = Bulk

Note

* For non-standard requests, please contact Application Engineering.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

