

# MC74AC151, MC74ACT151

## 1-of-8 Decoder/Demultiplexer

The MC74AC151/74ACT151 is a high-speed 8-input digital multiplexer. It provides, in one package, the ability to select one line of data from up to eight sources. The MC74AC151/74ACT151 can be used as a universal function generator to generate any logic function of four variables. Both true and complementary outputs are provided.

- Outputs Source/Sink 24 mA
- 'ACT151 Has TTL Compatible Inputs




Figure 1. Pinout: 16-Lead Packages Conductors (Top View)

### PIN ASSIGNMENT

| PIN                            | FUNCTION             |
|--------------------------------|----------------------|
| I <sub>0</sub> –I <sub>7</sub> | Data Inputs          |
| S <sub>0</sub> –S <sub>2</sub> | Select Inputs        |
| $\bar{E}$                      | Enable Input         |
| Z                              | Data Output          |
| $\bar{Z}$                      | Inverted Data Output |

### TRUTH TABLE


| Inputs    |                |                |                | Outputs        |                |
|-----------|----------------|----------------|----------------|----------------|----------------|
| $\bar{E}$ | S <sub>2</sub> | S <sub>1</sub> | S <sub>0</sub> | Z              | $\bar{Z}$      |
| H         | X              | X              | X              | H              | L              |
| L         | L              | L              | L              | I <sub>0</sub> | I <sub>0</sub> |
| L         | L              | L              | H              | I <sub>1</sub> | I <sub>1</sub> |
| L         | L              | H              | L              | I <sub>2</sub> | I <sub>2</sub> |
| L         | L              | H              | H              | I <sub>3</sub> | I <sub>3</sub> |
| L         | H              | L              | L              | I <sub>4</sub> | I <sub>4</sub> |
| L         | H              | L              | H              | I <sub>5</sub> | I <sub>5</sub> |
| L         | H              | H              | L              | I <sub>6</sub> | I <sub>6</sub> |
| L         | H              | H              | H              | I <sub>7</sub> | I <sub>7</sub> |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial



ON Semiconductor™


<http://onsemi.com>




DIP-16  
N SUFFIX  
CASE 648



SO-16  
D SUFFIX  
CASE 751B



TSSOP-16  
DT SUFFIX  
CASE 948F



EIAJ-16  
M SUFFIX  
CASE 966

### ORDERING INFORMATION

| Device         | Package  | Shipping         |
|----------------|----------|------------------|
| MC74AC151N     | PDIP-16  | 25 Units/Rail    |
| MC74ACT151N    | PDIP-16  | 25 Units/Rail    |
| MC74AC151D     | SOIC-16  | 48 Units/Rail    |
| MC74ACT151D    | SOIC-16  | 48 Units/Rail    |
| MC74AC151DR2   | SOIC-16  | 2500 Tape & Reel |
| MC74ACT151DR2  | SOIC-16  | 2500 Tape & Reel |
| MC74AC151DT    | TSSOP-16 | 96 Units/Rail    |
| MC74ACT151DT   | TSSOP-16 | 96 Units/Rail    |
| MC74AC151DTR2  | TSSOP-16 | 2500 Tape & Reel |
| MC74ACT151DTR2 | TSSOP-16 | 2500 Tape & Reel |
| MC74AC151M     | EIAJ-16  | 50 Units/Rail    |
| MC74ACT151M    | EIAJ-16  | 50 Units/Rail    |

### DEVICE MARKING INFORMATION

See general marking information in the device marking section on page 7 of this data sheet.

## MC74AC151, MC74ACT151




Figure 2. Logic Symbol

### FUNCTIONAL DESCRIPTION

The MC74AC151/74ACT151 is a logic implementation of a single pole, 8-position switch with the switch position controlled by the state of three Select inputs,  $S_0$ ,  $S_1$ ,  $S_2$ . Both true and complementary outputs are provided. The Enable input ( $\bar{E}$ ) is active LOW. When it is not activated, the complementary output is HIGH and the true output is LOW regardless of all other inputs. The logic function provided at the output is:

$$Z = \bar{E} \cdot (I_0 \cdot \bar{S}_0 \cdot \bar{S}_1 \cdot \bar{S}_2 + I_1 \cdot \bar{S}_0 \cdot \bar{S}_1 \cdot \bar{S}_2 + I_2 \cdot \bar{S}_0 \cdot S_1 \cdot \bar{S}_2 + I_3 \cdot \bar{S}_0 \cdot S_1 \cdot \bar{S}_2 + I_4 \cdot \bar{S}_0 \cdot \bar{S}_1 \cdot S_2 + I_5 \cdot \bar{S}_0 \cdot \bar{S}_1 \cdot S_2 + I_6 \cdot \bar{S}_0 \cdot S_1 \cdot S_2 + I_7 \cdot \bar{S}_0 \cdot S_1 \cdot S_2)$$

The MC74AC151/74ACT151 provides the ability, in one package, to select from eight sources of data or control information. By proper manipulation of the inputs, the MC74AC151/74ACT151 can provide any logic function of four variables and its complement.




Figure 3. Logic Diagram

## MC74AC151, MC74ACT151

### MAXIMUM RATINGS\*

| Symbol    | Parameter                                 | Value                  | Unit |
|-----------|-------------------------------------------|------------------------|------|
| $V_{CC}$  | DC Supply Voltage (Referenced to GND)     | -0.5 to +7.0           | V    |
| $V_{IN}$  | DC Input Voltage (Referenced to GND)      | -0.5 to $V_{CC} + 0.5$ | V    |
| $V_{OUT}$ | DC Output Voltage (Referenced to GND)     | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{IN}$  | DC Input Current, per Pin                 | $\pm 20$               | mA   |
| $I_{OUT}$ | DC Output Sink/Source Current, per Pin    | $\pm 50$               | mA   |
| $I_{CC}$  | DC $V_{CC}$ or GND Current per Output Pin | $\pm 50$               | mA   |
| $T_{stg}$ | Storage Temperature                       | -65 to +150            | °C   |

\*Maximum Ratings are those values beyond which damage to the device may occur. Functional operation should be restricted to the Recommended Operating Conditions.

### RECOMMENDED OPERATING CONDITIONS

| Symbol            | Parameter                                                               | Min                     | Typ | Max      | Unit |
|-------------------|-------------------------------------------------------------------------|-------------------------|-----|----------|------|
| $V_{CC}$          | Supply Voltage                                                          | 'AC                     | 2.0 | 5.0      | V    |
|                   |                                                                         | 'ACT                    | 4.5 | 5.0      |      |
| $V_{IN}, V_{OUT}$ | DC Input Voltage, Output Voltage (Ref. to GND)                          | 0                       | -   | $V_{CC}$ | V    |
| $t_r, t_f$        | Input Rise and Fall Time (Note 1)<br>'AC Devices except Schmitt Inputs  | $V_{CC} @ 3.0\text{ V}$ | -   | 150      | ns/V |
|                   |                                                                         | $V_{CC} @ 4.5\text{ V}$ | -   | 40       |      |
|                   |                                                                         | $V_{CC} @ 5.5\text{ V}$ | -   | 25       |      |
| $t_r, t_f$        | Input Rise and Fall Time (Note 2)<br>'ACT Devices except Schmitt Inputs | $V_{CC} @ 4.5\text{ V}$ | -   | 10       | ns/V |
|                   |                                                                         | $V_{CC} @ 5.5\text{ V}$ | -   | 8.0      |      |
| $T_J$             | Junction Temperature (PDIP)                                             | -                       | -   | 140      | °C   |
| $T_A$             | Operating Ambient Temperature Range                                     | -40                     | 25  | 85       | °C   |
| $I_{OH}$          | Output Current - High                                                   | -                       | -   | -24      | mA   |
| $I_{OL}$          | Output Current - Low                                                    | -                       | -   | 24       | mA   |

1.  $V_{IN}$  from 30% to 70%  $V_{CC}$ ; see individual Data Sheets for devices that differ from the typical input rise and fall times.
2.  $V_{IN}$  from 0.8 V to 2.0 V; see individual Data Sheets for devices that differ from the typical input rise and fall times.

# MC74AC151, MC74ACT151

## DC CHARACTERISTICS

| Symbol           | Parameter                            | V <sub>CC</sub><br>(V) | 74AC                   |                   | 74AC                                  | Unit | Conditions                                                                                          |
|------------------|--------------------------------------|------------------------|------------------------|-------------------|---------------------------------------|------|-----------------------------------------------------------------------------------------------------|
|                  |                                      |                        | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> =<br>–40°C to<br>+85°C |      |                                                                                                     |
|                  |                                      |                        | Typ                    | Guaranteed Limits |                                       |      |                                                                                                     |
| V <sub>IH</sub>  | Minimum High Level<br>Input Voltage  | 3.0                    | 1.5                    | 2.1               | 2.1                                   | V    | V <sub>OUT</sub> = 0.1 V<br>or V <sub>CC</sub> – 0.1 V                                              |
|                  |                                      | 4.5                    | 2.25                   | 3.15              | 3.15                                  |      |                                                                                                     |
|                  |                                      | 5.5                    | 2.75                   | 3.85              | 3.85                                  |      |                                                                                                     |
| V <sub>IL</sub>  | Maximum Low Level<br>Input Voltage   | 3.0                    | 1.5                    | 0.9               | 0.9                                   | V    | V <sub>OUT</sub> = 0.1 V<br>or V <sub>CC</sub> – 0.1 V                                              |
|                  |                                      | 4.5                    | 2.25                   | 1.35              | 1.35                                  |      |                                                                                                     |
|                  |                                      | 5.5                    | 2.75                   | 1.65              | 1.65                                  |      |                                                                                                     |
| V <sub>OH</sub>  | Minimum High Level<br>Output Voltage | 3.0                    | 2.99                   | 2.9               | 2.9                                   | V    | I <sub>OUT</sub> = –50 μA                                                                           |
|                  |                                      | 4.5                    | 4.49                   | 4.4               | 4.4                                   |      |                                                                                                     |
|                  |                                      | 5.5                    | 5.49                   | 5.4               | 5.4                                   |      |                                                                                                     |
|                  |                                      | 3.0                    | –                      | 2.56              | 2.46                                  | V    | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>–12 mA<br>I <sub>OH</sub> –24 mA<br>–24 mA |
|                  |                                      | 4.5                    | –                      | 3.86              | 3.76                                  |      |                                                                                                     |
|                  |                                      | 5.5                    | –                      | 4.86              | 4.76                                  |      |                                                                                                     |
| V <sub>OL</sub>  | Maximum Low Level<br>Output Voltage  | 3.0                    | 0.002                  | 0.1               | 0.1                                   | V    | I <sub>OUT</sub> = 50 μA                                                                            |
|                  |                                      | 4.5                    | 0.001                  | 0.1               | 0.1                                   |      |                                                                                                     |
|                  |                                      | 5.5                    | 0.001                  | 0.1               | 0.1                                   |      |                                                                                                     |
|                  |                                      | 3.0                    | –                      | 0.36              | 0.44                                  | V    | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>12 mA<br>I <sub>OL</sub> 24 mA<br>24 mA    |
|                  |                                      | 4.5                    | –                      | 0.36              | 0.44                                  |      |                                                                                                     |
|                  |                                      | 5.5                    | –                      | 0.36              | 0.44                                  |      |                                                                                                     |
| I <sub>IN</sub>  | Maximum Input<br>Leakage Current     | 5.5                    | –                      | ±0.1              | ±1.0                                  | μA   | V <sub>I</sub> = V <sub>CC</sub> , GND                                                              |
| I <sub>OLD</sub> | †Minimum Dynamic<br>Output Current   | 5.5                    | –                      | –                 | 75                                    | mA   | V <sub>OLD</sub> = 1.65 V Max                                                                       |
| I <sub>OHD</sub> |                                      | 5.5                    | –                      | –                 | –75                                   | mA   | V <sub>OHD</sub> = 3.85 V Min                                                                       |
| I <sub>CC</sub>  | Maximum Quiescent<br>Supply Current  | 5.5                    | –                      | 8.0               | 80                                    | μA   | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                            |

\*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

NOTE: I<sub>IN</sub> and I<sub>CC</sub> @ 3.0 V are guaranteed to be less than or equal to the respective limit @ 5.5 V V<sub>CC</sub>.

# MC74AC151, MC74ACT151

**AC CHARACTERISTICS** (For Figures and Waveforms – See Section 3 of the ON Semiconductor FACT Data Book, DL138/D)

| Symbol           | Parameter                                     | V <sub>CC</sub> *<br>(V) | 74AC                                             |             |              | 74AC                                                      |              | Unit | Fig. No. |
|------------------|-----------------------------------------------|--------------------------|--------------------------------------------------|-------------|--------------|-----------------------------------------------------------|--------------|------|----------|
|                  |                                               |                          | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |             |              | T <sub>A</sub> = –40°C to +85°C<br>C <sub>L</sub> = 50 pF |              |      |          |
|                  |                                               |                          | Min                                              | Typ         | Max          | Min                                                       | Max          |      |          |
| t <sub>PLH</sub> | Propagation Delay<br>S <sub>n</sub> to Z or Z | 3.3<br>5.0               | 3.0<br>2.5                                       | 11.5<br>8.5 | 18.0<br>13.0 | 3.0<br>2.0                                                | 20.0<br>15.0 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>S <sub>n</sub> to Z or Z | 3.3<br>5.0               | 2.5<br>2.0                                       | 12<br>8.5   | 18.0<br>13.0 | 2.5<br>1.5                                                | 20.0<br>15.0 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>E to Z or Z              | 3.3<br>5.0               | 2.5<br>2.0                                       | 8.0<br>6.0  | 13.0<br>10.0 | 2.0<br>1.5                                                | 14.0<br>11.0 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>E to Z or Z              | 3.3<br>5.0               | 1.5<br>1.5                                       | 8.5<br>6.5  | 13.0<br>10.0 | 1.5<br>1.5                                                | 14.0<br>11.0 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>I <sub>n</sub> to Z or Z | 3.3<br>5.0               | 2.5<br>1.5                                       | 9.5<br>7.0  | 14.0<br>10.5 | 2.0<br>1.5                                                | 15.5<br>11.0 | ns   | 3–5      |
| t <sub>PHL</sub> | Propagation Delay<br>I <sub>n</sub> to Z or Z | 3.3<br>5.0               | 2.5<br>1.5                                       | 9.5<br>7.0  | 15.0<br>11.0 | 2.0<br>1.5                                                | 16.0<br>12.0 | ns   | 3–5      |

\*Voltage Range 3.3 V is 3.3 V ± 0.3 V

\*Voltage Range 5.0 V is 5.0 V ± 0.5 V

## DC CHARACTERISTICS

| Symbol            | Parameter                              | V <sub>CC</sub><br>(V) | 74ACT                  |                   | 74ACT                                 | Unit | Conditions                                                                                |
|-------------------|----------------------------------------|------------------------|------------------------|-------------------|---------------------------------------|------|-------------------------------------------------------------------------------------------|
|                   |                                        |                        | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> =<br>–40°C to<br>+85°C |      |                                                                                           |
|                   |                                        |                        | Typ                    | Guaranteed Limits |                                       |      |                                                                                           |
| V <sub>IH</sub>   | Minimum High Level Input Voltage       | 4.5                    | 1.5                    | 2.0               | 2.0                                   | V    | V <sub>OUT</sub> = 0.1 V<br>or V <sub>CC</sub> – 0.1 V                                    |
|                   |                                        | 5.5                    | 1.5                    | 2.0               | 2.0                                   |      |                                                                                           |
| V <sub>IL</sub>   | Maximum Low Level Input Voltage        | 4.5                    | 1.5                    | 0.8               | 0.8                                   | V    | V <sub>OUT</sub> = 0.1 V<br>or V <sub>CC</sub> – 0.1 V                                    |
|                   |                                        | 5.5                    | 1.5                    | 0.8               | 0.8                                   |      |                                                                                           |
| V <sub>OH</sub>   | Minimum High Level Output Voltage      | 4.5                    | 4.49                   | 4.4               | 4.4                                   | V    | I <sub>OUT</sub> = –50 μA                                                                 |
|                   |                                        | 5.5                    | 5.49                   | 5.4               | 5.4                                   |      |                                                                                           |
|                   |                                        | 4.5                    | –                      | 3.86              | 3.76                                  | V    | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>I <sub>OH</sub> –24 mA<br>–24 mA |
|                   |                                        | 5.5                    | –                      | 4.86              | 4.76                                  |      |                                                                                           |
| V <sub>OL</sub>   | Maximum Low Level Output Voltage       | 4.5                    | 0.001                  | 0.1               | 0.1                                   | V    | I <sub>OUT</sub> = 50 μA                                                                  |
|                   |                                        | 5.5                    | 0.001                  | 0.1               | 0.1                                   |      |                                                                                           |
|                   |                                        | 4.5                    | –                      | 0.36              | 0.44                                  | V    | *V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub><br>I <sub>OL</sub> 24 mA<br>24 mA   |
|                   |                                        | 5.5                    | –                      | 0.36              | 0.44                                  |      |                                                                                           |
| I <sub>IN</sub>   | Maximum Input Leakage Current          | 5.5                    | –                      | ±0.1              | ±1.0                                  | μA   | V <sub>I</sub> = V <sub>CC</sub> , GND                                                    |
| ΔI <sub>CCT</sub> | Additional Max. I <sub>CC</sub> /Input | 5.5                    | 0.6                    | –                 | 1.5                                   | mA   | V <sub>I</sub> = V <sub>CC</sub> – 2.1 V                                                  |
| I <sub>OLD</sub>  | †Minimum Dynamic Output Current        | 5.5                    | –                      | –                 | 75                                    | mA   | V <sub>OLD</sub> = 1.65 V Max                                                             |
| I <sub>OHD</sub>  |                                        | 5.5                    | –                      | –                 | –75                                   | mA   | V <sub>OHD</sub> = 3.85 V Min                                                             |
| I <sub>CC</sub>   | Maximum Quiescent Supply Current       | 5.5                    | –                      | 8.0               | 80                                    | μA   | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                  |

\*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

## MC74AC151, MC74ACT151

**AC CHARACTERISTICS** (For Figures and Waveforms – See Section 3 of the ON Semiconductor FACT Data Book, DL138/D)

| Symbol           | Parameter                                        | V <sub>CC</sub> *<br>(V) | 74ACT                                            |     |      | 74ACT                                                        |      | Unit | Fig. No. |
|------------------|--------------------------------------------------|--------------------------|--------------------------------------------------|-----|------|--------------------------------------------------------------|------|------|----------|
|                  |                                                  |                          | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |     |      | T <sub>A</sub> = –40°C<br>to +85°C<br>C <sub>L</sub> = 50 pF |      |      |          |
|                  |                                                  |                          | Min                                              | Typ | Max  | Min                                                          | Max  |      |          |
| t <sub>PLH</sub> | Propagation Delay<br>S <sub>n</sub> to Z         | 5.0                      | 3.5                                              | –   | 15.5 | 3.0                                                          | 17.0 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>S <sub>n</sub> to Z         | 5.0                      | 3.5                                              | –   | 15.5 | 3.0                                                          | 16.5 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>S <sub>n</sub> to $\bar{Z}$ | 5.0                      | 3.5                                              | –   | 15   | 3.0                                                          | 16.5 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>S <sub>n</sub> to $\bar{Z}$ | 5.0                      | 4.0                                              | –   | 16.5 | 3.5                                                          | 18.5 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>$\bar{E}$ to Z              | 5.0                      | 2.5                                              | –   | 9.5  | 2.5                                                          | 10.0 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>$\bar{E}$ to Z              | 5.0                      | 2.5                                              | –   | 9.0  | 2.5                                                          | 10.0 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>$\bar{E}$ to $\bar{Z}$      | 5.0                      | 2.5                                              | –   | 8.5  | 2.5                                                          | 9.5  | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>$\bar{E}$ to $\bar{Z}$      | 5.0                      | 3.0                                              | –   | 10.0 | 2.5                                                          | 10.5 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>I <sub>n</sub> to Z         | 5.0                      | 3.5                                              | –   | 11.5 | 3.0                                                          | 12.5 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>I <sub>n</sub> to Z         | 5.0                      | 3.5                                              | –   | 12.0 | 3.0                                                          | 13.5 | ns   | 3–6      |
| t <sub>PLH</sub> | Propagation Delay<br>I <sub>n</sub> to $\bar{Z}$ | 5.0                      | 3.5                                              | –   | 12.0 | 3.0                                                          | 13.0 | ns   | 3–6      |
| t <sub>PHL</sub> | Propagation Delay<br>I <sub>n</sub> to $\bar{Z}$ | 5.0                      | 4.0                                              | –   | 12.5 | 3.0                                                          | 14.0 | ns   | 3–6      |


\*Voltage Range 5.0 V is 5.0 V ± 0.5 V

### CAPACITANCE

| Symbol          | Parameter                     | Value<br>Typ | Unit | Test Conditions         |
|-----------------|-------------------------------|--------------|------|-------------------------|
| C <sub>IN</sub> | Input Capacitance             | 4.5          | pF   | V <sub>CC</sub> = 5.0 V |
| C <sub>PD</sub> | Power Dissipation Capacitance | 70           | pF   | V <sub>CC</sub> = 5.0 V |

# MC74AC151, MC74ACT151

## MARKING DIAGRAMS



A = Assembly Location  
 WL, L = Wafer Lot  
 YY, Y = Year  
 WW, W = Work Week

# MC74AC151, MC74ACT151

## PACKAGE DIMENSIONS


### PDIP-16

#### N SUFFIX

16 PIN PLASTIC DIP PACKAGE

CASE 648-08

ISSUE R



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.740     | 0.770 | 18.80       | 19.55 |
| B   | 0.250     | 0.270 | 6.35        | 6.85  |
| C   | 0.145     | 0.175 | 3.69        | 4.44  |
| D   | 0.015     | 0.021 | 0.39        | 0.53  |
| F   | 0.040     | 0.70  | 1.02        | 1.77  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| H   | 0.050 BSC |       | 1.27 BSC    |       |
| J   | 0.008     | 0.015 | 0.21        | 0.38  |
| K   | 0.110     | 0.130 | 2.80        | 3.30  |
| L   | 0.295     | 0.305 | 7.50        | 7.74  |
| M   | 0°        | 10°   | 0°          | 10°   |
| S   | 0.020     | 0.040 | 0.51        | 1.01  |


### SO-16

#### D SUFFIX

16 PIN PLASTIC SOIC PACKAGE

CASE 751B-05

ISSUE J



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.


| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |

# MC74AC151, MC74ACT151

## PACKAGE DIMENSIONS

### TSSOP-16 DT SUFFIX

16 PIN PLASTIC TSSOP PACKAGE  
CASE948F-01  
ISSUE O




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| E   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

### EIAJ-16 M SUFFIX 16 PIN PLASTIC EIAJ PACKAGE CASE966-01 ISSUE O



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

| DIM            | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
|                | MIN         | MAX   | MIN       | MAX   |
| A              | ---         | 2.05  | ---       | 0.081 |
| A <sub>1</sub> | 0.05        | 0.20  | 0.002     | 0.008 |
| b              | 0.35        | 0.50  | 0.014     | 0.020 |
| c              | 0.18        | 0.27  | 0.007     | 0.011 |
| D              | 9.90        | 10.50 | 0.390     | 0.413 |
| E              | 5.10        | 5.45  | 0.201     | 0.215 |
| e              | 1.27 BSC    |       | 0.050 BSC |       |
| H <sub>E</sub> | 7.40        | 8.20  | 0.291     | 0.323 |
| L              | 0.50        | 0.85  | 0.020     | 0.033 |
| L <sub>E</sub> | 1.10        | 1.50  | 0.043     | 0.059 |
| M              | 0°          | 10°   | 0°        | 10°   |
| Q <sub>1</sub> | 0.70        | 0.90  | 0.028     | 0.035 |
| Z              | ---         | 0.78  | ---       | 0.031 |

## MC74AC151, MC74ACT151

**OBsolete**  
THIS DEVICE IS OBSOLETE  
PLEASE CONTACT YOUR ON SEMICONDUCTOR  
REPRESENTATIVE FOR INFORMATION

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

#### Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative