



T-1 1/4 Subminiature Lamps

| Line No. | Part No. Wire Lead | Part No. Miniature Flanged | Part No. Bi-Pin | Volts | Amps | M.S.C.P. | Filament Type | Life Hours |
|----------|--------------------|----------------------------|-----------------|-------|-------|----------|---------------|------------|
| 13 | 2135 | 7302 | 7306 | 1.3 | 0.030 | 0.006 | S-2 | 100 |
| 14 | 8631 | 8636 | 7636 | 1.35 | 0.060 | 0.006 | C-2R | 500 |
| 15 | 8655 | 8656 | 7307 | 2.5 | 0.400 | 0.55 | C-2R | 30 |
| 16 | 324 | 8637 | 7637 | 3.0 | 0.190 | 0.25 | C-2R | 350 |
| 17 | 8816 | 7305 | 7308 | 4.5 | 0.285 | 0.80 | C-2R | 100 |
| 18 | 580 | 3582 | 7580 | 5.0 | 0.060 | 0.03 | C-2R | 100,000 |
| 19 | 583 | 3585 | 7583 | 5.0 | 0.060 | 0.05 | C-2R | 100,000 |
| 20 | 515 | 3518 | 7515 | 5.0 | 0.115 | 0.15 | C-2R | 40,000 |
| 21 | 8661 | 8660 | 7660 | 6.0 | 0.040 | 0.06 | C-2R | 1,000 |
| 22 | 2114 | 8541 | 7309 | 6.0 | 0.060 | 0.13 | C-2R | 3,000 |
| 23 | 634 | 8628 | 7628 | 6.0 | 0.200 | 0.63 | C-2R | 1,000 |
| 24 | 8610 | 8551 | 7310 | 6.3 | 0.200 | 0.55 | C-2R | 5,000 |
| 25 | 8608 | 8609 | 7311 | 10.0 | 0.070 | 0.14 | C-2F | 10,000 |
| 26 | 8640 | 8646 | 7646 | 14.0 | 0.080 | 0.50 | C-2F | 1,000 |
| 27 | 8627 | 8632 | 7632 | 28.0 | 0.040 | 0.32 | C-2F | 1,000 |

