



# DB151G THRU DB157G

Single Phase 1.5 AMPS. Glass Passivated Bridge Rectifiers




Voltage Range  
50 to 1000 Volts  
Current  
1.5 Amperes

## Features

- ✧ UL Recognized File # E-96005
- ✧ Glass passivated junction
- ✧ Ideal for printed circuit board
- ✧ Reliable low cost construction utilizing molded plastic technique
- ✧ High surge current capability
- ✧ High temperature soldering guaranteed: 260°C / 10 seconds at 5 lbs., ( 2.3 kg ) tension
- ✧ Small size, simple installation
- ✧ Leads solderable per MIL-STD-202 Method 208

**DB**

**DBS**



Dimensions in inches and (millimeters)

## Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.



Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%


Type Number	Symbol	DB	DB	DB	DB	DB	DB	DB	Units
		151G	152G	153G	154G	155G	156G	157G	
		DBS	DBS	DBS	DBS	DBS	DBS	DBS	
		151G	152G	153G	154G	155G	156G	157G	
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_A = 40^\circ\text{C}$	$I_{(AV)}$	1.5							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	50							A
Maximum Instantaneous Forward Voltage @ 1.5A	$V_F$	1.1							V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=125^\circ\text{C}$	$I_R$	10 500							$\mu\text{A}$ $\mu\text{A}$
Typical Thermal Resistance (Note)	$R\theta_{JA}$ $R\theta_{JL}$	40 15							$^\circ\text{C}/\text{w}$
Operating Temperature Range	$T_J$	-55 to +150							$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150							$^\circ\text{C}$

Note: Thermal resistance from Junction to Ambient and from Junction to Lead Mounted on P.C.B. with 0.4" x 0.4" (10mm x 10mm) Copper Pads.


## RATINGS AND CHARACTERISTIC CURVES (DB151G THRU DB157G)



**FIG. 3- TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT**



**FIG. 4- TYPICAL FORWARD CHARACTERISTICS PER BRIDGE ELEMENT**



**FIG. 5- TYPICAL JUNCTION CAPACITANCE PER BRIDGE ELEMENT**

