

1N6639  
 1N6640  
 1N6641

300 mAmp  
 75-100 Volts  
 4 nsec  
 Computer  
 Switching Diode

**FEATURES**

- Available in axial leaded and surface mount configurations
- Ultra Fast Reverse Recovery Time
- Very low Capacitance
- Metallurgically Bonded
- Non-cavity glass package
- Available as JANTX, JANTXV and JANS per MIL-S-19500/609
- Replacement for 1N4150 Types


**MAXIMUM RATINGS @ 25°C**

Type Number	Reverse Voltage	Working Peak Reverse Voltage	Operating Current (see note 1)	Peak Forward Surge Current (see note 2)	Thermal Resistance Junction to Lead (L=375")	Thermal Resistance Junction to Case	Operating and Storage Temperature
Part Numbers	V <sub>BR</sub>	V <sub>RWM</sub>	I <sub>O</sub>	I <sub>FSM</sub>	R <sub>θJL</sub>	R <sub>θJC</sub>	T <sub>OP</sub> & T <sub>stg</sub>
	Volts	Volts	mA	Amps	°C/W	°C/W	°C
1N6639	100	75	300	2.5	160	50	-65 to +175
1N6639US	100	75	300	2.5	160	50	-65 to +175
1N6640	75	50	300	2.5	160	50	-65 to +175
1N6640US	75	50	300	2.5	160	50	-65 to +175
1N6641	75	50	300	2.5	160	50	-65 to +175
1N6641US	75	50	300	2.5	160	50	-65 to +175

**MECHANICAL CHARACTERISTICS**


CASE STYLE: Axial Leaded

CASE: Voidless Hermetically Sealed Hard Glass  
 LEAD: Solder dipped Copper Clad Steel  
 MARKING: Body Painted, Alpha Numeric  
 POLARITY: Cathode Band



	INCHES	MILLIMETERS
A	1.0 MIN	25.4 MIN
B	.160 MAX	4.06 MAX
C	Ø.020±.002	Ø.51±.03
D	Ø.075 MAX	Ø.190 MAX

1N6638US, 1N6642US, 1N6643US



	INCHES MAX/MIN	MILLIMETERS MAX/MIN
A	.185/.165	4.699/4.191
B	.028/.019	.711/.493
C	---/.003	---/.076
D	.075/.070	1.905/1.778

CASE STYLE: Surface Mount-US

END CAP MATERIAL: Solid Silver  
 END CAP STYLE: Square  
 POLARITY: Cathode Dot on End Cap

**ELECTRICAL CHARACTERISTICS @ 25°C**

Type Number	Maximum Forward Voltage V <sub>F</sub> @I <sub>F</sub>		Maximum D.C. Reverse Current I <sub>R</sub>			
	V@ 200mA	V@ 500mA	V <sub>R</sub> =75V T <sub>A</sub> =25°C nA	V <sub>R</sub> =50V T <sub>A</sub> =25°C nA	V <sub>R</sub> =75V T <sub>A</sub> =150°C µA	V <sub>R</sub> =50V T <sub>A</sub> =150°C µA
1N6639		1.2V	100		100	
1N6639US		1.2V	100		100	
1N6640	1.0V			100		100
1N6640US	1.0V			100		100
1N6641	1.1			100		100
1N6641US	1.1			100		100

Type Number	Reverse Recovery Time (note 3)	Maximum Forward Recovery Voltage and Time I <sub>F</sub> =50mA, t <sub>r</sub> = 1ns		Maximum Junction Capacitance f=1MHz V <sub>sig</sub> =50mV(p-p)	
		V <sub>fr</sub> Volts	t <sub>fr</sub> ns	V <sub>R</sub> =0V pf	V <sub>R</sub> = 10 V pf
1N6639	4	5.0	10	2.5	
1N6639US	4	5.0	10	2.5	
1N6640	4	5.0	10	2.5	
1N6640US	4	5.0	10	2.5	
1N6641	5	5.0	10	3.0	
1N6641US	5	5.0	10	3.0	

Note: (1) At maximum end cap temperature=110°C for US suffix types. Derate at 4.6mA/°C above end cap temperature=110°C. Derate axial types at 3.0mA/°C above ambient temperature temperature=25°C.  
 (2) Test Pulse = 8.3ms, half sine wave  
 (3) I<sub>F</sub> = I<sub>R</sub> = 10mA & I(REC) = 1.0mA