



**FEATURES**

- Bobbin Format
- Up to 2.1A IDC
- 2.2µH to 220µH
- Low DC Resistance
- Surface Mounting
- Compact Size
- Tape and Reel Packaging
- Optional Integral EMI Shield

**DESCRIPTION**

The 2300 series is a range of bobbin wound surface mount inductors designed for use in switching power supply and power line filter circuits. The parts are suitable for any application requiring a high saturation current in a miniature surface mount footprint. Where EMI is a critical factor the devices are available with an integral ferrite EMI shield.

**SELECTION GUIDE (UNSHIELDED TYPES)<sup>1</sup>**

	Nominal Inductance	Inductance Range	DC Resistance	DC Current Continuous <sup>2</sup>	Package Style
Order Code	µH 1kHz 100mV AC	µH 1kHz 100mV AC	Ω  MAX	A  MAX	
<b>232R2</b>	2.2	1.7 - 2.8	0.029	2.10	1
<b>233R3</b>	3.3	2.3 - 3.9	0.044	1.80	
<b>234R7</b>	4.7	3.6 - 6.0	0.068	1.48	
<b>236R8</b>	6.8	5.1 - 8.6	0.102	1.22	
<b>23100</b>	10	7.6 - 12.7	0.138	1.02	
<b>23150</b>	15	11.3 - 18.9	0.210	0.86	
<b>23220</b>	22	16.8 - 28.1	0.285	0.74	
<b>23330</b>	33	24.6 - 41.0	0.497	0.64	
<b>23470</b>	47	34.6 - 57.6	0.683	0.55	
<b>23680</b>	68	51.0 - 85.0	0.838	0.49	
<b>23101</b>	100	74.2 - 124	1.281	0.43	

**SELECTION GUIDE (EMI SHIELDED TYPES)<sup>1</sup>**

	Nominal Inductance	Inductance Range	DC Resistance	DC Current Continuous <sup>2</sup>	Package Style
Order Code	µH 1kHz 100mV AC	µH 1kHz 100mV AC	Ω  MAX	A  MAX	
<b>23S2R2</b>	2.2	1.8 - 3.0	0.025	2.10	2
<b>23S3R3</b>	3.3	2.7 - 4.5	0.031	1.80	
<b>23S4R7</b>	4.7	3.8 - 6.4	0.044	1.60	
<b>23S6R8</b>	6.8	5.2 - 8.6	0.064	1.40	
<b>23S100</b>	10	7.5 - 12.6	0.087	1.18	
<b>23S120</b>	12	9.4 - 15.6	0.107	1.08	
<b>23S150</b>	15	11.4 - 19.0	0.131	0.96	
<b>23S180</b>	18	13.6 - 22.6	0.143	0.88	
<b>23S220</b>	22	16.0 - 26.7	0.175	0.80	
<b>23S270</b>	27	20.0 - 33.3	0.218	0.72	
<b>23S330</b>	33	24.4 - 40.7	0.241	0.65	
<b>23S390</b>	39	29.3 - 48.8	0.370	0.60	
<b>23S470</b>	47	34.6 - 57.7	0.460	0.54	
<b>23S560</b>	56	42.4 - 70.6	0.509	0.50	
<b>23S680</b>	68	50.9 - 84.9	0.641	0.45	
<b>23S101</b>	100	75.8 - 126	0.782	0.37	
<b>23S151</b>	150	112 - 187	1.190	0.30	
<b>23S221</b>	220	167 - 279	2.280	0.25	

**ABSOLUTE MAXIMUM RATINGS**




Operating free air temperature range	-40°C to 85°C
Storage temperature range	-40°C to 125°C

1 Specifications typical at T<sub>A</sub> =25°C  
 2 The maximum DC current is the value at which the inductance falls to 75% of its nominal value or until its temperature rise reaches 40°C, whichever is sooner.  
 3 For tape and reel packaging details refer to datasheet NDC AN002.


# 2300 SERIES

## Bobbin Wound Surface Mount Inductors

### 1 – MECHANICAL DIMENSIONS (UNSHIELDED TYPES)






#### Recommended Footprint Details




Weight: 0.20g  
 Unless otherwise stated all dimensions in inches (mm)  $\pm 0.1$  (0.25).  
 Hatching represents solder pads.

### 2 – MECHANICAL DIMENSIONS (EMI SHIELDED TYPES)



#### Recommended Footprint Details



Weight: 0.34g  
 Unless otherwise stated all dimensions in inches (mm)  $\pm 0.1$  (0.25).  
 Hatching represents solder pads.

C&D Technologies (NCL) Limited reserve the right to alter or improve the specification, internal design or manufacturing process at any time, without notice. Please check with your supplier or visit our web site to ensure that you have the current and complete specification for your product before use.

© C&D Technologies (NCL) Limited 2003

NMP 2300.3

No part of this publication may be copied, transmitted or stored in a retrieval system or reproduced in any way including, but not limited to, photography, photocopy, magnetic or other recording means, without prior written permission from C&D Technologies (NCL) Limited.

Instructions for use are available from [www.cdpoweronline.com](http://www.cdpoweronline.com)

**C&D Technologies (NCL) Ltd**  
 Tanners Drive, Blakelands North  
 Milton Keynes MK14 5BU, England  
 Tel: +44 (0)1908 615232  
 Fax: +44 (0)1908 617545  
 email: [info@cdtechno-ncl.com](mailto:info@cdtechno-ncl.com)

[www.cdpoweronline.com](http://www.cdpoweronline.com)

**C&D Technologies Inc.**  
 3400 E Britannia Drive, Tucson,  
 Arizona 85706, USA  
 Tel: +1 (800) 547-2537  
 Fax: +1 (520) 741-4598  
 email: [sales@cdtechno.com](mailto:sales@cdtechno.com)

**CD TECHNOLOGIES**  
 Power Solutions