


2.3 INCH (58.4)mm) 8 X 8 DOT MATRIX STICK DISPLAY

**HER Red / Green GMA26881C
(BI-COLOR)**

PACKAGE DIMENSIONS



DESCRIPTION

The GMA26881C a common cathode column 8 X 8, bicolor High Efficiency Red / Green dot matrix display. It has a grey face with neutral segment color.

FEATURES

2.3" (58.4mm) character height.
Low power requirement.
Wide 130° viewing angle.
High brightness and contrast
8 X 8 array with X-Y select.
X-Y stackable.

Easy mounting on P.C. board.

NOTE: Dimensions are in mm (inch).
Tolerances are ± 0.25 (0.1) unless otherwise noted.
All pins are 0.5 (.02).

MODEL NUMBER

<u>Part Number</u>	<u>Colour</u>	<u>Description</u>
GMA26881C	HER Red/Green	Common anode row.

(For other color options, contact your local area Sales Office)



2.3 INCH (58.4mm) 8 X 8 DOT MATRIX STICK DISPLAY

ABSOLUTE MAXIMUM RATING ($T_A = 25^\circ\text{C}$ unless otherwise specified)

	HER	Green	Units
Peak forward current per segment (Duty cycle 1/10, 10KHz)	90	90	mA
Continuous IF per segment	25	25	mA
Power dissipation per segment	70*	70*	mW
*Derate linearly from 25°C	0.33	0.33	mW/°C
Reverse voltage VR per segment	5	5	Volts
Operating and storage temperature range	-25°C to +85°C		
Soldering time at 260°C (1/16" below seating plane)	3 sec		

ELECTRO - OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

	HER	Green	Test Condition
Luminous Intensity/Dot Digit average (Typical)	3000ucd	3000ucd	$I_F = 20\text{mA}$
Forward voltage (V_F) typical	2.0V	2.1V	$I_F = 20\text{ mA}$
maximum	2.8V	2.8V	$I_F = 20\text{ mA}$
Peak wavelength (nm)	635nm	570nm	$I_F = 20\text{ mA}$
Spectral line half width (nm)	45nm	30nm	$I_F = 20\text{mA}$
Reverse breakdown voltage V_R	5V	5V	$I_R = 100\text{uA}$


PIN CONNECTION:

GMA26881C

Pin Number	Function	Pin Number	Function
1	Cathode Column 5b	13	Anode Row 4
2	Cathode Column 5a	14	Cathode Column 4a
3	Anode Row 5	15	Cathode Column 4b
4	Cathode Column 6b	16	Anode Row 3
5	Cathode Column 6a	17	Cathode Column 3a
6	Anode Row 6	18	Cathode Column 3b
7	Cathode Column 7b	19	Anode Row 2
8	Cathode Column 7a	20	Cathode Column 2a
9	Anode Row 7	21	Cathode Column 2b
10	Cathode Column 8b	22	Anode Row 1
11	Cathode Column 8a	23	Cathode Column 1a
12	Anode Row 8	24	Cathode Column 1b

Note "a" = High Efficiency Red LED
"b" = Green LED

SCHEMATIC:



2.3 INCH (58.4mm) 8 X 8 DOT MATRIX STICK DISPLAY

GRAPHICAL DETAIL: High Efficiency Red ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY
VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE
(AVERAGE $I_F = 10\text{mA}$)



Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER
SEGMENT VS. A FUNCTION OF AMBIENT
TEMPERATURE.




Fig.6 MAX PEAK CURRENT VS. DUTY CYCLE %
(REFRESH RATE $f = 1\text{ KHz}$)

2.3 INCH (58.4)mm) 8 X 8 DOT MATRIX STICK DISPLAY

GRAPHICAL DETAIL: Green ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT CS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig. 6 MAX PEAK CURRENT VS. DUTY CYCLE %
(REFRESH RATE $f = 1\text{ KHz}$)