

FILAMENT REPLACEMENT LEDs - Ba15d

FEATURES



**245 SERIES**

PACK QUANTITY = 20 PIECES

- Direct replacement for Ba15d
- Bi-Polar - AC/DC Operation
- Internal potting for vibration resistance
- Low heat generation
- Low power requirements

SPECIFICATIONS

Ordering Information & Typical Technical Characteristics (Ta = 25°C)

Mean Time Between Failure = 100,000 Hours. Luminous intensity figures refer to the unmodified discrete LED.

PART NUMBER	COLOUR	LENS	VOLTAGE DC Vopr	CURRENT DC Iopr	LUMINOUS INTENSITY Iv@20mA	WAVE LENGTH λp	OPERATING TEMP Topr	STORAGE TEMP Tstg		
<b>HIGH INTENSITY</b>										
245-532-93-50	Green		Water Clear	28	18	23000	527	-40 ~ +95^	-40 ~ +100	Yes
245-930-93-50	Blue		Water Clear	28	18	7000	470	-40 ~ +95^	-40 ~ +100	Yes
245-997-93-50	Cool White		Water Clear	28	18	14000	*see below	-40 ~ +95^	-40 ~ +100	Yes
245-532-95-50	Green		Water Clear	60	11	23000	527	-40 ~ +95^	-40 ~ +100	Yes
245-930-95-50	Blue		Water Clear	60	11	7000	470	-40 ~ +95^	-40 ~ +100	Yes
245-997-95-50	Cool White		Water Clear	60	11	14000	*see below	-40 ~ +95^	-40 ~ +100	Yes
245-532-87-50	Green		Water Clear	130	5	23000	527	-40 ~ +95^	-40 ~ +100	Yes
245-930-87-50	Blue		Water Clear	130	5	7000	470	-40 ~ +95^	-40 ~ +100	Yes
245-997-87-50	Cool White		Water Clear	130	5	14000	*see below	-40 ~ +95^	-40 ~ +100	Yes
<b>UNITS</b>				<b>Vdc</b>	<b>mA</b>	<b>mcd</b>	<b>nm</b>	<b>°C</b>	<b>°C</b>	



<b>997F-C</b>	*Typical emission colour cool white			
x	0.245	0.361	0.356	0.264
y	0.229	0.385	0.351	0.220

^ = Products must be derated according to the derating information. Each derating graph refers to specific LEDs. Appropriate LED numbers shown. - Refer to page 3.

Intensities (Iv) and colour shades of white (x,y co-ordinates) may vary between LEDs within a batch.

Please note that this product is also available in red and yellow, please see DS089/06 for full details. It is also available at 230Vac/dc, contact our sales department for further details.


How to Order:

website: [www.marl.co.uk](http://www.marl.co.uk) • email: [sales@marl.co.uk](mailto:sales@marl.co.uk) •

• Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.

## 245 SERIES



Dimensions in mm (Typical)  
Not to scale

Colour dot on product denotes LED colour

## TECHNICAL INFORMATION

Lamp Base Style	Series	Metric Equivalent (mm)	Maximum Power Dissipation (mW)
BA15d Filament Base	245	15	1000

## DESIGN CONSIDERATIONS

### Single-Chip LEDs

All devices feature water clear high intensity LEDs as standard. The single chip LED devices have been modified by the removal of the domed portion of the encapsulation (flat-topped) to provide even illumination of switches and annunciators. Non flat topped versions are also available, please contact the sales department for details.

### Product Evaluation

Filament Replacement LEDs have been specifically designed to meet the primary objective of providing improved reliability. As this product range is suitable for both new-build and retro-fit, (sometimes in very old systems), a wide range of illuminated push button switches and lamp holders can be encountered. Due to subjectivity, evaluation of the LED type is recommended, (samples of all standard models are available). Care should be taken to correctly simulate operating ambient light conditions to ensure that the correct device has been selected to maximise viewing characteristics such as viewing angle, colour compatibility and on/off contrast ratio.

### Electro-static Discharge (ESD)

Build up of electrostatic discharge occurs in many situations involving people moving and handling products. The range of possible situations is very diverse but voltage levels as high as several thousand volts can and do arise in many individual situations. When an operator charged up to these levels handles a 'static sensitive device', there is a very probable likelihood that the device will be irreversibly damaged. It is essential that precautions are taken at all stages during manufacture and assembly of these products. Although LEDs were never considered to be static sensitive devices, changes in manufacturing technology and materials used to produce higher intensity products over a large range of the wavelength spectrum have changed this. Marl has an approved system of ESD control from goods in, through production and into final packing and despatch. We recommend all users of LED based products follow the guidelines of BS 100015.

### Power derating

The forward voltage/current value of an LED is dependant upon the ambient temperature of the environment in which it is operated. Therefore, care must be taken to operate the LED at the correct voltage/current values, depending upon the ambient temperature. Consequently, a recommendation regarding operating voltages and currents is given in order to address these temperature effects. This recommendation is termed 'de-rating'.

It is usual for forward voltages and currents to be specified for ambient temperature of 25°C. However, because the values of these qualities vary with temperature, Marl should be contacted if the device is to be operated at a temperature significantly higher than 25°C.

Marl accept no liability for any product that is operated higher than the stated voltage.

Note: All luminous intensity figures refer to the unmodified discrete LED.

### How to Order:

website: [www.marl.co.uk](http://www.marl.co.uk) • email: [sales@marl.co.uk](mailto:sales@marl.co.uk) •


• Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000  
Approved Manufacturer

## DERATING INFORMATION



## ALSO AVAILABLE

Part numbers also available in the 245 Series 1 LED version:

PART NO.	COLOUR	VOLTAGE DC (Vdc) Vopr
245-532-87-38	Green	130 Vac/dc
245-993-89-38	Warm White	50 Vac/dc
245-993-97-50	Warm White	12 Vac/dc
245-997-88-50	White	30 Vac/dc
245-997-91-50	White	230 Vac/dc
UNITS		

The products listed above illustrate all of the options available to order. These products may have custom modifications that alter their operation beyond the generic information contained within this datasheet. Please contact sales for further information.

### How to Order:

website: [www.marl.co.uk](http://www.marl.co.uk) • email: [sales@marl.co.uk](mailto:sales@marl.co.uk) •

• Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000  
Approved Manufacturer