



**APPLICATION NOTES**

1. Materials/Finishes:  
 Shells - See Table II  
 Insulators - High grade rigid dielectric/N.A.  
 Contacts - Copper Alloy/Gold Plated
2. Assembly to be identified with date code, cage code, Glenair P/N, and serial number
3. Electrical Performance:  
 Dielectric withstanding voltage class A and B: 100 VDC  
 All others: 500 VDC  
 Insulation resistance: 5,000 megohms @ 100 VDC  
 Current Rating Standard Density: 7.5 Amps maximum  
 Current Rating High Density: 5 Amps maximum
4. Dimensions B and D taken from inside of shell for Pin/Plug and outside for Socket/Receptacle
5. Metric dimensions (mm) are indicated in parentheses

240-021  
**D-Subminiature Connector**  
 EMI Filtered (MIL-DTL-24308 Type)



**TABLE I: DIMENSIONS**

Shell Size	Number of Contacts		A	B	C	D	E	F	G
	STD	HD	±.015 (0.38)	±.005 (0.13)	±.005 (0.13)	±.005 (0.13)	±.015 (0.38)	Max	Max
1	9P	15P	1.213 (30.8)	.666 (16.9)	.984 (25.0)	.329 (8.4)	.494 (12.5)	.769 (19.5)	.432 (11.0)
	9S	15S	1.213 (30.8)	.643 (16.3)	.984 (25.0)	.311 (7.9)	.494 (12.5)	.769 (19.5)	.432 (11.0)
2	15P	26P	1.541 (39.1)	.994 (25.2)	1.312 (33.3)	.329 (8.4)	.494 (12.5)	1.093 (27.8)	.432 (11.0)
	15S	26S	1.541 (39.1)	.971 (24.7)	1.312 (33.3)	.311 (7.9)	.494 (12.5)	1.635 (41.5)	.432 (11.0)
3	25P	44P	2.088 (53.0)	1.534 (39.0)	1.852 (47.0)	.329 (8.4)	.494 (12.5)	1.635 (41.5)	.432 (11.0)
	25S	44S	2.088 (53.0)	1.511 (38.4)	1.852 (47.0)	.311 (7.9)	.494 (12.5)	2.282 (58.0)	.432 (11.0)
4	37P	62P	2.729 (69.3)	2.182 (55.4)	2.500 (63.5)	.329 (8.4)	.494 (12.5)	2.282 (58.0)	.432 (11.0)
	37S	62S	2.729 (69.3)	2.159 (54.8)	2.500 (63.5)	.311 (7.9)	.494 (12.5)	2.282 (58.0)	.432 (11.0)
5	50P	78P	2.635 (66.9)	2.079 (52.8)	2.406 (61.1)	.441 (11.2)	.605 (15.4)	2.188 (55.6)	.544 (13.8)
	50S	78S	2.635 (66.9)	2.064 (52.4)	2.406 (61.1)	.423 (10.7)	.605 (15.4)	2.188 (55.6)	.544 (13.8)
6	X	104P	2.729 (69.3)	2.212 (56.2)	2.500 (63.5)	.503 (12.8)	.668 (17.0)	2.312 (58.7)	.606 (15.4)
		104S	2.729 (69.3)	2.189 (55.6)	2.500 (63.5)	.486 (12.3)	.668 (17.0)	2.312 (58.7)	.606 (15.4)

**TABLE II: SHELL MATERIAL/FINISH**

Symbol	Material	Finish Description
J	Aluminum	Yellow Cadmium
M		Electroless Nickel
MT		NI-PTFE 1000 Hour Grey™ Nickel Fluorocarbon Polymer
ZN		Zinc Nickel

**TABLE III: FILTER TYPE**

Symbol	Filter Type	H ±.010 (0.25)
P	PI-Circuit	.610 ((15.5)
C	C-Circuit	.380 (9.7)

**TABLE IV:  
 CAPACITOR ARRAY CODE AND  
 CAPACITANCE RANGE**

Class	PI-Circuit (pF)	C-Circuit (pF)
A	38,000 - 56,000	19,000 - 28,000
B	32,000 - 45,000	16,000 - 22,500
C	18,000 - 33,000	9,000 - 16,500
D	8,000 - 12,000	4,000 - 6,000
E	3,300 - 5,000	1,650 - 2,500
F	800 - 1,300	400 - 650
G	400 - 600	200 - 300

**TABLE V: HARDWARE OPTIONS**

Symbol	Hardware
B	No Hardware
C	4-40 Clinch Nut