

**isc Silicon PNP Power Transistor**


**2SA1494**

**DESCRIPTION**

- Collector-Emitter Breakdown Voltage-  
 $V_{(BR)CEO} = -200V(\text{Min})$
- Good Linearity of  $h_{FE}$
- Complement to Type 2SC3858


**APPLICATIONS**

- For audio and general purpose applications



**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	-200	V
$V_{CEO}$	Collector-Emitter Voltage	-200	V
$V_{EBO}$	Emitter-Base Voltage	-6	V
$I_C$	Collector Current-Continuous	-17	A
$I_B$	Base Current-Continuous	-5	A
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	200	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ\text{C}$



## isc Silicon PNP Power Transistor

2SA1494

## ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C = -50\text{mA}$ ; $I_B = 0$	-200			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = -10\text{A}$ ; $I_B = -1\text{A}$			-2.5	V
$I_{CBO}$	Collector Cutoff Current	$V_{CB} = -200\text{V}$ ; $I_E = 0$			-100	$\mu\text{A}$
$I_{EBO}$	Emitter Cutoff Current	$V_{EB} = -6\text{V}$ ; $I_C = 0$			-100	$\mu\text{A}$
$h_{FE}$	DC Current Gain	$I_C = -8\text{A}$ ; $V_{CE} = -4\text{V}$	50		180	
$C_{OB}$	Output Capacitance	$I_E = 0$ ; $V_{CB} = -10\text{V}$ ; $f_{test} = 1.0\text{MHz}$		500		pF
$f_T$	Current-Gain—Bandwidth Product	$I_E = 1\text{A}$ ; $V_{CE} = -12\text{V}$		20		MHz

## Switching times

$t_{on}$	Turn-on Time	$I_C = -10\text{A}$ , $R_L = 4\Omega$ , $I_{B1} = -I_{B2} = -1\text{A}$ , $V_{CC} = -40\text{V}$		0.6		$\mu\text{s}$
$t_{stg}$	Storage Time			0.9		$\mu\text{s}$
$t_f$	Fall Time			0.2		$\mu\text{s}$

◆  $h_{FE}$  Classifications

Y	P	G
50-100	70-140	90-180