

## Silicon PNP Power Transistors

## 2SA980/981/982

## DESCRIPTION

- With TO-3 package
- Complement to type 2SC2260/2261/2262

## APPLICATIONS

- For power switching and general purpose applications

## PINNING(see Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings( $T_a =$ )

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$V_{CBO}$	Collector-base voltage	2SA980	-100	V
		2SA981	-120	
		2SA982	-140	
$V_{CEO}$	Collector-emitter voltage	2SA980	-100	V
		2SA981	-120	
		2SA982	-140	
$V_{EBO}$	Emitter-base voltage	Open collector	-6	V
$I_C$	Collector current		-8	A
$I_B$	Base current		-3	A
$P_C$	Collector power dissipation	$T_C=25$	80	W
$T_j$	Junction temperature		150	
$T_{stg}$	Storage temperature		-65~150	

## Silicon PNP Power Transistors

## 2SA980/981/982

## CHARACTERISTICS

T<sub>j</sub>=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>(BR)CEO</sub>	Collector-emitter breakdown voltage	2SA980	-100			V
		2SA981	-120			
		2SA982	-140			
V <sub>CEsat</sub>	Collector-emitter saturation voltage	I <sub>C</sub> =-3A; I <sub>B</sub> =-0.3A			-1.5	V
I <sub>CBO</sub>	Collector cut-off current	2SA980				mA
		2SA981			-0.1	
		2SA982				
I <sub>EBO</sub>	Emitter cut-off current	V <sub>EB</sub> =-6V; I <sub>C</sub> =0			-0.1	mA
h <sub>FE</sub>	DC current gain	I <sub>C</sub> =-3A; V <sub>CE</sub> =-4V	30			
f <sub>T</sub>	Transition frequency	I <sub>C</sub> =-0.5A; V <sub>CE</sub> =-12V		20		MHz

## Switching times

t <sub>r</sub>	Rise time			0.85		μs
t <sub>s</sub>	Storage time	I <sub>C</sub> =-3A; R <sub>L</sub> =4 I <sub>B1</sub> =-0.2A; I <sub>B2</sub> =0.1A V <sub>CC</sub> =-12V		2.0		μs
t <sub>f</sub>	Fall time			0.3		μs

Silicon PNP Power Transistors

2SA980/981/982

PACKAGE OUTLINE



Fig.2 outline dimensions (unindicated tolerance: ± 0.1mm)