


## NPN Epitaxial Planar Silicon Transistor

## 2SC4577

## ■ Features

- Low collector-to-emitter saturation voltage.
- Small-sized package.



## ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Collector-base voltage	V <sub>CB0</sub>	20	V
Collector-emitter voltage	V <sub>CEO</sub>	15	V
Emitter-base voltage	V <sub>EBO</sub>	5	V
Collector current	I <sub>C</sub>	500	mA
Collector current (pulse)	I <sub>cp</sub>	1	A
Collector dissipation	P <sub>C</sub>	200	mW
Junction temperature	T <sub>j</sub>	150	°C
Storage temperature	T <sub>stg</sub>	-55 to +150	°C

## ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Collector cutoff current	I <sub>CBO</sub>	V <sub>CB</sub> = 15V, I <sub>E</sub> =0			0.1	μA
Emitter cutoff current	I <sub>EBO</sub>	V <sub>EB</sub> = 4V, I <sub>C</sub> =0			0.1	μA
DC current gain	h <sub>FE</sub>	V <sub>CE</sub> = 2V, I <sub>C</sub> = 10mA	135		600	
Gain bandwidth product	f <sub>T</sub>	V <sub>CE</sub> = 2V, I <sub>C</sub> = 50mA		300		MHz
Output capacitance	C <sub>ob</sub>	V <sub>CB</sub> = 10V, f = 1.0MHz		4.0		pF
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 5mA, I <sub>B</sub> = 0.5mA		15	30	mV
		I <sub>C</sub> = 200mA, I <sub>B</sub> = 10mA		160	300	mV
Base-emitter saturation voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 200mA, I <sub>B</sub> = 10mA		0.95	1.2	V
Collector-base breakdown voltage	V <sub>(BR)CBO</sub>	I <sub>C</sub> = 10μA, I <sub>E</sub> = 0	20			V
Collector-emitter breakdown voltage	V <sub>(BR)CEO</sub>	I <sub>C</sub> = 1mA, R <sub>BE</sub> = ∞	15			V
Emitter-base breakdown voltage	V <sub>(BR)EBO</sub>	I <sub>E</sub> = 10μA, I <sub>C</sub> = 0	5			V

## ■ hFE Classification

Marking	UT		
Rank	5	6	7
hFE	135~270	200~400	300~600