

SANYO	No.2926A	2SA1641
		PNP Epitaxial Planar Silicon Transistor

High-Current Switching Applications

Features

- Adoption of FBET, MBIT processes.
- Low saturation voltage.
- Fast switching speed.
- Large current capacity.
- Small and slim package making it easy to make 2SA1641-used set smaller

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector to Base Voltage	V _{CB0}	-25	V
Collector to Emitter Voltage	V _{CEO}	-20	V
Emitter to Base Voltage	V _{EBO}	-5	V
Collector Current	I _C	-8	A
Collector Current(Pulse)	I _{CP}	-12	A
Base Current	I _B	-1.5	A
Collector Dissipation	P _C	1	W
		T _c = 25°C	
Junction Temperature	T _j	15	W
Storage Temperature	T _{stg}	-55 to +150	°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
Collector Cutoff Current	I _{CB0}	V _{CB} = -20V, I _E = 0			-1	μA
Emitter Cutoff Current	I _{EBO}	V _{EB} = -4V, I _C = 0			-1	μA
DC Current Gain	h _{FE} (1)	V _{CE} = -2V, I _C = -500mA	100*		400*	
	h _{FE} (2)	V _{CE} = -2V, I _C = -6A	60			
Gain-Bandwidth Product	f _T	V _{CE} = -2V, I _C = -500mA		200		MHz
C-E Saturation Voltage	V _{CE(sat)}	I _C = -5A, I _B = -250mA	-220	-400		mV
B-E Saturation Voltage	V _{BE(sat)}	I _C = -5A, I _B = -250mA	-1	-1.3		V
Collector Output Capacitance	c _{ob}	V _{CB} = -10V, f = 1MHz		85		pF
C-B Breakdown Voltage	V _{(BR)CBO}	I _C = -10μA, I _E = 0	-25			V
C-E Breakdown Voltage	V _{(BR)CEO}	I _C = -1mA, R _{BE} = ∞	-20			V
E-B Breakdown Voltage	V _{(BR)EBO}	I _E = -10μA, I _C = 0	-5			V


*: The 2SA1641 is classified by 500mA h_{FE} as follows :

100 R 200	140 S 280	200 T 400
-----------	-----------	-----------

Continued on next page.

Package Dimensions 2045B

(unit : mm)




- 1: Base
- 2: Collector
- 3: Emitter
- 4: Collector

SANYO: TP

Package Dimensions 2044B

(unit : mm)



- 1: Base
- 2: Collector
- 3: Emitter
- 4: Collector

SANYO: TP-FA


Continued from preceding page.

Turn-on Time
Storage Time
Fall Time







t_{on} See specified Test Circuit.
 t_{stg} "
 t_f "




min	typ	max	unit
	30	300	ns
	200	800	ns
	15	150	ns

Switching Time Test Circuit



$20I_{B1} = -20I_{B2} = I_C = -5A$ Unit (Resistance : Ω , Capacitance : F)





EPW.com.cn 电子产品世界

- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.