

SANYO	No.3578	2SA1770/2SC4614
		PNP/NPN Epitaxial Planar Silicon Transistors
High-Voltage Switching Applications		

Features

- Adoption of MBIT process
- High breakdown voltage and large current capacity

() : 2SA1770

Absolute Maximum Ratings at Ta=25°C

			unit
Collector to Base Voltage	V_{CBO}	(-)180	V
Collector to Emitter Voltage	V_{CEO}	(-)160	V
Emitter to Base Voltage	V_{EBO}	(-)6	V
Collector Current	I_C	(-)1.5	A
Collector Current(Pulse)	I_{CP}	(-)2.5	A
Collector Dissipation	P_C	1	W
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55 to +150	°C

Electrical Characteristics at Ta=25°C


			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)120V, I_E = 0$			(-)1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4V, I_C = 0$			(-)1	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = (-)5V, I_C = (-)100mA$	100 *		400 *	
	$h_{FE(2)}$	$V_{CE} = (-)5V, I_C = (-)10mA$	80			
Gain-Bandwidth Product	f_T	$V_{CE} = (-)10V, I_C = (-)50mA$		120		MHz
Output Capacitance	C_{ob}	$V_{CB} = (-)10V, f = 1MHz$		(22)		pF
				14		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		(-)200	(-)500	mV
				130	450	mV
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		(-)0.85	(-)1.2	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu A, I_E = 0$	(-)180			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1mA, R_{FE} = \infty$	(-)160			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\mu A, I_C = 0$	(-)6			V

Continued on next page.

* : The 2SA1770/2SC4614 are classified by 100mA h_{FE} as follows :


100 R	200	140 S	280	200 T	400
-------	-----	-------	-----	-------	-----

Package Dimensions 2064
(unit: mm)









h_{FE} rank : R, S, T

Switching Time Test Circuit













Continued from preceding page.

			min	typ	max	unit
Turn-on Time	t_{on}	See specified Test Circuit.		(40)		ns
			"	40		ns
Storage Time	t_{stg}			(0.7)		μs
			"	1.2		μs
Fall time	t_f			(40)		ns
			"	80		ns



2SA1770/2SC4614





E E P W .com.cn 电子產品世界

- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.