

SANYO	No.1334C	2SA1319/2SC3332
		PNP/NPN Epitaxial Planar Silicon Transistors
High-Voltage Switching Applications		

Features

- High breakdown voltage.
- Excellent h_{FE} linearity.
- Wide ASO and highly resistant to breakdown.
- Adoption of MBIT process.

(): 2SA1319

Absolute Maximum Ratings/ $T_a = 25^\circ\text{C}$

			unit
Collector to Base Voltage	V_{CB0}	(-)180	V
Collector to Emitter Voltage	V_{CE0}	(-)160	V
Emitter to Base Voltage	V_{EB0}	(-)6	V
Collector Current	I_C	(-)0.7	A
Collector Current(Pulse)	I_{CP}	(-)1.5	A
Collector Dissipation	P_C	700	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics/ $T_a = 25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)120\text{V}, I_E = 0$			(-)0.1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4\text{V}, I_C = 0$			(-)0.1	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = (-)5\text{V}, I_C = (-)100\text{mA}$	100*		400*	
	$h_{FE(2)}$	$V_{CE} = (-)5\text{V}, I_C = (-)10\text{mA}$	80			
Gain-bandwidth product	f_T	$V_{CE} = (-)10\text{V}, I_C = (-)50\text{mA}$		120		MHz
Common Base Output Capacitance	c_{ob}	$V_{CB} = (-)10\text{V}$		(11)8		pF
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)250\text{mA}, I_B = (-)25\text{mA}$		0.12	0.4	V
				(0.20)	(0.5)	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)250\text{mA}, I_B = (-)25\text{mA}$		(-)0.85	(-)1.2	V
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu\text{A}, I_E = 0$	(-)180			V
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1\text{mA}, R_{BE} = \infty$	(-)160			V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\mu\text{A}, I_C = 0$	(-)6			V
Turn-on Time	t_{on}	At specified test circuit		(60)50		ns
Storage Time	t_{stg}	"		(900)1000		ns
Fall Time	t_f	"		(60)60		ns


*: The 2SA1319/2SC3332 are classified by 100mA h_{FE} as follows:

100	R	200	140	S	280	200	T	400
-----	---	-----	-----	---	-----	-----	---	-----


Package Dimensions
(unit: mm) 2003A

Switching Time Test Circuit


(For PNP, the polarity is reversed.)











Unit(Resistance : Ω , Capacitance : F)








JEDEC: TO-92
EIAJ: SC-43
SANYO: NP



B. Base
C. Collector
E. Emitter





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.