


UTC 2SC2881 NPN EPITAXIAL SILICON TRANSISTOR

VOLTAGE AMPLIFIER
APPLICATIONS POWER
AMPLIFIER APPLICATIONS

FEATURES

- * High voltage: $V_{CE0} = 120V$
- * High transition frequency: $f_T = 120MHz$ (typ.)
- * $P_c = 1.0 \sim 2.0 W$ (mounted on ceramic substrate)
- * Complementary to 2SA1201



SOT-89

1:EMITTER 2:COLLECTOR 3:BASE

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-base voltage	V_{CBO}	120	V
Collector-emitter voltage	V_{CEO}	120	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	800	mA
Base current	I_B	160	mA
Collector power dissipation	P_c	500	mW
	P_c (Note 1)	1000	
Junction temperature	T_J	150	°C
Storage temperature range	T_{stg}	-55 ~ 150	°C

Note 1: Mounted on ceramic substrate(250mm²×0.8t)

ELECTRICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = 10mA, I_B = 0$	120			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = 1mA, I_C = 0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB} = 120V, I_E = 0$			0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = 5V, I_C = 0$			0.1	μA
DC current gain	h_{FE}	$V_{CE} = 5V, I_C = 100mA$	80		240	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 500mA, I_B = 50mA$			1.0	V
Base-emitter voltage	V_{BE}	$V_{CE} = 5V, I_C = 500mA$			1.0	V
Transition frequency	f_T	$V_{CE} = 5V, I_C = 100mA$		120		MHz
Collector output capacitance	C_{ob}	$V_{CB} = 10V, f = 1MHz, I_E = 0$			30	pF


CLASSIFICATION OF h_{FE}

RANK	O	Y
RANGE	80 - 160	120 - 240

UTC UNISONIC TECHNOLOGIES CO., LTD.

UTC 2SC2881 NPN EPITAXIAL SILICON TRANSISTOR

TYPICAL PERFORMANCE CHARACTERISTICS



UTC 2SC2881 NPN EPITAXIAL SILICON TRANSISTOR

EEPW 电子產品世界
.com.cn

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.