

NEC[®]**NPN SILICON HIGH
FREQUENCY TRANSISTOR****NE219
SERIES****FEATURES**

- HIGH f_T : 8 GHz
- LOW NOISE:
1 dB at 0.5 GHz
2.2 dB at 2 GHz
- HIGH COLLECTOR CURRENT: 80 mA
- HIGH OSCILLATOR POWER OUTPUT:
100 mW at 6 GHz
- EXCELLENT GENERAL PURPOSE TRANSISTOR

DESCRIPTION AND APPLICATIONS

The NE219 series of NPN silicon bipolar transistors is designed for small signal amplifier and oscillator applications up to 6 GHz. The series employs arsenic doped emitters and NEC's hi-rel platinum-gold metallization system which permits reliable operation at high temperature operation (100°C) at rated dissipation. The series is available in either chip form (NE21900) or in a variety of packages. Low noise and high current capability provides wide dynamic range and economical solutions to a wide variety of microstrip thick and thin film applications. Quality, performance, uniformity and reliability are assured by NEC's quality assurance program which is patterned after MIL-S-19500. The NE219 is available in Grade C (JANTXV equivalent), Grade CX (JANTX equivalent), and Grade D.

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

SYMBOLS	PARAMETERS	UNITS	RATINGS
V_{CB0}	Collector to Base Voltage	V	20
V_{CE0}	Collector to Emitter Voltage	V	10 ¹
V_{EB0}	Emitter to Base Voltage	V	1.5
I_C	Collector Current	mA	80
T_J	Junction Temperature	°C	200 ²
T_{STG}	Storage Temperature	°C	-65 to +200 ³

Notes:

1. Typical $V_{CE0} = 20\text{ V}$ for $R = 10\ \Omega$.
2. $T_J = 150^\circ\text{C}$ for NE21936 and NE21937.
3. $T_{STG} = -65$ to $+150^\circ\text{C}$ for NE21936, NE21937 and NE21935 Grade D.

NE21935 TYPICAL NOISE PARAMETERS $V_{CE} = 8\text{ V}, I_C = 5\text{ mA}$

FREQUENCY (MHz)	$NF_{min}/(\text{dB})$	G_n/dB	OPT SOURCE	$R_n/50\ \Omega$
500	1.3	20.7	.15 $\angle 100^\circ$	.15
1000	1.4	16.2	.31 $\angle 146^\circ$	.12
1500	2.1	13.5	.49 $\angle 178^\circ$	.04
2000	2.3	11.8	.48 $\angle -172^\circ$	.07
2500	2.7	9.6	.53 $\angle -155^\circ$	.13
3000	3.4	9.6	.58 $\angle -133^\circ$	.26
3500	3.6	8.0	.66 $\angle -128^\circ$	.36

 $V_{CE} = 8\text{ V}, I_C = 20\text{ mA}$

500	1.6	22.0	.14 $\angle 132^\circ$	.17
1000	2.0	17.3	.30 $\angle 176^\circ$	.13
1500	2.6	14.9	.47 $\angle -167^\circ$	.08
2000	2.9	13.0	.53 $\angle -159^\circ$	.12
2500	3.2	11.4	.56 $\angle -150^\circ$	.19
3000	3.9	11.4	.58 $\angle -127^\circ$	.36
3500	4.3	9.2	.68 $\angle -123^\circ$	.28

*Input tuned for minimum Noise Figure, output tuned for Maximum Gain.

PERFORMANCE SPECIFICATIONS ($T_A = 25^\circ\text{C}$)

PART NUMBER EIAJ ¹ REGISTERED NUMBER PACKAGE OUTLINE										NE21903 2SC22174			NE21908 2SC2218			NE21912			NE21935 2SC2367			NE21937 2SC2869			NE21987			
PARAMETERS AND CONDITIONS										03			08			12			35			37			87			
SYMBOLS	UNITS									MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
f _T	Gain Bandwidth Product at V _{CE} = 8 V, I _C = 20 mA										8.0			8.0				8.0					8.0				8.0	
S ₂₁ E ²	Insertion Power Gain at V _{CE} = 8 V, I _C = 20 mA, f = 0.5 GHz f = 1 GHz f = 2 GHz									21.0 15.5 8.0	21.0 15.5 9.6			21.0 15.5 9.6				15.5 8.0 9.0				13.0 7.0						
NF _{MIN}	Minimum Noise Figure ² at V _{CE} = 8 V, I _C = 5 mA, f = 0.5 GHz f = 1 GHz f = 2 GHz										1.3 2.2	3.5			1.3 2.2	3.5												
MAG	Maximum Available Gain ³ at V _{CE} = 8 V, I _C = 20 mA, f = 0.5 GHz f = 1 GHz f = 2 GHz										25.0 18.4 12.6			25.0 18.4 12.6				25.0 18.4 12.6				12 2.2	2.5					
GNF	Associated Gain at Optimum Noise Figure, V _{CE} = 8 V, I _C = 5 mA, f = 0.5 GHz f = 1 GHz f = 2 GHz										15.0 13.0 8.0			15.0 13.0 8.0				15.0 13.0 8.0				12.0						
Posc	Oscillator Power Output at V _{CE} = 8 V, I _C = 40 mA, f = 6 GHz																										100	

Notes:

1. Electronics Industrial Association of Japan.
2. Input and output are tuned for optimum noise figure.
3. Maximum Available Gain (MAG) is calculated from the device S-Parameters using the equation, $MAG = \frac{|S_{21}|}{|S_{12}|} \sqrt{K^2 - 1}$ K = $\frac{1 + |\Delta|^2 - |S_{11}|^2 - |S_{22}|^2}{2|S_{21}||S_{12}|}$ $\Delta = S_{11}S_{22} - S_{21}S_{12}$
4. EIAJ registered number refers to grade C versions of these devices.


ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

PART NUMBER EIAJ ¹ REGISTERED NUMBER PACKAGE OUTLINE										NE21903 2SC22174			NE21908 2SC22184			NE21912			NE21935 2SC2367			NE21937 2SC2869			NE21987		
										03			08			12			35			37			87		
SYMBOLS	PARAMETERS AND CONDITIONS									UNITS	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX		
I _{CO}	Collector Cutoff Current at V _{CS} = 8 V, I _E = 0									μA			1.0			1.0			1.0			1.0			1.0		
I _{EO}	Emitter Cutoff Current at V _{EB} = 1 V, I _C = 0									μA			1.0			1.0			1.0			1.0			1.0		
h _{FE}	Forward Current Gain at V _{CE} = 8 V, I _C = 20 mA										30	100	300	30	100	300	30	100	300	30	100	300	30	100	300		
C _{CB}	Collector to Base Capacitance ² at V _{CB} = 8 V, I _E = 0									pF		0.4	1.0		0.4	1.0		0.4	1.0		0.7	1.0		0.4	1.0		
R _{TH}	Thermal Resistance (μ-C)									°C/W			70			90			80	500 ³					70		
P _T	Total Power Dissipation (T _A = 25°C)									mW			580			350			580	250					700		


Notes:

1. Electronic Industrial Association of Japan.
2. C_{CB} measurement employs a three-terminal capacitance bridge incorporating a guard circuit. The emitter terminal shall be connected to the guard terminal.
3. R_{TH} ($\mu\text{-C}$)
4. EIAJ registered number refers to grade C versions of these devices.


OUTLINE DIMENSIONS (Units in mm)




OUTLINE 03




OUTLINE 08




OUTLINE 12
(TO-72)




OUTLINE 35
(MICRO-X)





OUTLINE 37
(DISK-MOLD)









OUTLINE 87



TYPICAL DEVICE CHARACTERISTICS ($T_A = 25^\circ\text{C}$)




TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

N E C/ CALIFORNIA
NE219 SERIES


15E D ■ 6427414 0001397 0 ■

T-31-17
T-31-21
T-31-23

TYPICAL COMMON COLLECTOR SCATTERING PARAMETERS



NE21900
Coordinates in Ohms
Frequency in GHz
(VCE = 8 V, IC = 20 mA)



S-MAGN AND ANGLES:

VCE = 8 V, IC = 10 mA
FREQUENCY (MHz)

	S11		S21		S12		S22	
2000	.88	-56	1.57	-29	.44	47	.64	143
2500	.87	-67	1.50	-34	.52	41	.60	139
3000	.83	-77	1.39	-42	.58	31	.54	128
3500	.82	-85	1.26	-44	.60	27	.46	131
4000	.80	-93	1.18	-49	.64	21	.43	124
4500	.79	-98	1.12	-52	.67	14	.38	125
5000	.79	-103	1.02	-53	.68	11	.32	130
5500	.77	-109	1.00	-55	.72	7	.31	126
6000	.78	-113	.93	-57	.72	4	.25	142


VCE = 8 V, IC = 20 mA

	S11		S21		S12		S22	
2000	.91	-53	1.66	-29	.40	51	.71	147
2500	.90	-64	1.59	-34	.47	45	.68	143
3000	.87	-74	1.47	-42	.53	35	.62	132
3500	.86	-82	1.35	-43	.55	32	.54	135
4000	.84	-90	1.26	-49	.60	26	.52	128
4500	.84	-95	1.20	-52	.63	19	.47	129
5000	.83	-101	1.09	-54	.64	16	.41	131
5500	.82	-107	1.07	-56	.64	12	.40	127
6000	.82	-111	.99	-59	.69	9	.34	138


VCE = 8 V, IC = 30 mA

	S11		S21		S12		S22	
2000	.91	-52	1.67	-29	.39	52	.74	148
2500	.91	-64	1.61	-34	.47	46	.70	144
3000	.87	-74	1.49	-42	.52	36	.64	133
3500	.87	-82	1.36	-44	.55	33	.57	136
4000	.84	-90	1.28	-50	.59	27	.54	129
4500	.85	-95	1.22	-53	.62	20	.50	129
5000	.84	-100	1.10	-55	.64	17	.43	131
5500	.83	-107	1.08	-57	.69	13	.42	127
6000	.84	-111	1.00	-59	.69	11	.36	137

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE21900
Coordinates in Ohms
Frequency in GHz
(V_{CE} = 8 V, I_C = 20 mA)



S-MAGN AND ANGLES:

V_{CE} = 8 V, I_C = 10 mA

FREQUENCY (MHz)

	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
2000	.70	-155	2.78	89	.08	72	.32	-44
2500	.68	-167	2.31	78	.09	72	.27	-45
3000	.72	-173	1.99	70	.11	74	.24	-42
3500	.74	-174	1.77	67	.12	77	.20	-58
4000	.70	-176	1.57	55	.14	71	.13	-80
4500	.72	-176	1.38	52	.15	74	.15	-101
5000	.76	-172	1.26	46	.17	73	.19	-128
5500	.72	-168	1.13	41	.19	71	.26	-143
6000	.73	-168	.99	38	.19	72	.33	-148


V_{CE} = 8 V, I_C = 20 mA

	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
2000	.69	-159	3.03	88	.07	81	.26	-46
2500	.67	-170	2.51	78	.09	79	.21	-44
3000	.72	-175	2.15	70	.11	79	.19	-39
3500	.74	-176	1.90	67	.13	81	.14	-58
4000	.69	-175	1.68	56	.15	74	.08	-90
4500	.73	-174	1.46	53	.16	77	.11	-115
5000	.76	-172	1.34	47	.18	74	.16	-143
5500	.72	-167	1.21	42	.19	73	.23	-154
6000	.73	-167	1.07	40	.20	74	.30	-155


V_{CE} = 8 V, I_C = 30 mA

	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
2000	.69	-161	3.07	87	.07	84	.25	-45
2500	.67	-171	2.53	77	.09	82	.20	-42
3000	.72	-176	2.16	70	.11	82	.18	-36
3500	.74	-177	1.92	67	.13	83	.13	-55
4000	.70	-174	1.68	56	.15	75	.07	-88
4500	.73	-174	1.49	52	.16	78	.09	-115
5000	.77	-171	1.36	47	.18	75	.15	-144
5500	.73	-167	1.22	41	.19	74	.22	-154
6000	.73	-166	1.08	40	.20	74	.29	-155

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE21903
Coordinates In Ohms
Frequency In GHz
(VCE = 8 V, IC = 20 mA)



S-MAGN AND ANGLES:

VCE = 8 V, IC = 10 mA
FREQUENCY (MHz)

	S11		S21		S12		S22	
100	.79	-45	22.62	152	.01	77	.91	-18
500	.63	-140	9.88	102	.04	39	.47	-41
1000	.62	-173	5.30	81	.05	40	.36	-44
1500	.62	169	3.59	67	.07	43	.35	-49
2000	.62	156	2.68	57	.09	51	.35	-57
2500	.64	143	2.17	45	.10	51	.31	-69
3000	.67	134	1.88	35	.13	51	.32	-82
3500	.68	122	1.58	25	.14	44	.32	-94
4000	.70	114	1.40	13	.15	43	.34	-106
4500	.70	106	1.18	6	.17	39	.36	-116
5000	.71	98	1.10	-2	.19	38	.38	-124

VCE = 8 V, IC = 20 mA


	S11		S21		S12		S22	
100	.69	-64	32.32	144	.01	71	.84	-24
500	.60	-156	11.17	96	.03	46	.37	-42
1000	.61	178	5.81	78	.04	53	.28	-44
1500	.61	164	3.92	66	.06	55	.28	-50
2000	.62	151	2.93	56	.09	59	.29	-59
2500	.64	140	2.38	46	.11	55	.25	-72
3000	.67	130	2.06	35	.13	51	.25	-85
3500	.68	120	1.73	26	.15	48	.26	-96
4000	.69	112	1.54	14	.16	44	.28	-108
4500	.69	105	1.32	7	.18	42	.31	-115
5000	.70	96	1.19	0	.20	40	.33	-125

VCE = 8 V, IC = 40 mA

	S11		S21		S12		S22	
100	.62	-84	39.23	136	.01	57	.76	-29
500	.60	-166	11.61	92	.02	54	.32	-39
1000	.61	173	5.94	76	.04	62	.25	-40
1500	.62	160	3.99	64	.06	59	.26	-47
2000	.62	149	2.98	55	.09	62	.27	-56
2500	.65	138	2.43	45	.11	56	.24	-70
3000	.66	129	2.11	34	.13	55	.24	-83
3500	.68	120	1.78	25	.15	51	.25	-94
4000	.70	112	1.59	13	.16	46	.27	-106
4500	.70	104	1.35	6	.18	43	.30	-113
5000	.71	97	1.26	-1	.20	39	.31	-124

NE219 SERIES

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



S-MAGN AND ANGLES:

VCE = 8 V, IC = 5 mA

FREQUENCY (MHz)

	S11	S21	S12	S22
100	.91 -29	14.21 160	.01 79	.96 -13
500	.73 -112	8.27 113	.07 38	.61 -40
1000	.68 -149	4.84 89	.08 26	.46 -53
1500	.67 -169	3.34 73	.08 22	.44 -58
2000	.67 180	2.53 62	.08 24	.43 -66
2500	.67 168	2.01 50	.09 24	.42 -76
3000	.67 158	1.73 40	.09 27	.44 -86
3500	.67 149	1.48 30	.10 29	.46 -94
4000	.67 141	1.34 20	.11 30	.49 -103
4500	.66 134	1.16 10	.12 30	.52 -110
5000	.66 125	1.06 3	.13 30	.55 -118



VCE = 8 V, IC = 10 mA

	S11	S21	S12	S22
100	.84 -42	23.68 153	.01 78	.91 -19
500	.67 -132	10.89 105	.05 37	.45 -50
1000	.65 -163	5.90 84	.05 33	.32 -58
1500	.63 -178	4.00 71	.07 37	.31 -64
2000	.64 173	3.02 62	.08 42	.32 -71
2500	.65 160	2.47 50	.08 37	.31 -82
3000	.65 152	2.13 41	.09 40	.33 -91
3500	.65 143	1.82 32	.11 40	.35 -98
4000	.66 137	1.64 22	.12 38	.38 -107
4500	.65 130	1.44 13	.13 36	.41 -113
5000	.65 121	1.31 5	.14 32	.44 -121

VCE = 8 V, IC = 20 mA

	S11	S21	S12	S22
100	.75 -59	34.58 145	.01 71	.84 -27
500	.65 -148	12.53 99	.03 43	.34 -58
1000	.65 -171	6.56 81	.04 43	.24 -65
1500	.64 176	4.44 69	.06 44	.24 -69
2000	.64 168	3.36 61	.07 49	.25 -77
2500	.65 156	2.73 51	.08 47	.24 -87
3000	.65 149	2.37 42	.10 47	.27 -95
3500	.65 141	2.02 32	.11 46	.30 -101
4000	.66 134	1.82 23	.13 42	.33 -109
4500	.65 127	1.58 13	.14 38	.36 -115
5000	.64 119	1.43 6	.15 35	.39 -123

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE21912
Coordinates in Ohms
Frequency in GHz
(VCE = 8 V, IC = 20 mA)

S-MAGN AND ANGLES:

VCE = 8 V, IC = 5 mA

FREQUENCY (MHz)	S11		S21		S12		S22	
100	.80	-27	12.30	149	.01	74	.92	-13
200	.67	-46	9.87	130	.03	66	.83	-20
500	.37	-78	5.45	97	.07	62	.68	-31
1000	.19	-97	3.03	71	.11	62	.63	-43
1500	.16	-97	2.14	51	.15	57	.66	-59
2000	.20	-98	1.62	31	.16	46	.71	-78

VCE = 8 V, IC = 10 mA

100	.69	-31	17.67	140	.01	74	.86	-15
200	.53	-47	12.60	120	.02	67	.76	-22
500	.29	-66	6.18	92	.07	70	.64	-29
1000	.17	-73	3.34	69	.12	65	.59	-41
1500	.19	-76	2.33	51	.17	56	.62	-58
2000	.26	-87	1.75	31	.18	44	.69	-77


VCE = 8 V, IC = 20 mA

100	.58	-34	22.03	131	.01	70	.80	-17
200	.43	-47	14.19	112	.02	70	.70	-21
500	.24	-60	6.53	88	.07	71	.60	-29
1000	.17	-61	3.49	67	.13	66	.58	-40
1500	.20	-67	2.42	50	.17	56	.61	-57
2000	.29	-84	1.81	30	.18	43	.68	-77


VCE = 8 V, IC = 30 mA

100	.52	-36	23.55	126	.01	70	.77	-17
200	.38	-46	14.52	109	.02	71	.67	-20
500	.22	-58	6.54	86	.07	70	.59	-28
1000	.16	-58	3.48	66	.13	66	.58	-40
1500	.20	-65	2.41	49	.17	56	.61	-58
2000	.28	-83	1.80	29	.18	42	.68	-78

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE21935
Coordinates in Ohms
Frequency in GHz
($V_{CE} = 8\text{ V}$, $I_C = 20\text{ mA}$)



S-MAGN AND ANGLES:

$V_{CE} = 8\text{ V}$, $I_C = 5\text{ mA}$
FREQUENCY (MHz)

	S11		S21		S12		S22	
100	.80	-30	13.74	160	.01	80	.96	-12
500	.65	-117	8.05	112	.07	40	.62	-40
1000	.62	-159	4.72	86	.07	30	.45	-50
1500	.62	-178	3.24	69	.08	30	.42	-56
2000	.62	-162	2.44	56	.09	34	.42	-64
2500	.64	-146	1.95	42	.10	28	.39	-76
3000	.65	-133	1.67	30	.11	33	.40	-87
3500	.66	-120	1.39	20	.13	33	.42	-97
4000	.67	-109	1.27	9	.14	32	.43	-108
4500	.68	-99	1.11	-1	.16	29	.45	-117
5000	.69	-89	1.02	-10	.18	25	.48	-127



$V_{CE} = 8\text{ V}$, $I_C = 10\text{ mA}$

	S11		S21		S12		S22	
100	.67	-44	22.00	153	.01	76	.92	-18
500	.59	-139	10.21	104	.04	42	.48	-48
1000	.60	-173	5.57	82	.05	41	.34	-55
1500	.59	-169	3.78	67	.07	42	.32	-61
2000	.60	-155	2.86	56	.09	45	.32	-68
2500	.62	-140	2.29	43	.11	43	.30	-80
3000	.63	-129	1.96	31	.12	41	.31	-91
3500	.64	-117	1.68	22	.14	39	.32	-101
4000	.65	-107	1.50	11	.16	35	.34	-112
4500	.66	-98	1.30	1	.18	29	.36	-121
5000	.67	-87	1.20	-8	.19	25	.38	-131

$V_{CE} = 8\text{ V}$, $I_C = 20\text{ mA}$

	S11		S21		S12		S22	
100	.55	-66	31.47	146	.01	70	.86	-25
500	.57	-157	11.59	98	.03	48	.37	-52
1000	.59	-177	6.10	79	.05	51	.26	-58
1500	.59	-162	4.13	65	.07	53	.25	-63
2000	.59	-150	3.09	55	.09	55	.26	-71
2500	.61	-136	2.49	43	.11	46	.24	-84
3000	.62	-125	2.13	32	.13	45	.26	-94
3500	.63	-114	1.78	22	.15	42	.27	-104
4000	.65	-105	1.62	12	.17	37	.29	-115
4500	.66	-95	1.41	2	.19	31	.31	-123
5000	.67	-85	1.31	-7	.20	26	.33	-132

TYPICAL COMMON EMITTER SCATTERING PARAMETERS



NE21937
Coordinates in Ohms
Frequency in GHz
(Vce = 8 V, Ic = 20 mA)

S-MAGN AND ANGLES:

VCE = 8 V, IC = 5 mA
FREQUENCY (MHz)

	S11		S21		S12		S22	
100	.67	-36	12.58	154	.01	76	.95	-13
200	.56	-69	10.71	135	.03	58	.84	-21
500	.43	-132	6.19	102	.06	50	.60	-31
1000	.42	177	3.49	75	.09	51	.49	-40
1500	.44	148	2.41	56	.12	51	.46	-48
2000	.49	125	1.84	42	.16	52	.44	-60
2500	.54	105	1.50	26	.19	45	.37	-71
3000	.59	96	1.29	16	.24	42	.35	-95

VCE = 8 V, IC = 10 mA


	S11		S21		S12		S22	
100	.53	-52	19.37	146	.01	72	.89	-17
200	.42	-91	14.71	125	.02	56	.73	-27
500	.36	-153	7.39	95	.05	58	.49	-32
1000	.38	165	3.98	72	.09	60	.41	-38
1500	.41	140	2.71	56	.13	57	.39	-47
2000	.45	122	2.07	42	.17	54	.36	-60
2500	.50	105	1.70	27	.21	47	.31	-73
3000	.55	93	1.44	14	.26	40	.28	-95

VCE = 8 V, IC = 20 mA

	S11		S21		S12		S22	
100	.39	-71	26.29	137	.01	74	.81	-23
200	.32	-118	17.89	116	.01	60	.62	-30
500	.32	-170	8.16	90	.05	66	.42	-30
1000	.36	156	4.28	70	.09	65	.36	-37
1500	.39	135	2.91	54	.14	59	.34	-46
2000	.43	118	2.22	42	.18	55	.31	-60
2500	.49	102	1.80	27	.22	46	.26	-77
3000	.53	91	1.53	14	.26	38	.23	-96

NE219 SERIES

TYPICAL COMMON COLLECTOR SCATTERING PARAMETERS



S-MAGN AND ANGLES:

VCE = 8 V, IC = 10 mA

FREQUENCY (MHz)

FREQUENCY (MHz)	S11		S21		S12		S22	
100	.97	-4	1.81	-3	.03	55	.85	177
500	.96	-20	1.84	-15	.15	65	.86	163
1000	.98	-42	1.82	-30	.29	52	.83	147
1500	.95	-62	1.75	-42	.40	38	.78	133
2000	.91	-80	1.60	-56	.50	22	.70	118
2500	.86	-96	1.51	-67	.59	10	.64	103
3000	.85	-113	1.42	-78	.66	-4	.57	89
3500	.84	-129	1.32	-91	.70	-17	.49	75
4000	.82	-144	1.21	-100	.73	-32	.42	63
4500	.79	-158	1.15	-110	.76	-42	.36	51
5000	.77	-173	1.06	-120	.79	-55	.31	38
5500	.76	-176	1.02	-131	.80	-66	.26	24
6000	.73	-163	.94	-140	.81	-79	.21	10

VCE = 8 V, IC = 20 mA

100	.98	-3	1.87	-3	.03	48	.91	177
500	.97	-19	1.89	-15	.13	64	.91	165
1000	1.00	-39	1.88	-28	.24	54	.88	150
1500	.99	-58	1.81	-40	.34	42	.85	138
2000	.94	-75	1.64	-55	.44	27	.78	123
2500	.91	-90	1.60	-66	.52	16	.74	109
3000	.91	-107	1.51	-77	.59	2	.68	95
3500	.90	-122	1.42	-90	.63	-11	.60	82
4000	.89	-137	1.31	-100	.69	-24	.54	70
4500	.87	-150	1.26	-111	.71	-35	.48	59
5000	.85	-165	1.16	-121	.75	-48	.43	46
5500	.84	-176	1.11	-133	.77	-59	.37	34
6000	.82	-171	1.02	-143	.78	-72	.32	21

VCE = 8 V, IC = 40 mA

100	.97	-3	1.88	-3	.03	41	.94	178
500	.97	-19	1.92	-14	.11	64	.93	165
1000	1.00	-38	1.91	-28	.22	55	.91	152
1500	.99	-57	1.85	-39	.32	44	.89	139
2000	.95	-75	1.63	-54	.41	29	.82	125
2500	.93	-91	1.66	-66	.49	19	.79	111
3000	.93	-110	1.59	-78	.57	5	.73	98
3500	.93	-127	1.51	-92	.62	-7	.65	85
4000	.91	-143	1.39	-102	.67	-21	.59	73
4500	.90	-158	1.33	-114	.71	-32	.53	62
5000	.88	-175	1.21	-125	.75	-45	.48	50
5500	.88	-172	1.16	-138	.77	-57	.42	36
6000	.85	-158	1.04	-148	.79	-70	.35	24