

TO-92 Plastic Package Transistors (NPN)

Maximum Ratings								Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)																		
Type No.	V _{CE0} (V) Max	V _{CE0} (V) Min	V _{CE0} (V) Min	P _D (W) @Tc=25°C	I _C (A)	I _{CEO} (μA) Max	V _{CE(sat)} (V) @ I _C (A)	I _{CE(sat)} (μA) Max	V _{CE(sat)} (V) @ I _C (A)	I _{RE} (μA) Min	I _{RE} (μA) Max	I _C (mA) Min	I _C (mA) Max	V _{CE(sat)} (V) Max	V _{CE(sat)} (V) Min	V _{CE(sat)} (V) Max	C _{ob} (pF) Typ	f _T (MHz) Min	f _T (MHz) Typ	I _C (mA) Max	I _{sat} (nA) Max	N _F (dB) Max	Q Freq (MHz) Max	C _{in} (pF) Max	CDL Case Style	
2SC2274D	100	80	5	0.6	0.5	1	40			80	120	50	5	0.6		1.2	400	5		120		10				TO-92-1
										35		400	5													
2SC2274E	100	80	5	0.8	0.5	1	40			100	200	50	5	0.6		1.2	400	5		120		10				TO-92-1
										35		400	5													
2SC2274F	100	80	5	0.6	0.5	1	40			160	320	50	5	0.6		1.2	400	5		120		10				TO-92-1
										35		400	5													
2SC2274K	100	80	5	0.6	0.5	1	40			60	320	50	5	0.6		1.2	400	5		120		10				TO-92-1
										35		400	5													
2SC2300	55	50	5	0.2	0.1	0.5	18			250	1200	2	12	0.2			10	3.5	150	230		2				TO-92-1
2SC2300D	55	50	5	0.2	0.1	0.5	18			250	500	2	12	0.2			10	3.5	150	230		2				TO-92-1
2SC2300E	55	50	5	0.2	0.1	0.5	18			400	800	2	12	0.2			10	3.5	150	230		2				TO-92-1
2SC2300F	55	50	5	0.2	0.1	0.5	18			600	1200	2	12	0.2			10	3.5	150	230		2				TO-92-1
2SC2458	50	50	5	0.2	0.15	0.1	50			70	700	2	6	0.25			100	3.5	80		1	10				TO-92-1
2SC2458BL	50	50	5	0.2	0.2	0.1	50			350	700	2	6	0.25			100	3.5	80		1	10				TO-92-1
2SC2458GR	50	50	5	0.2	0.15	0.1	50			200	400	2	6	0.25			100	3.5	80		1	10				TO-92-1
2SC2458D	50	50	5	0.2	0.15	0.1	50			70	140	2	6	0.25			100	3.5	80		1	10				TO-92-1
2SC2458Y	50	50	5	0.2	0.15	0.1	50			120	240	2	6	0.25			100	3.5	80		1	10				TO-92-1
2SC2482	300	300	7	0.9	0.1	1	240			20	4	10	10	1		1	10	3		50		20				TO-92-1
										30	150	20	10													
2SC3114	60	50	7	0.4	0.15	0.1	40			100	560	1	6	0.5			50	3		100		1				TO-92-1
2SC3114R	60	50	7	0.4	0.15	0.1	40			100	200	1	6	0.5			50	3		100		1				TO-92-1
2SC3114S	60	50	7	0.4	0.15	0.1	40			140	280	1	6	0.5			50	3		100		1				TO-92-1
2SC3114T	60	50	7	0.4	0.15	0.1	40			200	400	1	6	0.5			50	3		100		1				TO-92-1
2SC3114U	60	50	7	0.4	0.15	0.1	40			280	560	1	6	0.5			50	3		100		1				TO-92-1
2SC3197	30	25	4	0.3	0.05	0.1	30			20	200	12.5	12.5	0.2		1.5	13	0.8	2	300		13				TO-92-1
2SC3198	60	50	5	0.625	0.15	0.1	60			70	700	2	6	0.25		1	100	2	3.5	80		1	10			TO-92-1
										25		150	6													
2SC3198BL	60	50	5	0.625	0.15	0.1	60			350	700	2	6	0.25		1	100	2	3.5	80		1	10			TO-92-1
										25		150	6													
2SC3198GR	60	50	5	0.625	0.15	0.1	60			200	400	2	6	0.2		1	100	2	3.5	80		1	10			TO-92-1
										25		150	6													
2SC3198D	60	50	5	0.625	0.15	0.1	60			70	140	2	6	0.25		1	100	2	3.5	80		1	10			TO-92-1
										25		150	6													
2SC3198Y	60	50	5	0.625	0.15	0.1	60			120	240	2	6	0.25		1	100	2	3.5	80		1	10			TO-92-1
										25		150	6													
2SC3199	50	50	5	0.4	0.15	0.1	50			70	700	2	6	0.25			100	2	3.5	80		1	10			TO-92-1
2SC3199GR	50	50	5	0.4	0.15	0.1	50			200	400	2	6	0.25			100	2	3.5	80		1				TO-92-1
2SC3199D	50	50	4	0.4	0.15	0.1	50			70	140	2	6	0.25			100	2	3.5	80		1	10			TO-92-1