

No.4232

2SJ256

P-Channel MOS Silicon FET

SANYO

**Very High-Speed
Switching Applications**

Features



- Low ON resistance.
- Very high-speed switching.
- Low-voltage drive.
- Micaless package facilitating mounting.

Absolute Maximum Ratings at Ta = 25°C









			unit
Drain to Source Voltage	V _{DSS}	-30	V
Gate to Source Voltage	V _{GSS}	±15	V
Drain Current(DC)	I _D	-18	A
Drain Current(Pulse)	I _{DP}	PW ≤ 10μs, duty cycle ≤ 1% -72	A
Allowable Power Dissipation	P _D	2.0	W
	T _c = 25°C	30	W
Channel Temperature	T _{ch}	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C



Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
D-S Breakdown Voltage	V _{(BR)DSS}	I _D = -1mA, V _{GS} = 0	-30			V
G-S Breakdown Voltage	V _{(BR)GSS}	I _G = ±100μA, V _{DS} = 0	±15			V
Zero Gate Voltage	I _{DSS}	V _{DS} = -30V, V _{GS} = 0			-100	μA
Drain Current						
Gate to Source Leakage Current	I _{GSS}	V _{GS} = ±12V, V _{DS} = 0			±10	μA
Cutoff Voltage	V _{GS(off)}	V _{DS} = -10V, I _D = -1mA	-1.0		-2.0	V
Forward Transfer Admittance	Y _{fs}	V _{DS} = -10V, I _D = -10A	8.5	14		S
Static Drain to Source on State Resistance	R _{DS(on)}	I _D = -10A, V _{GS} = -10V	40	55		mΩ
Input Capacitance	C _{iss}	I _D = -10A, V _{GS} = -4V	55	75		mΩ
Output Capacitance	C _{oss}	V _{DS} = -10V, f = 1MHz	2000			pF
Reverse Transfer Capacitance	C _{rss}	V _{DS} = -10V, f = 1MHz	1200			pF
Turn-ON Delay Time	t _{d(on)}	V _{DS} = -10V, f = 1MHz	440			pF
Rise Time	t _r	See specified Test Circuit.	18			ns
Turn-OFF Delay Time	t _{d(off)}	"	50			ns
Fall Time	t _f	"	400			ns
Diode Forward Voltage	V _{SD}	I _S = -18A, V _{GS} = 0	-1.0	-1.5		V

Switching Time Test Circuit**Package Dimensions 2063**
(unit : mm)

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.