

SANYO	No.3457	2SK1454
		N-Channel MOS Silicon FET
Very High-Speed Switching Applications		

Features

- Low ON-state resistance.
- Very high-speed switching
- Converters.

Absolute Maximum Ratings at Ta = 25°C


			unit
Drain to Source Voltage	V _{DSS}	450	V
Gate to Source Voltage	V _{GSS}	±30	V
Drain Current(DC)	I _D	30	A
Drain Current(Pulse)	I _{DP}	PW ≤ 10μs, duty cycle ≤ 1%	120 A
Allowable Power Dissipation	P _D	T _c = 25°C	250 W
			3.5 W
Channel Temperature	T _{ch}	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
D-S Breakdown Voltage	V _{(BR)DSS}	I _D = 1mA, V _{GS} = 0	450			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 450V, V _{GS} = 0			1.0	mA
Gate to Source Leakage Current	I _{GSS}	V _{GS} = ±30V, V _{DS} = 0			±100	nA
Cutoff Voltage	V _{GS(off)}	V _{DS} = 10V, I _D = 1mA	2.0		3.0	V
Forward Transfer Admittance	Y _{fs}	V _{DS} = 10V, I _D = 15A	12.5	25		S
Static Drain to Source on State Resistance	R _{DS(on)}	I _D = 15A, V _{GS} = 10V	0.12	0.16		Ω
Input Capacitance	C _{iss}	V _{DS} = 20V, f = 1MHz		6400		pF
Output Capacitance	C _{oss}	V _{DS} = 20V, f = 1MHz		880		pF
Reverse Transfer Capacitance	C _{rss}	V _{DS} = 20V, f = 1MHz		320		pF
Turn-ON Delay Time	t _{d(on)}	I _D = 15A, V _{GS} = 10V V _{DD} = 200V, R _{GS} = 50Ω		55		ns
Rise Time	t _r		140		ns	
Turn-OFF Delay Time	t _{d(off)}		1000		ns	
Fall Time	t _f		350		ns	
Diode Forward Voltage	V _{SD}	I _S = 30A, V _{GS} = 0			1.8	V


(Note) Be careful in handling the 2SK1454 because it has no protection diode between gate and source.

Switching Time Test Circuit











Package Dimensions 2077





(unit : mm)



S : Source
D : Drain
G : Gate

SANYO: TO-3PBL





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.