

# DATA SHEET

EEPW 电子產品世界  
.com.cn

## 74LVC573A

Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

Product specification

1998 Jul 29

## Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

### 74LVC573A

#### FEATURES

- 5-volt tolerant inputs/outputs, for interfacing with 5-volt logic
- Supply voltage range of 2.7V to 3.6V
- Complies with JEDEC standard no. 8-1A
- Inputs accept voltages up to 5.5V
- CMOS low power consumption
- Direct interface with TTL levels
- High impedance when  $V_{CC} = 0V$
- Flow-through pin-out architecture

#### DESCRIPTION

The 74LVC573A is a high-performance, low-power, low-voltage, Si-gate CMOS device, superior to most advanced CMOS compatible TTL families.

Inputs can be driven from either 3.3V or 5V devices. In 3-State operation, outputs can handle 5V. This feature allows the use of these devices as translators in a mixed 3.3V/5V environment.

The 74LVC573A is an octal D-type transparent latch featuring separate D-type inputs for each latch and 3-State outputs for bus-oriented applications. A latch enable (LE) input and an output enable ( $\overline{OE}$ ) input are common to all internal latches.

The '573A' consists of eight D-type transparent latches with 3-State true outputs. When LE is HIGH, data at the  $D_n$  inputs enters the latches. In this condition, the latches are transparent, i.e. a latch output will change each time its corresponding D-input changes. When LE is LOW, the latches store the information that was present at the D-inputs one setup time preceding the HIGH-to-LOW transition of LE. When  $\overline{OE}$  is LOW, the contents of the eight latches are available at the outputs. When  $\overline{OE}$  is HIGH, the outputs go to the high impedance OFF-state. Operation of the  $\overline{OE}$  input does not affect the state of the latches.

The '573A' is functionally identical to the '373A', but the '373A' has a different pin arrangement.

#### QUICK REFERENCE DATA

| SYMBOL            | PARAMETER  | CONDITIONS                      | TYPICAL    | UNIT |
|-------------------|--|---------------------------------|------------|------|
| $t_{PHL}/t_{PLH}$ | Propagation delay<br>$D_n$ to $Q_n$ ;<br>LE to $Q_n$ | $C_L = 50pF$<br>$V_{CC} = 3.3V$ | 4.3<br>4.6 | ns   |
| $C_I$             | Input capacitance                                    |                                 | 5.0        | pF   |
| $C_{PD}$          | Power dissipation capacitance per latch              | Notes 1 and 2                   | 20         | pF   |

#### NOTE:

1.  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu W$ ):  
 $P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum (C_L \times V_{CC}^2 \times f_o)$  where:  
 $f_i$  = input frequency in MHz;  $C_L$  = output load capacity in pF;  
 $f_o$  = output frequency in MHz;  $V_{CC}$  = supply voltage in V;  
 $\sum (C_L \times V_{CC}^2 \times f_o)$  = sum of outputs.
2. The condition is  $V_I = GND$  to  $V_{CC}$

#### ORDERING INFORMATION

| PACKAGES  | TEMPERATURE RANGE | OUTSIDE NORTH AMERICA | NORTH AMERICA | PKG. DWG. # |
|---|-------------------|-----------------------|---------------|-------------|
| 20-Pin Plastic Shrink Small Outline (SO)                | -40°C to +85°C    | 74LVC573A D           | 74LVC573A D   | SOT163-1    |
| 20-Pin Plastic Shrink Small Outline (SSOP) Type II      | -40°C to +85°C    | 74LVC573A DB          | 74LVC573A DB  | SOT339-1    |
| 20-Pin Plastic Thin Shrink Small Outline (TSSOP) Type I | -40°C to +85°C    | 74LVC573A PW          | 7LVC573APW DH | SOT360-1    |


# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A


## PIN DESCRIPTION

| PIN NUMBER                     | SYMBOL          | FUNCTION                         |
|--------------------------------|-----------------|----------------------------------|
| 1                              | $\overline{OE}$ | Output enable input (active-Low) |
| 2, 3, 4, 5, 6, 7, 8, 9         | D0-D7           | Data inputs                      |
| 19, 18, 17, 16, 15, 14, 13, 12 | Q0-Q7           | Data outputs                     |
| 10                             | GND             | Ground (0V)                      |
| 11                             | LE              | Latch enable input (active-High) |
| 20                             | V <sub>CC</sub> | Positive supply voltage          |


## PIN CONFIGURATION




## LOGIC SYMBOL (IEEE/IEC)



## FUNCTIONAL DIAGRAM




## LOGIC SYMBOL



# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

## LOGIC DIAGRAM



## FUNCTION TABLE

| OPERATING MODES                                | INPUTS          |    |       | INTERNAL LATCHES | OUTPUTS        |
|--|-----------------|----|-------|------------------|----------------|
|  | $\overline{OE}$ | LE | $D_n$ |                  | $Q_0$ to $Q_7$ |
| Enable and read register<br>(transparent mode) | L               | H  | L     | L                | L              |
|  | L               | H  | H     | H                | H              |
| Latch and read register                        | L               | L  | l     | L                | L              |
|  | L               | L  | h     | H                | H              |
| Latch register and<br>disable outputs          | H               | L  | l     | L                | Z              |
|  | H               | L  | h     | H                | Z              |

H = HIGH voltage level  
 h = HIGH voltage level one setup time prior to the HIGH-to-LOW LE transition  
 L = LOW voltage level  
 l = LOW voltage level one setup time prior to the HIGH-to-LOW LE transition  
 X = Don't care  
 Z = High impedance OFF-state

# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

## RECOMMENDED OPERATING CONDITIONS

| SYMBOL                          | PARAMETER   | CONDITIONS   | LIMITS |                 | UNIT |
|---------------------------------|---|--|--------|-----------------|------|
|                                 |   |  | MIN    | MAX             |      |
| V <sub>CC</sub>                 | DC supply voltage (for max. speed performance)    |  | 2.7    | 3.6             | V    |
|                                 | DC supply voltage (for low-voltage applications)  |  | 1.2    | 3.6             |      |
| V <sub>I</sub>                  | DC Input voltage range                            |  | 0      | 5.5             | V    |
| V <sub>O</sub>                  | DC output voltage range; output HIGH or LOW state |  | 0      | V <sub>CC</sub> | V    |
|                                 | DC output voltage range; output 3-State           |  | 0      | 5.5             |      |
| T <sub>amb</sub>                | Operating ambient temperature range in free-air   |  | -40    | +85             | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input rise and fall times                         | V <sub>CC</sub> = 1.2 to 2.7V<br>V <sub>CC</sub> = 2.7 to 3.6V | 0<br>0 | 20<br>10        | ns/V |

## ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

In accordance with the Absolute Maximum Rating System (IEC 134)  
Voltages are referenced to GND (ground = 0V)

| SYMBOL                             | PARAMETER   | CONDITIONS   | RATING                        | UNIT |
|------------------------------------|---|--|-------------------------------|------|
| V <sub>CC</sub>                    | DC supply voltage   |  | -0.5 to +6.5                  | V    |
| I <sub>IK</sub>                    | DC input diode current  | V <sub>I</sub> < 0   | -50                           | mA   |
| V <sub>I</sub>                     | DC input voltage  | Note 2   | -0.5 to +6.5                  | V    |
| I <sub>OK</sub>                    | DC output diode current   | V <sub>O</sub> > V <sub>CC</sub> or V <sub>O</sub> < 0                               | ± 50                          | mA   |
| V <sub>O</sub>                     | DC output voltage; output HIGH or LOW state                             | Note 2   | -0.5 to V <sub>CC</sub> + 0.5 | V    |
|                                    | DC output voltage; output 3-State                                       | Note 2   | -0.5 to 6.5                   |      |
| I <sub>O</sub>                     | DC output source or sink current  | V <sub>O</sub> = 0 to V <sub>CC</sub>  | ± 50                          | mA   |
| I <sub>GND</sub> , I <sub>CC</sub> | DC V <sub>CC</sub> or GND current                                       |  | ± 100                         | mA   |
| T <sub>stg</sub>                   | Storage temperature range   |  | -65 to +150                   | °C   |
| P <sub>TOT</sub>                   | Power dissipation per package   |  |                               |      |
|                                    | - plastic mini-pack (SO)<br>- plastic shrink mini-pack (SSOP and TSSOP) | above +70°C derate linearly with 8 mW/K<br>above +60°C derate linearly with 5.5 mW/K | 500<br>500                    | mW   |

### NOTES:

- Stresses beyond those listed may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

## DC ELECTRICAL CHARACTERISTICS

Over recommended operating conditions voltages are referenced to GND (ground = 0V)

| SYMBOL           | PARAMETER   | TEST CONDITIONS  | LIMITS                |                  |      | UNIT |
|------------------|---|--|-----------------------|------------------|------|------|
|                  |   |  | Temp = -40°C to +85°C |                  |      |      |
|                  |   |  | MIN                   | TYP <sup>1</sup> | MAX  |      |
| V <sub>IH</sub>  | HIGH level Input voltage                          | V <sub>CC</sub> = 1.2V   | V <sub>CC</sub>       |                  |      | V    |
|                  |   | V <sub>CC</sub> = 2.7 to 3.6V  | 2.0                   |                  |      |      |
| V <sub>IL</sub>  | LOW level Input voltage                           | V <sub>CC</sub> = 1.2V   |                       |                  | GND  | V    |
|                  |   | V <sub>CC</sub> = 2.7 to 3.6V  |                       |                  | 0.8  |      |
| V <sub>OH</sub>  | HIGH level output voltage                         | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -12mA       | V <sub>CC</sub> - 0.5 |                  |      | V    |
|                  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -100μA      | V <sub>CC</sub> - 0.2 | V <sub>CC</sub>  |      |      |
|                  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -18mA       | V <sub>CC</sub> - 0.6 |                  |      |      |
|                  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = -24mA       | V <sub>CC</sub> - 0.8 |                  |      |      |
| V <sub>OL</sub>  | LOW level output voltage                          | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 12mA        |                       |                  | 0.40 | V    |
|                  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100μA       |                       | GND              | 0.20 |      |
|                  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 24mA        |                       |                  | 0.55 |      |
| I <sub>I</sub>   | Input leakage current <sup>2</sup>                | V <sub>CC</sub> = 3.6V; V <sub>I</sub> = 5.5V or GND   |                       | ±0.1             | ±5   | μA   |
| I <sub>OZ</sub>  | 3-State output OFF-state current                  | V <sub>CC</sub> = 3.6V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; V <sub>O</sub> = 5.5V or GND |                       | 0.1              | ±10  | μA   |
| I <sub>off</sub> | Power off leakage supply                          | V <sub>CC</sub> = 0.0V; V <sub>I</sub> or V <sub>O</sub> = 5.5V  |                       | 0.1              | ±10  | μA   |
| I <sub>CC</sub>  | Quiescent supply current                          | V <sub>CC</sub> = 3.6V; V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0                        |                       | 0.1              | 10   | μA   |
| ΔI <sub>CC</sub> | Additional quiescent supply current per input pin | V <sub>CC</sub> = 2.7V to 3.6V; V <sub>I</sub> = V <sub>CC</sub> - 0.6V; I <sub>O</sub> = 0                |                       | 5                | 500  | μA   |

### NOTES:

- All typical values are at V<sub>CC</sub> = 3.3V and T<sub>amb</sub> = 25°C.
- The specified overdrive current at the data input forces the data input to the opposite logic input state.

## AC CHARACTERISTICS

GND = 0V; t<sub>r</sub> = t<sub>f</sub> ≤ 2.5ns; C<sub>L</sub> = 50pF; R<sub>L</sub> = 500Ω; T<sub>amb</sub> = -40°C to +85°C.

| SYMBOL                               | PARAMETER   | WAVEFORM | LIMITS                       |                  |     |                        |     |                        | UNIT |
|--------------------------------------|---|----------|------------------------------|------------------|-----|------------------------|-----|------------------------|------|
|                                      |   |          | V <sub>CC</sub> = 3.3V ±0.3V |                  |     | V <sub>CC</sub> = 2.7V |     | V <sub>CC</sub> = 1.2V |      |
|                                      |   |          | MIN                          | TYP <sup>1</sup> | MAX | MIN                    | MAX | TYP                    |      |
| t <sub>PHL</sub><br>t <sub>PLH</sub> | Propagation delay<br>D <sub>n</sub> to Q <sub>n</sub> | 1, 5     | 1.5                          | 4.3              | 6.2 | 1.5                    | 7.2 | 19                     | ns   |
| t <sub>PHL</sub><br>t <sub>PLH</sub> | Propagation delay<br>LE to Q <sub>n</sub>             | 2, 5     | 1.5                          | 4.6              | 6.5 | 1.5                    | 7.5 | 21                     | ns   |
| t <sub>PZH</sub><br>t <sub>PZL</sub> | 3-State output enable time<br>OE to Q <sub>n</sub>    | 2, 5     | 1.5                          | 3.8              | 7.5 | 1.5                    | 8.5 | 17                     | ns   |
| t <sub>PHZ</sub><br>t <sub>PLZ</sub> | 3-State output disable time<br>OE to Q <sub>n</sub>   | 3, 5     | 1.5                          | 3.5              | 6.0 | 1.5                    | 6.5 | 15                     | ns   |
| t <sub>W</sub>                       | LE pulse width HIGH                                   | 2        | 3.2                          | 1.6              | –   | 3.2                    | –   | –                      | ns   |
| t <sub>SU</sub>                      | Setup time<br>D <sub>n</sub> to LE                    | 4        | 1.7                          | 0.3              | –   | 1.7                    | –   | –                      | ns   |
| t <sub>H</sub>                       | Hold time<br>D <sub>n</sub> to LE                     | 4        | 1.4                          | 0.2              | –   | 1.5                    | –   | –                      | ns   |

### NOTE:


- Unless otherwise stated, all typical values are at V<sub>CC</sub> = 3.3V and T<sub>amb</sub> = 25°C.

# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)


74LVC573A

## AC WAVEFORMS


$V_M = 1.5V$  at  $V_{CC} \geq 2.7V$ ;  $V_M = 0.5 V_{CC}$  at  $V_{CC} < 2.7V$ .  
 $V_{OL}$  and  $V_{OH}$  are the typical output voltage drop that occur with the output load.  
 $V_X = V_{OL} + 0.3V$  at  $V_{CC} \geq 2.7V$ ;  $V_X = V_{OL} + 0.1 V_{CC}$  at  $V_{CC} < 2.7V$   
 $V_Y = V_{OH} - 0.3V$  at  $V_{CC} \geq 2.7V$ ;  $V_Y = V_{OH} - 0.1 V_{CC}$  at  $V_{CC} < 2.7V$




Waveform 1. Input ( $D_n$ ) to output ( $Q_n$ ) propagation delays.



Waveform 2. Latch enable input (LE) pulse width, the latch enable input to output ( $Q_n$ ) propagation delays




Waveform 3. 3-State enable and disable times.



Waveform 4. Data setup and hold times for the  $D_n$  input to the LE input.

## TEST CIRCUIT



Test Circuit for 3-State Outputs

### SWITCH POSITION

| TEST              | SWITCH       |
|-------------------|--------------|
| $t_{PLH}/t_{PHL}$ | Open         |
| $t_{PLZ}/t_{PZL}$ | $2 * V_{CC}$ |
| $t_{PHZ}/t_{PZH}$ | GND          |

| $V_{CC}$     | $V_{IN}$ |
|--------------|----------|
| $< 2.7V$     | $V_{CC}$ |
| $2.7 - 3.6V$ | $2.7V$   |

### DEFINITIONS

$R_L$  = Load resistor  
 $C_L$  = Load capacitance includes jig and probe capacitance  
 $R_T$  = Termination resistance should be equal to  $Z_{OUT}$  of pulse generators.

SW00047


Waveform 5. Load circuitry for switching times.

Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

SO20: plastic small outline package; 20 leads; body width 7.5 mm

SOT163-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT   | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c              | D <sup>(1)</sup> | E <sup>(1)</sup> | e     | H <sub>E</sub> | L     | L <sub>p</sub> | Q              | v    | w    | y     | Z <sup>(1)</sup> | θ        |
|--------|--------|----------------|----------------|----------------|----------------|----------------|------------------|------------------|-------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm     | 2.65   | 0.30<br>0.10   | 2.45<br>2.25   | 0.25           | 0.49<br>0.36   | 0.32<br>0.23   | 13.0<br>12.6     | 7.6<br>7.4       | 1.27  | 10.65<br>10.00 | 1.4   | 1.1<br>0.4     | 1.1<br>1.0     | 0.25 | 0.25 | 0.1   | 0.9<br>0.4       | 8°<br>0° |
| inches | 0.10   | 0.012<br>0.004 | 0.096<br>0.089 | 0.01           | 0.019<br>0.014 | 0.013<br>0.009 | 0.51<br>0.49     | 0.30<br>0.29     | 0.050 | 0.419<br>0.394 | 0.055 | 0.043<br>0.016 | 0.043<br>0.039 | 0.01 | 0.01 | 0.004 | 0.035<br>0.016   |          |

Note

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT163-1        | 075E04     | MS-013AC |      |  |                     | 95-01-24<br>97-05-22 |

Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

SSOP20: plastic shrink small outline package; 20 leads; body width 5.3 mm

SOT339-1



DIMENSIONS (mm are the original dimensions)

| UNIT | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c            | D <sup>(1)</sup> | E <sup>(1)</sup> | e    | H <sub>E</sub> | L    | L <sub>p</sub> | Q          | v   | w    | y   | z <sup>(1)</sup> | θ        |
|------|--------|----------------|----------------|----------------|----------------|--------------|------------------|------------------|------|----------------|------|----------------|------------|-----|------|-----|------------------|----------|
| mm   | 2.0    | 0.21<br>0.05   | 1.80<br>1.65   | 0.25           | 0.38<br>0.25   | 0.20<br>0.09 | 7.4<br>7.0       | 5.4<br>5.2       | 0.65 | 7.9<br>7.6     | 1.25 | 1.03<br>0.63   | 0.9<br>0.7 | 0.2 | 0.13 | 0.1 | 0.9<br>0.5       | 8°<br>0° |

Note

1. Plastic or metal protrusions of 0.20 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT339-1        |            | MO-150AE |      |  |                     | 93-09-08<br>95-02-04 |

Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

TSSOP20: plastic thin shrink small outline package; 20 leads; body width 4.4 mm

SOT360-1



DIMENSIONS (mm are the original dimensions)

| UNIT | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c          | D <sup>(1)</sup> | E <sup>(2)</sup> | e    | H <sub>E</sub> | L   | L <sub>p</sub> | Q          | v   | w    | y   | Z <sup>(1)</sup> | θ        |
|------|--------|----------------|----------------|----------------|----------------|------------|------------------|------------------|------|----------------|-----|----------------|------------|-----|------|-----|------------------|----------|
| mm   | 1.10   | 0.15<br>0.05   | 0.95<br>0.80   | 0.25           | 0.30<br>0.19   | 0.2<br>0.1 | 6.6<br>6.4       | 4.5<br>4.3       | 0.65 | 6.6<br>6.2     | 1.0 | 0.75<br>0.50   | 0.4<br>0.3 | 0.2 | 0.13 | 0.1 | 0.5<br>0.2       | 8°<br>0° |

Notes

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT360-1        |            | MO-153AC |      |  |                     | 93-06-16<br>95-02-04 |

---

Octal D-type transparent latch with 5-volt  
tolerant inputs/outputs (3-State)

---

74LVC573A

NOTES



# Octal D-type transparent latch with 5-volt tolerant inputs/outputs (3-State)

74LVC573A

## Data sheet status

| Data sheet status         | Product status | Definition [1]   |
|---------------------------|----------------|--|
| Objective specification   | Development    | This data sheet contains the design target or goal specifications for product development. Specification may change in any manner without notice.  |
| Preliminary specification | Qualification  | This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. |
| Product specification     | Production     | This data sheet contains final specifications. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.   |

[1] Please consult the most recently issued datasheet before initiating or completing a design.

## Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors  
811 East Arques Avenue  
P.O. Box 3409  
Sunnyvale, California 94088-3409  
Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1998  
All rights reserved. Printed in U.S.A.

print code

Date of release: 08-98

Document order number:

9397-750-04513

*Let's make things better.*