

# DATA SHEET

EEPW 电子产品世界  
.com.cn

## 74LV574

Octal D-type flip-flop;  
positive edge-trigger (3-State)

Product specification  
Supersedes data of 1997 Feb 03  
IC24 Data Handbook

1998 Jun 10

## Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

## FEATURES

- Wide operating voltage: 1.0 to 5.5V
- Optimized for Low Voltage applications: 1.0 to 3.6V
- Accepts TTL input levels between  $V_{CC} = 2.7V$  and  $V_{CC} = 3.6V$
- Typical  $V_{OLP}$  (output ground bounce)  $< 0.8V$  at  $V_{CC} = 3.3V$ ,  $T_{amb} = 25^{\circ}C$
- Typical  $V_{OHV}$  (output  $V_{OH}$  undershoot)  $> 2V$  at  $V_{CC} = 3.3V$ ,  $T_{amb} = 25^{\circ}C$
- Common 3-State output enable input
- Output capability: bus driver
- $I_{CC}$  category: MSI

## DESCRIPTION

The 74LV574 is a low-voltage Si-gate CMOS device and is pin and function compatible with 74HC/HCT574.

The 74LV574 is an octal D-type flip-flop featuring separate D-type inputs for each flip-flop and non-inverting 3-state outputs for bus oriented applications. A clock (CP) and an output enable (OE) input are common to all flip-flops.

The eight flip-flops will store the state of their individual D-inputs that meet the set-up and hold times requirements on the LOW-to-HIGH CP transition.

When OE is LOW, the contents of the eight flip-flops is available at the outputs. When OE is HIGH, the outputs go to the high impedance OFF-state. Operation of the OE input does not affect the state of the flip-flops.

## QUICK REFERENCE DATA

GND = 0V;  $T_{amb} = 25^{\circ}C$ ;  $t_r = t_f \leq 2.5$  ns

| SYMBOL            | PARAMETER                                   | CONDITIONS                      | TYPICAL | UNIT |
|-------------------|---|---------------------------------|---------|------|
| $t_{PHL}/t_{PLH}$ | Propagation delay CP to $Q_n$               | $C_L = 15pF$<br>$V_{CC} = 3.3V$ | 13      | ns   |
| $f_{max}$         | Maximum clock frequency                     | $C_L = 15pF$ , $V_{CC} = 3.3V$  | 77      | MHz  |
| $C_I$             | Input capacitance                           |                                 | 3.5     | pF   |
| $C_{PD}$          | Power dissipation capacitance per flip-flop | Notes 1 and 2                   | 25      | pF   |

## NOTES:

- $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu W$ )  
 $P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum (C_L \times V_{CC}^2 \times f_o)$  where:  
 $f_i$  = input frequency in MHz;  $C_L$  = output load capacity in pF;  
 $f_o$  = output frequency in MHz;  $V_{CC}$  = supply voltage in V;  
 $\sum (C_L \times V_{CC}^2 \times f_o)$  = sum of the outputs.
- The condition is  $V_I = GND$  to  $V_{CC}$

## ORDERING AND PACKAGE INFORMATION

| PACKAGES                    | TEMPERATURE RANGE | OUTSIDE NORTH AMERICA | NORTH AMERICA | PKG. DWG. # |
|-----------------------------|-------------------|-----------------------|---------------|-------------|
| 20-Pin Plastic DIL          | -40°C to +125°C   | 74LV574 N             | 74LV574 N     | SOT146-1    |
| 20-Pin Plastic SO           | -40°C to +125°C   | 74LV574 D             | 74LV574 D     | SOT163-1    |
| 20-Pin Plastic SSOP Type II | -40°C to +125°C   | 74LV574 DB            | 74LV574 DB    | SOT339-1    |
| 20-Pin Plastic TSSOP Type I | -40°C to +125°C   | 74LV574 PW            | 74LV574PW DH  | SOT360-1    |

## PIN DESCRIPTION

| PIN NUMBER                        | SYMBOL          | FUNCTION                                  |
|-----------------------------------|-----------------|---|
| 1                                 | $\overline{OE}$ | Output enabled input (active LOW)         |
| 2, 3, 4, 5,<br>6, 7, 8, 9         | D0-D7           | Data inputs                               |
| 19, 18, 17, 16,<br>15, 14, 13, 12 | Q0-Q7           | 3-State flip-flop outputs                 |
| 10                                | GND             | Ground (0V)                               |
| 11                                | CP              | Clock input (LOW-to-HIGH, edge-triggered) |
| 20                                | VCC             | Positive supply voltage                   |

## FUNCTION TABLE

| OPERATING MODES                   | INPUTS |            |    | INTERNAL FLIP-FLOPS | OUTPUTS Q0 to Q7 |
|-----------------------------------|--------|------------|----|---------------------|------------------|
|                                   | OE     | CP         | Dn |                     |                  |
| Load and read register            | L      | $\uparrow$ | l  | L                   | L                |
|                                   | L      | $\uparrow$ | h  | H                   | H                |
| Load register and disable outputs | H      | $\uparrow$ | l  | L                   | Z                |
|                                   | H      | $\uparrow$ | h  | H                   | Z                |

H = HIGH voltage level

h = HIGH voltage level one set-up time prior to the LOW-to-HIGH CP transition

L = LOW voltage level

l = LOW voltage level one set-up time prior to the LOW-to-HIGH CP transition


Z = High impedance OFF-state

$\uparrow$  = LOW-to-HIGH clock transition


Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574


PIN CONFIGURATION




LOGIC SYMBOL (IEEE/IEC)



LOGIC SYMBOL




FUNCTIONAL DIAGRAM



## Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

## LOGIC DIAGRAM

ABSOLUTE MAXIMUM RATINGS<sup>1, 2</sup>

In accordance with the Absolute Maximum Rating System (IEC 134)  
 Voltages are referenced to GND (ground = 0V)

| SYMBOL                         | PARAMETER  | CONDITIONS  | RATING            | UNIT |
|--------------------------------|--|---|-------------------|------|
| $V_{CC}$                       | DC supply voltage  |   | -0.5 to +7.0      | V    |
| $\pm I_{IK}$                   | DC input diode current   | $V_I < -0.5$ or $V_I > V_{CC} + 0.5V$   | 20                | mA   |
| $\pm I_{OK}$                   | DC output diode current  | $V_O < -0.5$ or $V_O > V_{CC} + 0.5V$   | 50                | mA   |
| $\pm I_O$                      | DC output source or sink current<br>- bus driver outputs   | $-0.5V < V_O < V_{CC} + 0.5V$   | 35                | mA   |
| $\pm I_{GND},$<br>$\pm I_{CC}$ | DC $V_{CC}$ or GND current for types with<br>-bus driver outputs   |   | 70                | mA   |
| $T_{stg}$                      | Storage temperature range  |   | -65 to +150       | °C   |
| $P_{TOT}$                      | Power dissipation per package<br>-plastic DIL<br>-plastic mini-pack (SO)<br>-plastic shrink mini-pack (SSOP and TSSOP) | for temperature range: -40 to +125°C<br>above +70°C derate linearly with 12mW/K<br>above +70°C derate linearly with 8 mW/K<br>above +60°C derate linearly with 5.5 mW/K | 750<br>500<br>400 | mW   |

## NOTES:

- Stresses beyond those listed may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

## RECOMMENDED OPERATING CONDITIONS

| SYMBOL     | PARAMETER                                       | CONDITIONS   | MIN              | TYP.             | MAX                     | UNIT |
|------------|---|--|------------------|------------------|-------------------------|------|
| $V_{CC}$   | DC supply voltage                               | See Note <sup>1</sup>  | 1.0              | 3.3              | 5.5                     | V    |
| $V_I$      | Input voltage                                   |  | 0                | -                | $V_{CC}$                | V    |
| $V_O$      | Output voltage                                  |  | 0                | -                | $V_{CC}$                | V    |
| $T_{amb}$  | Operating ambient temperature range in free air | See DC and AC characteristics  | -40<br>-40       |                  | +85<br>+125             | °C   |
| $t_r, t_f$ | Input rise and fall times                       | $V_{CC} = 1.0V$ to $2.0V$<br>$V_{CC} = 2.0V$ to $2.7V$<br>$V_{CC} = 2.7V$ to $3.6V$<br>$V_{CC} = 3.6V$ to $5.5V$ | -<br>-<br>-<br>- | -<br>-<br>-<br>- | 500<br>200<br>100<br>50 | ns/V |

## NOTES:

- The LV is guaranteed to function down to  $V_{CC} = 1.0V$  (input levels GND or  $V_{CC}$ ); DC characteristics are guaranteed from  $V_{CC} = 1.2V$  to  $V_{CC} = 5.5V$ .

## Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

**DC CHARACTERISTICS FOR THE LV FAMILY**

Over recommended operating conditions voltages are referenced to GND (ground = 0V)

| SYMBOL   | PARAMETER                                     | TEST CONDITIONS   | LIMITS              |                  |                     |                     |                     | UNIT |
|--|---|---|---------------------|------------------|---------------------|---------------------|---------------------|------|
|  |   |   | -40°C to +85°C      |                  |                     | -40°C to +125°C     |                     |      |
|  |   |   | MIN                 | TYP <sup>1</sup> | MAX                 | MIN                 | MAX                 |      |
| V <sub>IH</sub>  | HIGH level Input voltage                      | V <sub>CC</sub> = 1.2V  | 0.9                 |                  |                     | 0.9                 |                     | V    |
|  |   | V <sub>CC</sub> = 2.0V  | 1.4                 |                  |                     | 1.4                 |                     |      |
|  |   | V <sub>CC</sub> = 2.7 to 3.6V   | 2.0                 |                  |                     | 2.0                 |                     |      |
|  |   | V <sub>CC</sub> = 4.5 to 5.5V   | 0.7*V <sub>CC</sub> |                  |                     | 0.7*V <sub>CC</sub> |                     |      |
| V <sub>IL</sub>  | LOW level Input voltage                       | V <sub>CC</sub> = 1.2V  |                     |                  | 0.3                 |                     | 0.3                 | V    |
|  |   | V <sub>CC</sub> = 2.0V  |                     |                  | 0.6                 |                     | 0.6                 |      |
|  |   | V <sub>CC</sub> = 2.7 to 3.6V   |                     |                  | 0.8                 |                     | 0.8                 |      |
|  |   | V <sub>CC</sub> = 4.5 to 5.5  |                     |                  | 0.3*V <sub>CC</sub> |                     | 0.3*V <sub>CC</sub> |      |
| V <sub>OH</sub>  | HIGH level output voltage; all outputs        | V <sub>CC</sub> = 1.2V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 100µA                 |                     | 1.2              |                     |                     |                     | V    |
|  |   | V <sub>CC</sub> = 2.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 100µA                 | 1.8                 | 2.0              |                     | 1.8                 |                     |      |
|  |   | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 100µA                 | 2.5                 | 2.7              |                     | 2.5                 |                     |      |
|  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 100µA                 | 2.8                 | 3.0              |                     | 2.8                 |                     |      |
|  |   | V <sub>CC</sub> = 4.5V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 100µA                 | 4.3                 | 4.5              |                     | 4.3                 |                     |      |
|  | HIGH level output voltage; BUS driver outputs | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 8mA                   | 2.40                | 2.82             |                     | 2.20                |                     |      |
| V <sub>CC</sub> = 4.5V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; -I <sub>O</sub> = 16mA |   | 3.60  | 4.20                |                  | 3.50                |                     |                     |      |
| V <sub>OL</sub>  | LOW level output voltage; all outputs         | V <sub>CC</sub> = 1.2V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100µA                  |                     | 0                |                     |                     |                     | V    |
|  |   | V <sub>CC</sub> = 2.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100µA                  |                     | 0                | 0.2                 |                     | 0.2                 |      |
|  |   | V <sub>CC</sub> = 2.7V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100µA                  |                     | 0                | 0.2                 |                     | 0.2                 |      |
|  |   | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100µA                  |                     | 0                | 0.2                 |                     | 0.2                 |      |
|  |   | V <sub>CC</sub> = 4.5V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 100µA                  |                     | 0                | 0.2                 |                     | 0.2                 |      |
|  | LOW level output voltage; BUS driver outputs  | V <sub>CC</sub> = 3.0V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 8mA                    |                     | 0.20             | 0.40                |                     | 0.50                |      |
|  |   | V <sub>CC</sub> = 4.5V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; I <sub>O</sub> = 16mA                   |                     | 0.35             | 0.55                |                     | 0.65                |      |
| I <sub>I</sub>   | Input leakage current                         | V <sub>CC</sub> = 5.5V; V <sub>I</sub> = V <sub>CC</sub> or GND   |                     |                  | 1.0                 |                     | 1.0                 | µA   |
| I <sub>OZ</sub>  | 3-State output OFF-state current              | V <sub>CC</sub> = 5.5V; V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; V <sub>O</sub> = V <sub>CC</sub> or GND |                     |                  | 5                   |                     | 10                  | µA   |
| I <sub>CC</sub>  | Quiescent supply current; MSI                 | V <sub>CC</sub> = 5.5V; V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0                                   |                     |                  | 20.0                |                     | 160                 | µA   |
| ΔI <sub>CC</sub>   | Additional quiescent supply current per input | V <sub>CC</sub> = 2.7V to 3.6V; V <sub>I</sub> = V <sub>CC</sub> - 0.6V   |                     |                  | 500                 |                     | 850                 | µA   |

**NOTE:**1. All typical values are measured at T<sub>amb</sub> = 25°C.

## Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

**AC CHARACTERISTICS**GND = 0V;  $t_r = t_f \leq 2.5\text{ns}$ ;  $C_L = 50\text{pF}$ ;  $R_L = 1\text{K}\Omega$ 

| SYMBOL            | PARAMETER                                  | WAVEFORM    | CONDITION  | LIMITS<br>-40 to +85 °C |                 |     | LIMITS<br>-40 to +125 °C |     | UNIT |
|-------------------|--|-------------|------------|-------------------------|-----------------|-----|--------------------------|-----|------|
|                   |  |             |            | $V_{CC}(\text{V})$      | MIN             | TYP | MAX                      | MIN |      |
| $t_{PHL}/t_{PLH}$ | Propagation delay<br>CP to Qn              | Figure 1, 4 | 1.2        | –                       | 80              | –   | –                        | –   | ns   |
|                   |  |             | 2.0        | –                       | 27              | 34  | –                        | 43  |      |
|                   |  |             | 2.7        | –                       | 20              | 25  | –                        | 31  |      |
|                   |  |             | 3.0 to 3.6 | –                       | 15 <sup>2</sup> | 20  | –                        | 25  |      |
|                   |  |             | 4.5 to 5.5 | –                       | –               | 17  | –                        | 21  |      |
| $t_{PZH}/t_{PZL}$ | 3-State output<br>enable time<br>OE to Qn  | Figure 2, 4 | 1.2        | –                       | 70              | –   | –                        | –   | ns   |
|                   |  |             | 2.0        | –                       | 24              | 34  | –                        | 43  |      |
|                   |  |             | 2.7        | –                       | 18              | 25  | –                        | 31  |      |
|                   |  |             | 3.0 to 3.6 | –                       | 13 <sup>2</sup> | 20  | –                        | 25  |      |
|                   |  |             | 4.5 to 5.5 | –                       | –               | 17  | –                        | 21  |      |
| $t_{PHZ}/t_{PLZ}$ | 3-State output<br>disable time<br>OE to Qn | Figure 2, 4 | 1.2        | –                       | 75              | –   | –                        | –   | ns   |
|                   |  |             | 2.0        | –                       | 27              | 27  | –                        | 34  |      |
|                   |  |             | 2.7        | –                       | 21              | 21  | –                        | 26  |      |
|                   |  |             | 3.0 to 3.6 | –                       | 16 <sup>2</sup> | 17  | –                        | 21  |      |
|                   |  |             | 4.5 to 5.5 | –                       | –               | 15  | –                        | 18  |      |
| $t_W$             | Clock pulse width<br>HIGH or LOW           | Figure 1    | 2.0        | 34                      | 9               | –   | 41                       | –   | ns   |
|                   |  |             | 2.7        | 25                      | 6               | –   | 30                       | –   |      |
|                   |  |             | 3.0 to 3.6 | 20                      | 5 <sup>2</sup>  | –   | 24                       | –   |      |
| $t_{su}$          | Set-up time<br>Dn to CP                    | Figure 3    | 1.2        | –                       | 10              | –   | –                        | –   | ns   |
|                   |  |             | 2.0        | 22                      | 4               | –   | 26                       | –   |      |
|                   |  |             | 2.7        | 16                      | 3               | –   | 19                       | –   |      |
|                   |  |             | 3.0 to 3.6 | 13                      | 2 <sup>2</sup>  | –   | 15                       | –   |      |
| $t_h$             | Hold time<br>Dn to CP                      | Figure 3    | 1.2        | –                       | -10             | –   | –                        | –   | ns   |
|                   |  |             | 2.0        | 5                       | -4              | –   | 5                        | –   |      |
|                   |  |             | 2.7        | 5                       | -3              | –   | 5                        | –   |      |
|                   |  |             | 3.0 to 3.6 | 5                       | -2 <sup>2</sup> | –   | 5                        | –   |      |
| $f_{max}$         | Maximum clock<br>pulse frequency           | Figure 1    | 2.0        | 15                      | 40              | –   | 12                       | –   | MHz  |
|                   |  |             | 2.7        | 19                      | 58              | –   | 16                       | –   |      |
|                   |  |             | 3.0 to 3.6 | 24                      | 70 <sup>2</sup> | –   | 20                       | –   |      |

**NOTE:**

1. Unless otherwise stated, all typical values are at  $T_{amb} = 25^\circ\text{C}$ .
2. Typical value measured at  $V_{CC} = 3.3\text{V}$ .

# Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

## AC WAVEFORMS

$V_M = 1.5V$  at  $V_{CC} \geq 2.7V$  and  $\leq 3.6V$   
 $V_M = 0.5 * V_{CC}$  at  $V_{CC} < 2.7V$  and  $\geq 4.5V$   
 $V_{OL}$  and  $V_{OH}$  are the typical output voltage drop that occur with the output load.  
 $V_X = V_{OL} + 0.3V$  at  $V_{CC} \geq 2.7V$  and  $\leq 3.6V$   
 $V_X = V_{OL} + 0.1V_{CC}$  at  $V_{CC} < 2.7V$  and  $\geq 4.5V$   
 $V_Y = V_{OH} - 0.3V$  at  $V_{CC} \geq 2.7V$  and  $\leq 3.6V$   
 $V_Y = V_{OH} - 0.1V_{CC}$  at  $V_{CC} < 2.7V$  and  $\geq 4.5V$




Figure 1. Clock (CP) to output (Qn) propagation delays, the clock pulse (CP) and the maximum clock pulse frequency




Figure 2. 3-state enable and disable times





Figure 3. Data set-up and hold times for the Dn input to the CP input

**NOTE:**  
The shaded areas indicate when the input is permitted to change for predictable output performance.

## TEST CIRCUIT



### DEFINITIONS

$R_L$  = Load resistor  
 $C_L$  = Load capacitance includes jig and probe capacitance.  
 $R_T$  = Termination resistance should be equal to  $Z_{OUT}$  of pulse generators.

### SWITCH POSITION

| TEST                               | S <sub>1</sub>      | V <sub>CC</sub> | V <sub>I</sub>  |
|------------------------------------|---------------------|-----------------|-----------------|
| t <sub>PLH</sub> /t <sub>PHL</sub> | Open                | < 2.7V          | V <sub>CC</sub> |
| t <sub>PLZ</sub> /t <sub>PZL</sub> | 2 * V <sub>CC</sub> | 2.7–3.6V        | 2.7V            |
| t <sub>PHZ</sub> /t <sub>PZH</sub> | GND                 | ≥ 4.5V          | V <sub>CC</sub> |

SV00896


Figure 4. Load circuitry for switching times

Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

DIP20: plastic dual in-line package; 20 leads (300 mil)

SOT146-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT   | A max. | A <sub>1</sub> min. | A <sub>2</sub> max. | b              | b <sub>1</sub> | c              | D <sup>(1)</sup> | E <sup>(1)</sup> | e    | e <sub>1</sub> | L            | M <sub>E</sub> | M <sub>H</sub> | w     | Z <sup>(1)</sup> max. |
|--------|--------|---------------------|---------------------|----------------|----------------|----------------|------------------|------------------|------|----------------|--------------|----------------|----------------|-------|-----------------------|
| mm     | 4.2    | 0.51                | 3.2                 | 1.73<br>1.30   | 0.53<br>0.38   | 0.36<br>0.23   | 26.92<br>26.54   | 6.40<br>6.22     | 2.54 | 7.62           | 3.60<br>3.05 | 8.25<br>7.80   | 10.0<br>8.3    | 0.254 | 2.0                   |
| inches | 0.17   | 0.020               | 0.13                | 0.068<br>0.051 | 0.021<br>0.015 | 0.014<br>0.009 | 1.060<br>1.045   | 0.25<br>0.24     | 0.10 | 0.30           | 0.14<br>0.12 | 0.32<br>0.31   | 0.39<br>0.33   | 0.01  | 0.078                 |

Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES |       |       |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|-------|-------|--|---------------------|----------------------|
|                 | IEC        | JEDEC | EIAJ  |  |                     |                      |
| SOT146-1        |            |       | SC603 |  |                     | 92-11-17<br>95-05-24 |




Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

SO20: plastic small outline package; 20 leads; body width 7.5 mm

SOT163-1



**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**

| UNIT   | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c              | D <sup>(1)</sup> | E <sup>(1)</sup> | e     | H <sub>E</sub> | L     | L <sub>p</sub> | Q              | v    | w    | y     | Z <sup>(1)</sup> | θ        |
|--------|--------|----------------|----------------|----------------|----------------|----------------|------------------|------------------|-------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm     | 2.65   | 0.30<br>0.10   | 2.45<br>2.25   | 0.25           | 0.49<br>0.36   | 0.32<br>0.23   | 13.0<br>12.6     | 7.6<br>7.4       | 1.27  | 10.65<br>10.00 | 1.4   | 1.1<br>0.4     | 1.1<br>1.0     | 0.25 | 0.25 | 0.1   | 0.9<br>0.4       | 8°<br>0° |
| inches | 0.10   | 0.012<br>0.004 | 0.096<br>0.089 | 0.01           | 0.019<br>0.014 | 0.013<br>0.009 | 0.51<br>0.49     | 0.30<br>0.29     | 0.050 | 0.42<br>0.39   | 0.055 | 0.043<br>0.016 | 0.043<br>0.039 | 0.01 | 0.01 | 0.004 | 0.035<br>0.016   |          |

**Note**

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT163-1        | 075E04     | MS-013AC |      |  |                     | 92-11-17<br>95-01-24 |

Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

SSOP20: plastic shrink small outline package; 20 leads; body width 5.3 mm

SOT339-1



**DIMENSIONS** (mm are the original dimensions)

| UNIT | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c            | D <sup>(1)</sup> | E <sup>(1)</sup> | e    | H <sub>E</sub> | L    | L <sub>p</sub> | Q          | v   | w    | y   | z <sup>(1)</sup> | θ        |
|------|--------|----------------|----------------|----------------|----------------|--------------|------------------|------------------|------|----------------|------|----------------|------------|-----|------|-----|------------------|----------|
| mm   | 2.0    | 0.21<br>0.05   | 1.80<br>1.65   | 0.25           | 0.38<br>0.25   | 0.20<br>0.09 | 7.4<br>7.0       | 5.4<br>5.2       | 0.65 | 7.9<br>7.6     | 1.25 | 1.03<br>0.63   | 0.9<br>0.7 | 0.2 | 0.13 | 0.1 | 0.9<br>0.5       | 8°<br>0° |

**Note**

1. Plastic or metal protrusions of 0.20 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT339-1        |            | MO-150AE |      |  |                     | 93-09-08<br>95-02-04 |

Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

TSSOP20: plastic thin shrink small outline package; 20 leads; body width 4.4 mm

SOT360-1



**DIMENSIONS (mm are the original dimensions)**

| UNIT | A max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c          | D <sup>(1)</sup> | E <sup>(2)</sup> | e    | H <sub>E</sub> | L   | L <sub>p</sub> | Q          | v   | w    | y   | Z <sup>(1)</sup> | θ        |
|------|--------|----------------|----------------|----------------|----------------|------------|------------------|------------------|------|----------------|-----|----------------|------------|-----|------|-----|------------------|----------|
| mm   | 1.10   | 0.15<br>0.05   | 0.95<br>0.80   | 0.25           | 0.30<br>0.19   | 0.2<br>0.1 | 6.6<br>6.4       | 4.5<br>4.3       | 0.65 | 6.6<br>6.2     | 1.0 | 0.75<br>0.50   | 0.4<br>0.3 | 0.2 | 0.13 | 0.1 | 0.5<br>0.2       | 8°<br>0° |

**Notes**

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES |          |      |  | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|----------|------|--|---------------------|----------------------|
|                 | IEC        | JEDEC    | EIAJ |  |                     |                      |
| SOT360-1        |            | MO-153AC |      |  |                     | 93-06-16<br>95-02-04 |

## Octal D-type flip-flop; positive edge-trigger (3-State)

74LV574

## DEFINITIONS

| Data Sheet Identification        | Product Status                | Definition   |
|----------------------------------|-------------------------------|--|
| <i>Objective Specification</i>   | <b>Formative or in Design</b> | This data sheet contains the design target or goal specifications for product development. Specifications may change in any manner without notice.   |
| <i>Preliminary Specification</i> | <b>Preproduction Product</b>  | This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. |
| <i>Product Specification</i>     | <b>Full Production</b>        | This data sheet contains Final Specifications. Philips Semiconductors reserves the right to make changes at any time without notice, in order to improve design and supply the best possible product.  |

Philips Semiconductors and Philips Electronics North America Corporation reserve the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified. Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## LIFE SUPPORT APPLICATIONS

Philips Semiconductors and Philips Electronics North America Corporation Products are not designed for use in life support appliances, devices, or systems where malfunction of a Philips Semiconductors and Philips Electronics North America Corporation Product can reasonably be expected to result in a personal injury. Philips Semiconductors and Philips Electronics North America Corporation customers using or selling Philips Semiconductors and Philips Electronics North America Corporation Products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors and Philips Electronics North America Corporation for any damages resulting from such improper use or sale.

**Philips Semiconductors**  
 811 East Arques Avenue  
 P.O. Box 3409  
 Sunnyvale, California 94088-3409  
 Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1998  
 All rights reserved. Printed in U.S.A.

print code

Date of release: 05-96

Document order number:

9397-750-04454

*Let's make things better.*