



Microsemi Corp.
The diode experts.

SCOTTSDALE, AZ
For more information call:
(602) 941-6300

30S SERIES

DESCRIPTION/FEATURES

- ECONOMICAL SERIES
- HIGH SURGE, 150 AMP MAXIMUM
- UNIVERSAL REPLACEMENT FOR MANY GLASS, EPOXY, ENCAPSULATED, AND METALLIC RECTIFIERS
- PEAK REVERSE VOLTAGES THROUGH 1000 VOLTS

VOLTAGE RATINGS

| Part Number | V_{RRM} - Working Peak Reverse Voltage (V) | V_R - Max. Direct Reverse Voltage (V) |
|-------------|--|--|
| | $T_J = -65^\circ\text{C}$ to 175°C | $T_J = -65^\circ\text{C}$ to 175°C |
| 30S1 | 100 | 100 |
| 30S2 | 200 | 200 |
| 30S3 | 300 | 300 |
| 30S4 | 400 | 400 |
| 30S5 | 500 | 500 |
| 30S6 | 600 | 600 |
| 30S8 | 800 | 800 |
| 30S10 | 1000 | 1000 |

ELECTRICAL SPECIFICATIONS


| Parameter | Value | Units | Conditions |
|---|-------|---------------|---|
| $I_{F(AV)}$ Max. average forward current | 3.0 | A | 1 phase operation, 180° conduction, $T_L = 125^\circ\text{C}$, lead length 9.5 mm (0.375 in.) |
| I_{FSM} Max. peak one-cycle non-repetitive surge current | 143 | A | Half cycle 50 Hz sine wave or 6 ms rectangular pulse |
| | 150 | | Following any rated load condition and with rated V_{RRM} applied. |
| | 170 | | Half cycle 60 Hz sine wave or 5 ms rectangular pulse |
| | 178 | | Half cycle 50 Hz sine wave or 6 ms rectangular pulse |
| I^2t Max. I^2t for fusing | 103 | A^2s | $t = 10$ ms With rated V_{RRM} applied following surge, initial $T_J = 175^\circ\text{C}$. |
| | 94 | | $t = 8.3$ ms |
| Max. I^2t for individual device fusing | 146 | A^2s | $t = 10$ ms With $V_{RRM} = 0$ following surge, initial $T_J = 175^\circ\text{C}$. |
| | 133 | | $t = 8.3$ ms |
| $I^2\sqrt{t}$ Max. $I^2\sqrt{t}$ for individual device fusing | 1450 | $A^2\sqrt{s}$ | $t = 0.1$ to 10 ms, $V_{RRM} = 0$ following surge. |
| V_{FM} Max. peak forward voltage | 1.0 | V | $I_{F(AV)} = 3A$ (9.4A peak); $T_J = 25^\circ\text{C}$. |
| $I_{R(AV)}$ Max. average reverse current | 0.3 | mA | Max. rated $I_{F(AV)}$, V_{RRM} and $T_L = 100^\circ\text{C}$. ($\ell = 9.5$ mm (0.375 in.)) |

① I^2t for time $t_x = I^2\sqrt{t} \cdot \sqrt{t_x}$.

THERMAL-MECHANICAL SPECIFICATIONS

| Parameter | Value | Units | Conditions |
|---|--------------|------------------|--|
| T_J Max. operating junction temperature range | -65 to 175 | $^\circ\text{C}$ | |
| T_{stg} Max. storage temperature range | -65 to 175 | $^\circ\text{C}$ | |
| R_{thJC} Max. internal thermal resistance, junction-to-lead | 16.5 | deg. C/W | DC operation, double-side cooled, measured 9.5 mm (0.375 in.) from body. |
| wt Approximate weight | 0.65 (0.023) | g (oz.) | |

3 AMP MEDIUM POWER SILICON RECTIFIER DIODES



Cathode Indicated by Color Band
All Dimensions in Inches (Millimeters).

MECHANICAL CHARACTERISTICS

CASE: Molded plastic use Flame Retardant Epoxy.

TERMINALS: Axial leads, solderable per MIL-STD-202, Method 208.

POLARITY: Color band denotes cathode.

MOUNTING POSITION: Any.

30S Series

RATING AND CHARACTERISTIC CURVES




Fig. 1 - Average Forward Current Vs. Lead Temperature at Heat Sinks, $l = 9.5$ mm (3/8 Inch) (Single Phase Operation)




Fig. 2 - Maximum Forward Voltage Vs. Forward Current




Fig. 3 - Maximum Forward Power Loss Vs. Forward Current (Sinusoidal Current Waveform)




Fig. 4 - Maximum Transient Thermal Impedance, Junction-to-Lead, Vs. Pulse Duration




Fig. 5 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses