



WXA SERIES
105°C Miniaturized low profile.
◆FEATURES

- 9~25mm height.
- RoHS compliance.


◆SPECIFICATIONS

Items	Characteristics																																															
Category Temperature Range	-55~+105°C	-40~+105°C	-25~+105°C																																													
Rated Voltage Range	6.3~50V.DC	160~250V.DC	350~450V.DC																																													
Capacitance Tolerance	±20%(20°C, 120Hz)																																															
Leakage Current(MAX)	6.3~50V.DC	160~450V.DC																																														
	I=0.01CV or 3 μA whichever is greater. (After 2 minutes application of rated voltage)	CV ≤ 1000	CV > 1000																																													
		I=0.1CV+40 μA (1 minute) I=0.03CV+15 μA (5 minutes)	I=0.04CV+100 μA (1 minute) I=0.02CV+25 μA (5 minutes)																																													
	I=Leakage Current(μA)	C=Rated Capacitance(μF)	V=Rated Voltage(V)																																													
Dissipation Factor(MAX) (tan δ)	Rated Voltage (V)											(20°C, 120Hz)																																				
	<table border="1"> <tr> <td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>160</td><td>200</td><td>250</td><td>350</td><td>400</td><td>450</td> </tr> <tr> <td>φ 8, φ 10</td><td>0.30</td><td>0.26</td><td>0.20</td><td>0.18</td><td>0.14</td><td>0.12</td><td>0.20</td><td>0.20</td><td>0.20</td><td>0.20</td><td>0.25</td> </tr> <tr> <td>φ 12.5~φ 18</td><td>0.26</td><td>0.22</td><td>0.18</td><td>0.16</td><td>0.14</td><td>0.12</td><td>0.20</td><td>0.20</td><td>0.20</td><td>0.20</td><td>0.25</td> </tr> </table>												6.3	10	16	25	35	50	160	200	250	350	400	450	φ 8, φ 10	0.30	0.26	0.20	0.18	0.14	0.12	0.20	0.20	0.20	0.20	0.25	φ 12.5~φ 18	0.26	0.22	0.18	0.16	0.14	0.12	0.20	0.20	0.20	0.20	0.25
6.3	10	16	25	35	50	160	200	250	350	400	450																																					
φ 8, φ 10	0.30	0.26	0.20	0.18	0.14	0.12	0.20	0.20	0.20	0.20	0.25																																					
φ 12.5~φ 18	0.26	0.22	0.18	0.16	0.14	0.12	0.20	0.20	0.20	0.20	0.25																																					
When rated capacitance is over 1000 μF, tan δ shall be added 0.02 to the listed value with increase of every 1000 μF.																																																
Endurance	After applying rated voltage with rated ripple current for 2000hrs at 105°C, the capacitors shall meet the following requirements.																																															
	Capacitance Change		Within ±25% of the initial value.																																													
Dissipation Factor		Not more than 200% of the specified value.																																														
Leakage Current		Not more than the specified value.																																														
Low Temperature Stability Impedance Ratio(MAX)	Rated Voltage (V)											(120Hz)																																				
	<table border="1"> <tr> <td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>160</td><td>200</td><td>250</td><td>350</td><td>400</td><td>450</td> </tr> <tr> <td>Z(-25°C)/Z(20°C)</td><td>4</td><td>3</td><td>2</td><td>2</td><td>2</td><td>2</td><td>3</td><td>3</td><td>3</td><td>6</td><td>6</td><td>6</td> </tr> <tr> <td>Z(-40°C)/Z(20°C)</td><td>8</td><td>6</td><td>4</td><td>4</td><td>3</td><td>3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>												6.3	10	16	25	35	50	160	200	250	350	400	450	Z(-25°C)/Z(20°C)	4	3	2	2	2	2	3	3	3	6	6	6	Z(-40°C)/Z(20°C)	8	6	4	4	3	3	-	-	-	-
6.3	10	16	25	35	50	160	200	250	350	400	450																																					
Z(-25°C)/Z(20°C)	4	3	2	2	2	2	3	3	3	6	6	6																																				
Z(-40°C)/Z(20°C)	8	6	4	4	3	3	-	-	-	-	-	-																																				

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency (Hz)	60 (50)	120	500	1k	10k ≤	
Coefficient	1.5~6.8 μF	0.65	1.0	1.20	1.30	1.50
	10~68 μF	0.8	1.0	1.20	1.30	1.50
	100~1000 μF	0.8	1.0	1.10	1.15	1.20
	2200~10000 μF	0.8	1.0	1.05	1.10	1.15

◆PART NUMBER

□□□	WXA	□□□□□	□	□□□	□□	DXL
Rated Voltage	Series	Rated Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

