




Dimensions: dimensions are in mm



Specification

400ST120	Transmitter
400SR120	Receiver
Center Frequency	40.0±1.0Khz
Bandwidth (-6dB)	400ST120 2.0Khz 400SR120 2.0Khz
Transmitting Sound Pressure Level	115dB min.
at 40.0Khz; 0dB re 0.0002μbar per 10Vrms at 30cm	
Receiving Sensitivity	-67dB min.
at 40.0Khz 0dB = 1 volt/μbar	
Capacitance at 1Khz	±20% 2400 pF
Max. Driving Voltage (cont.)	20Vrms
Total Beam Angle	-6dB 85° typical
Operation Temperature	-30 to 80°C
Storage Temperature	-40 to 85°C

All specification taken typical at 25°C
Closer frequency tolerance can be supplied upon request.


Model available:

1	400ST/R120	Aluminum Housing
2	400ST/R12B	Black Al. Housing

Impedance/Phase Angle vs. Frequency


Tested under 1Vrms Oscillation Level

400SR120 Impedance ————
 400SR120 Phase ————
 400ST120 Impedance ······
 400ST120 Phase ······




Sensitivity/Sound Pressure Level

Tested under 10Vrms @30cm



Beam Angle: Tested at 40.0Khz frequency





400SR120 Receiver

400ST120 Transmitter



Sensitivity Variation vs. Loaded Resistor

SPL Variation vs. Driving Voltage





Center Frequency Shift vs. Loaded Resistor

Center Frequency Shift vs. Driving Voltage



Sensitivity Variation vs. Temperature

SPL Variation vs. Temperature



Center Frequency Shift vs. Temperature

Center Frequency Shift vs. Temperature

