


KBU4A ...KBU4M; KBU6A ...KBU6M; KBU8A ...KBU8M

4.0A/6.0A/8.0A SINGLE - PHASE SILICON BRIDGE

Features

- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- Plastic material has Underwriters Laboratory Flammability Classification 94V-0.
- Surge overload rating - 200 amperes peak
- Mounting Position: Any
- Mounting Torque: 5 In. lb. max
- U/L recognized file # 142814

VOLTAGE RANGE
50 to 1000 Volts
CURRENT
4.0/6.0/8.0 Amperes




Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless specified Resistive or inductive load, 60 Hz.
For capacitive load, derate current by 20%.

| | KBU4A | KBU4B | KBU4D | KBU4G | KBU4J | KBU4K | KBU4M | |
|--|--------------|-----------|-------|-----------|-------|-------|-----------|---------------------|
| | KBU6A | KBU6B | KBU6D | KBU6G | KBU6J | KBU6K | KBU6M | |
| | KBU8A | KBU8B | KBU8D | KBU8G | KBU8J | KBU8K | KBU8M | UNITS |
| Maximum Recurrent Peak Reverse Voltage | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Max RMS Bridge Input Voltage | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Maximum DC Blocking Voltage | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum Average Forward Rectified Output Current at $T_C = 100\text{ }^\circ\text{C}$ $T_A = 50\text{ }^\circ\text{C}/40\text{ }^\circ\text{C}/45\text{ }^\circ\text{C}$ | | 40 40 | | 60 60 | | | 80 60 | A A |
| Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | | 200 | | 250 | | | 300 | A |
| Maximum Instantaneous Forward Voltage Drop per element at 3.0A/3.0A/8.0A | | 1.0 | | 1.0 | | | 1.0 | V |
| Maximum Reverse Leakage at rated $T_A = 25\text{ }^\circ\text{C}$ DC Block Voltage per element $T_C = 100\text{ }^\circ\text{C}$ | | 10 100 | | 10 200 | | | 10 300 | μA mA |
| Operating and storage temperature Range, T_J, T_{STG} | -65 to + 150 | | | | | | | $^\circ\text{C}$ |



SEMTECH ELECTRONICS LTD.
(wholly owned subsidiary of HONEY TECHNOLOGY LTD.)



KBU4A ...KBU4M; KBU6A ...KBU6M; KBU8A ...KBU8M 4.0A/6.0A/8.0A SINGLE - PHASE SILICON BRIDGE

RATING AND CHARACTERISTICS CURVES

KBU4/6/8 SERIES

FIG. 1-DERATING CURVE FOR
OUTPUT RECTIFIED CURRENT




FIG. 2-TYPICAL INSTANTANEOUS FORWARD
CHARACTERISTICS




FIG. 3-MAXIMUM NON RETETITIVE PEAK
FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE
CHARACTERISTICS







FIG. 5-TYPICAL JUNCTION CAPACITANCE
PER ELEMENT



SEMTECH ELECTRONICS LTD.
(wholly owned subsidiary of HONEY TECHNOLOGY LTD.)

