

## FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

## SPECIFICATIONS

### Material

**Coating:** Conformal silicone-ceramic.

**Core:** Ceramic.

**Terminals:** Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

### Derating

Linearly from  
100% @ +25°C to  
0% @ +275°C.

### Electrical

**Tolerance:** ±5% (J type), ±1% (F type) (other tolerances available).

**Power rating:** Based on 25°C free air rating (other wattages available).


**Overload:** Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.

**Temperature coefficient:** Under 1Ω: ±90 ppm/°C  
1Ω to 9.99Ω: ±50 ppm/°C  
10Ω and over: ±20 ppm/°C



# 40 Series

## Ohmicone® Silicone-Ceramic Conformal Axial Term. Wirewound, 1% and 5% Tol. Std.



Series	Wattage	Ohms	Dimensions (in. / mm)		Voltage	Lead ga.
			Length	Diam.		
41	1.0	0.10-6K	0.437 / 11.1	0.125 / 3.2	150	24
42	2.0	0.10-8K	0.406 / 10.3	0.219 / 5.6	100	20
43	3.0	0.10-20K	0.593 / 15.1	0.218 / 5.5	200	20
45	5.0	0.10-70K	0.937 / 23.8	0.343 / 8.7	460	18
47	7.0	0.10-80K	1.280 / 32.5	0.343 / 8.7	670	18
40	10.0	0.10-150K	1.642 / 41.7	0.406 / 10.3	1000	18

Non-Inductive versions available. Insert "N" before tolerance code. Example: 42NJ27R

Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

## ORDERING INFO

40 Series  
Ohmicone®  
Silicone Ceramic  
Conformal Axial  
Term. Wirewound

Non-Inductive  
Winding  
Optional (blank  
= std. winding)

RoHS  
Compliant

**41NJR10E**

Wattage	Tolerance	Resistance Value
1 = 1W	F = 1%	R10 = 0.10Ω
2	J = 5%	1R0 = 1.0Ω
3		10R = 10.0Ω
5		250 = 250Ω
7		1K0 = 1,000Ω
0 = 10W		4K5 = 4,500Ω
		50K = 50,000Ω

## STANDARD PART NUMBERS FOR 40 SERIES

		Wattage and Tolerance												Wattage and Tolerance												Wattage and Tolerance																																																																																																																																																																																																																																																																																																																																					
		1% Tolerance					5% Tolerance							1% Tolerance					5% Tolerance							1% Tolerance					5% Tolerance																																																																																																																																																																																																																																																																																																																																
Ohmic value	Part No. Prefix Suffix	1	3	5	10	1	2	3	5	10	Ohmic value	Part No. Prefix Suffix	1	3	5	10	1	2	3	5	10	Ohmic value	Part No. Prefix Suffix	1	3	5	10	1	2	3	5	10	Ohmic value	Part No. Prefix Suffix	1	3	5	10	1	2	3	5	10	Ohmic value	Part No. Prefix Suffix	1	3	5	10	1	2	3	5	10																																																																																																																																																																																																																																																																																																									
0.1	R10	✓	✓	✓	✓	✓	✓	✓	✓	✓	68	68R	✓	✓	✓	✓	✓	✓	✓	✓	✓	2,200	2K2	✓	✓	✓	✓	✗	✗	✓	✓	✓	2,500	2K5	✓	✓	✓	✓	✓	✗	✓	✓	✓	2,700	2K7	✓	✓	✓	✓	✗	✗	✓	✓	✓	3,000	3K0	✓	✓	✓	✓	✓	✓	✓	✓	✓	3,300	3K3	✓	✓	✓	✓	✗	✗	✓	✓	✓	3,500	3K5	✓	✓	✓	✓	✗	✗	✓	✓	✓	3,900	3K9	✓	✓	✓	✓	✗	✗	✓	✓	✓	4,000	4K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	4,500	4K5	✓	✓	✓	✓	✗	✗	✓	✓	✓	4,700	4K7	✓	✓	✓	✓	✗	✗	✓	✓	✓	5,000	5K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	6,000	6K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	6,800	6K8	✓	✓	✓	✓	✓	✓	✓	✓	✓	7,000	7K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	7,500	7K5	✓	✓	✓	✓	✗	✗	✓	✓	✓	8,000	8K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	9,000	9K0	✓	✓	✓	✓	✗	✗	✓	✓	✓	10,000	10K	✓	✓	✓	✓	✓	✓	✓	✓	✓	12,000	12K	✓	✓	✓	✓	✗	✗	✓	✓	✓	13,000	13K	✓	✓	✓	✓	✗	✗	✓	✓	✓	15,000	15K	✓	✓	✓	✓	✗	✗	✓	✓	✓	17,000	17K	✓	✓	✓	✓	✗	✗	✓	✓	✓	20,000	20K	✓	✓	✓	✓	✗	✗	✓	✓	✓	22,000	22K	✓	✓	✓	✓	✓	✓	✓	✓	✓	25,000	25K	✓	✓	✓	✓	✗	✗	✓	✓	✓	30,000	30K	✓	✓	✓	✓	✗	✗	✓	✓	✓	33,000	33K	✓	✓	✓	✓	✗	✗	✓	✓	✓	35,000	35K	✓	✓	✓	✓	✗	✗	✓	✓	✓	40,000	40K	✓	✓	✓	✓	✗	✗	✓	✓	✓	50,000	50K	✓	✓	✓	✓	✗	✗	✓	✓	✓

✓ = Standard values  
✗ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Check product availability at [www.ohmite.com](http://www.ohmite.com)