

$V_{DSM} = 1800 \text{ V}$
 $I_{TAVM} = 1660 \text{ A}$
 $I_{TRMS} = 2610 \text{ A}$
 $I_{TSM} = 21000 \text{ A}$
 $V_{T0} = 0.83 \text{ V}$
 $r_T = 0.230 \text{ m}\Omega$

Phase Control Thyristor

5STP 18F1800

Doc. No. 5SYA1028-04 Sep. 01

- Patented free-floating silicon technology
- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability

Blocking

Part Number	5STP 18F1800	5STP 18F1600	5STP 18F1200	Conditions	
V _{DRM} V _{RRM}	1800 V	1600 V	1200 V	f = 50 Hz, t _p = 10ms	
V _{RSM1}	2000 V	1800 V	1400 V	t _p = 5ms, single pulse	
I _{DRM}	≤ 200 mA			V _{DRM}	T _j = 125°C
I _{RRM}	≤ 200 mA			V _{RRM}	
dV/dt _{crit}	1000 V/μs			Exp. to 0.67 x V _{DRM} , T _j = 125°C	

Mechanical data

F_M	Mounting force	nom.	22 kN
		min.	14 kN
		max.	24 kN
a	Acceleration		
	Device unclamped		50 m/s ²
	Device clamped		100 m/s ²
m	Weight		0.6 kg
D_S	Surface creepage distance		25 mm
D_a	Air strike distance		14 mm




ABB Semiconductors AG reserves the right to change specifications without notice.

ABB

On-state

I _{TAVM}	Max. average on-state current	1660 A	Half sine wave, T _C = 70°C	
I _{TRMS}	Max. RMS on-state current	2610 A		
I _{TSM}	Max. peak non-repetitive	21000 A	tp = 10 ms	T _j = 125°C
	surge current	22000 A	tp = 8.3 ms	After surge:
I ² t	Limiting load integral	2205 kA ² s	tp = 10 ms	V _D = V _R = 0V
		2008 kA ² s	tp = 8.3 ms	
V _T	On-state voltage	1.30 V	I _T = 2000 A	T _j = 125°C
V _{T0}	Threshold voltage	0.83 V	I _T = 1000 - 3000 A	
r _T	Slope resistance	0.230 mΩ		
I _H	Holding current	20-70 mA	T _j = 25°C	
		15-60 mA	T _j = 125°C	
I _L	Latching current	100- mA	T _j = 25°C	
		50-200 mA	T _j = 125°C	

Switching

di/dt_{crit}	Critical rate of rise of on-state current	150 A/ μs	Cont. $f = 50\text{ Hz}$	$V_D \leq 0.67 \cdot V_{DRM}$, $T_j = 125^\circ\text{C}$ $I_{TRM} = 2000\text{ A}$ $I_{FG} = 2\text{ A}$, $t_r = 0.5\text{ }\mu\text{s}$
		300 A/ μs	60 sec. $f = 50\text{ Hz}$	
t_d	Delay time	$\leq 3.0\text{ }\mu\text{s}$	$V_D = 0.4 \cdot V_{DRM}$	$I_{FG} = 2\text{ A}$, $t_r = 0.5\text{ }\mu\text{s}$
t_q	Turn-off time	$\leq 400\text{ }\mu\text{s}$	$V_D \leq 0.67 \cdot V_{DRM}$ $dv_D/dt = 20\text{ V}/\mu\text{s}$	$I_{TRM} = 2000\text{ A}$, $T_j = 125^\circ\text{C}$ $V_R > 200\text{ V}$, $di_T/dt = -20\text{ A}/\mu\text{s}$
Q_{rr}	Recovery charge	min	2500 μAs	
		max	4500 μAs	

Triggering

V_{GT}	Gate trigger voltage	2.6 V	$T_j = 25^\circ$
I_{GT}	Gate trigger current	400 mA	$T_j = 25^\circ$
V_{GD}	Gate non-trigger voltage	0.3 V	$V_D = 0.4 \times V_{DRM}$
I_{GD}	Gate non-trigger current	10 mA	$V_D = 0.4 \times V_{DRM}$
V_{FGM}	Peak forward gate voltage	12 V	
I_{FGM}	Peak forward gate current	10 A	
V_{RGM}	Peak reverse gate voltage	10 V	
P_G	Gate power loss	3 W	

Thermal

T_{jmax}	Max. operating junction temperature range	125 °C	
T_{stg}	Storage temperature range	-40...140 °C	
R_{thJC}	Thermal resistance junction to case	33 K/kW	Anode side cooled
		35 K/kW	Cathode side cooled
		17 K/kW	Double side cooled
R_{thCH}	Thermal resistance case to heat sink	8 K/kW	Single side cooled
		4 K/kW	Double side cooled

Analytical function for transient thermal impedance:

$$Z_{thJC}(t) = \sum_{i=1}^n R_i(1 - e^{-t/\tau_i})$$

i	1	2	3	4
$R_i(K/kW)$	10.35	3.76	2.29	0.67
$\tau_i(s)$	0.3723	0.0525	0.0057	0.0023




Fig. 1 Transient thermal impedance junction to case.




Fig. 2 On-state characteristics.




Fig. 3 On-state characteristics.
 $T_j=125^{\circ}C$, 10ms half sine




Fig. 4 On-state power dissipation vs. mean on-state current. Turn-on losses excluded.




Fig. 5 Max. permissible case temperature vs. mean on-state current.




Fig. 6 Surge on-state current vs. pulse length. Half-sine wave.




Fig. 7 Surge on-state current vs. number of pulses. Half-sine wave, 10 ms, 50Hz.




Fig. 8 Gate trigger characteristics.




Fig. 9 Max. peak gate power loss.




Fig. 10 Recovery charge vs. decay rate of on-state current.




Fig. 11 Peak reverse recovery current vs. decay rate of on-state current.

ABB Semiconductors AG reserves the right to change specifications without notice.



ABB Semiconductors AG
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Telephone +41 (0)62 888 6419
Fax +41 (0)62 888 6306
Email abbsem@ch.abb.com
Internet www.abbsem.com