



# Micro-D Backshells EMI, Elliptical, One Piece 500-047



**Elliptical Backshells** provide extra room for large wire bundles. This one piece version features an oversize shield termination area for both standard and micro **BAND-IT®** shield termination straps.

| MATERIALS |                            |
|-----------|----------------------------|
| Shell     | Aluminum Alloy 6061 -T6    |
| Clips     | 17-7PH Stainless Steel     |
| Hardware  | 300 Series Stainless Steel |

## HOW TO ORDER 500-047 ELLIPTICAL BACKSHELLS

| Series             | Shell Finish                        | Connector Size | Hardware Option                     | EMI Band Strap Option                                 |
|--------------------|-------------------------------------|----------------|-------------------------------------|---|
| 500-047            | <b>E</b> – Chem Film                | <b>09</b>      | <b>B</b> – Fillister Head Jackscrew | <b>Omit (Leave Blank)</b><br><b>Band Not Included</b> |
|                    | <b>J</b> – Cadmium, Yellow Chromate | <b>15</b>      |                                     |   |
|                    | <b>M</b> – Electroless Nickel       | <b>21</b>      | <b>H</b> – Hex Head Jackscrew       |   |
|                    | <b>NF</b> – Cadmium, Olive Drab     | <b>25</b>      |                                     |   |
|                    | <b>31</b>                           | <b>67</b>      | <b>E</b> – Extended Jackscrew       |   |
|                    | <b>37</b>                           | <b>100</b>     |                                     |   |
| <b>Z2</b> – Gold   |                                     |                |                                     | <b>B</b> – Standard Band<br>.250" Wide                |
|                    |                                     |                |                                     | <b>M</b> – Micro Band<br>.125" Wide                   |
| Sample Part Number |                                     |                |                                     |   |
| 500-047            | – M                                 | 25             | H                                   |   |



| Size | A Max. |       | B Max. |       | C     |       | D Max. |       | E    |      | F Max. |       | G Max. |       | H Max. |       |
|------|--------|-------|--------|-------|-------|-------|--------|-------|------|------|--------|-------|--------|-------|--------|-------|
|      | In.    | mm.   | In.    | mm.   | In.   | mm.   | In.    | mm.   | In.  | mm.  | In.    | mm.   | In.    | mm.   | In.    | mm.   |
| 09   | .850   | 21.59 | .370   | 9.40  | .565  | 14.35 | .312   | 7.92  | .281 | 7.14 | .450   | 11.43 | .481   | 12.22 | .780   | 19.81 |
| 15   | 1.000  | 25.40 | .370   | 9.40  | .715  | 18.16 | .420   | 10.67 | .281 | 7.14 | .450   | 11.43 | .589   | 14.96 | .910   | 23.11 |
| 21   | 1.150  | 29.21 | .370   | 9.40  | .865  | 21.97 | .591   | 15.01 | .281 | 7.14 | .450   | 11.43 | .759   | 19.28 | 1.030  | 26.16 |
| 25   | 1.250  | 31.75 | .370   | 9.40  | .965  | 24.51 | .690   | 17.53 | .281 | 7.14 | .450   | 11.43 | .859   | 21.82 | 1.090  | 27.68 |
| 31   | 1.400  | 35.56 | .370   | 9.40  | 1.115 | 28.32 | .820   | 20.83 | .281 | 7.14 | .450   | 11.43 | .989   | 25.12 | 1.150  | 29.21 |
| 37   | 1.550  | 39.37 | .370   | 9.40  | 1.265 | 32.13 | .970   | 24.64 | .281 | 7.14 | .450   | 11.43 | 1.139  | 28.93 | 1.180  | 29.97 |
| 51   | 1.500  | 38.10 | .410   | 10.41 | 1.215 | 30.86 | .920   | 23.37 | .312 | 7.92 | .481   | 12.22 | 1.089  | 27.66 | 1.220  | 30.99 |
| 51-2 | 1.910  | 48.51 | .370   | 9.40  | 1.615 | 41.02 | 1.030  | 26.16 | .281 | 7.14 | .450   | 11.43 | 1.489  | 37.82 | 1.220  | 30.99 |
| 67   | 2.310  | 58.67 | .370   | 9.40  | 2.015 | 51.18 | 1.720  | 43.69 | .281 | 7.14 | .450   | 11.43 | 1.889  | 47.98 | 1.220  | 30.99 |
| 69   | 1.810  | 45.97 | .410   | 10.41 | 1.515 | 38.48 | 1.220  | 30.99 | .312 | 7.92 | .481   | 12.22 | 1.389  | 35.28 | 1.220  | 30.99 |
| 100  | 2.235  | 56.77 | .460   | 11.68 | 1.800 | 45.72 | 1.290  | 32.77 | .360 | 9.14 | .529   | 13.44 | 1.459  | 37.06 | 1.280  | 32.51 |