


**TIL111**

**TIL111-M**


**TIL117-M**

**MOC8100-M**

**WHITE PACKAGE (-M SUFFIX)**




**SCHEMATIC**



PIN 1. ANODE  
2. CATHODE  
3. NO CONNECTION  
4. EMITTER  
5. COLLECTOR  
6. BASE

**BLACK PACKAGE (NO -M SUFFIX)**



**DESCRIPTION**

The MOC8100, TIL111 and TIL117 optocouplers consist of a gallium arsenide infrared emitting diode driving a silicon phototransistor in a 6-pin dual in-line package.

**FEATURES**

- The TIL111 is also available in both black and white packages by specifying -M suffix, e.g. TIL111-M for the white package and no suffix for the black package.
- UL recognized (File # E90700)
- VDE recognized (File # 94766); (File #102497 for white package)
  - Add option V for white package (e.g., TIL111V-M)
  - Add option 300 for black package (e.g., TIL111.300)

**APPLICATIONS**

- Power supply regulators
- Digital logic inputs
- Microprocessor inputs
- Appliance sensor systems
- Industrial controls

**TIL111**

**TIL111-M**

**TIL117-M**

**MOC8100-M**

| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise specified)       |                    |                  |                        |                      |
|--|--------------------|------------------|------------------------|----------------------|
| Parameter  | Device             | Symbol           | Value                  | Units                |
| <b>TOTAL DEVICE</b>  |                    |                  |                        |                      |
| Storage Temperature  | All                | $T_{STG}$        | -55 to +150            | $^\circ\text{C}$     |
| Operating Temperature  | All                | $T_{OPR}$        | -55 to +100            | $^\circ\text{C}$     |
| Lead Solder Temperature  | All                | $T_{SOL}$        | 260 for 10 sec         | $^\circ\text{C}$     |
| Total Device Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | All                | $P_D$            | 250                    | mW                   |
|  |                    |                  | 3.3 (non-M), 2.94 (-M) | mW/ $^\circ\text{C}$ |
| <b>EMITTER</b>   |                    |                  |                        |                      |
| DC/Average Forward Input Current   | All                | $I_F$            | 100 (non-M), 60 (-M)   | mA                   |
| Reverse Input Voltage  | TIL111/TIL111-M    | $V_R$            | 3                      | V                    |
|  | MOC8100-M/TIL117-M |                  | 6                      |                      |
| Forward Current - Peak (300 $\mu\text{s}$ , 2% Duty Cycle)                                   | All                | $I_F(\text{pk})$ | 3                      | A                    |
| LED Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$          | All                | $P_D$            | 150 (non-M), 120 (-M)  | mW                   |
|  |                    |                  | 2.0 (non-M), 1.41 (-M) | mW/ $^\circ\text{C}$ |
| <b>DETECTOR</b>  |                    |                  |                        |                      |
| Collector-Emitter Voltage  | All                | $V_{CEO}$        | 30                     | V                    |
| Collector-Base Voltage   | All                | $V_{CBO}$        | 70                     | V                    |
| Emitter-Collector Voltage  | TIL111-M/TIL117-M  | $V_{ECO}$        | 7                      | V                    |
| Emitter-Base Voltage   | All                | $V_{EBO}$        | 7                      |                      |
| Detector Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$     | All                | $P_D$            | 150                    | mW                   |
|  |                    |                  | 2.0 (non-M), 1.76 (-M) | mW/ $^\circ\text{C}$ |

**TIL111**

**TIL111-M**

**TIL117-M**

**MOC8100-M**

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$  unless otherwise specified)

**INDIVIDUAL COMPONENT CHARACTERISTICS**

| Parameter                           | Test Conditions                                | Device   | Symbol                       | Min        | Typ*  | Max | Unit          |               |
|-------------------------------------|--|--|------------------------------|------------|-------|-----|---------------|---------------|
| <b>EMITTER</b>                      |  |  |                              |            |       |     |               |               |
| Input Forward Voltage               | $(I_F = 16 \text{ mA})$                        | $(T_A = 25^\circ\text{C})$                                 | TIL111/TIL111-M              |            | 1.2   | 1.4 | V             |               |
|                                     | $(I_F = 10 \text{ mA}; \text{ for MOC8100-M})$ | $(T_A = 0-70^\circ\text{C})$                               | MOC8100-M/<br>TIL117-M       |            | 1.2   | 1.4 |               |               |
|                                     | $(I_F = 16 \text{ mA}; \text{ for TIL117-M})$  | $(T_A = -55^\circ\text{C})$                                |                              |            | 1.32  |     |               |               |
|                                     |  | $(T_A = +100^\circ\text{C})$                               |                              |            | 1.10  |     |               |               |
| Reverse Leakage Current             |  | $(V_R = 3.0 \text{ V})$                                    | TIL111/TIL111-M/<br>TIL117-M | $I_R$      | 0.001 | 10  | $\mu\text{A}$ |               |
|                                     |  | $(V_R = 6.0 \text{ V})$                                    | MOC8100-M                    |            | 0.001 | 10  | $\mu\text{A}$ |               |
| <b>DETECTOR</b>                     |  |  |                              |            |       |     |               |               |
| Collector-Emitter Breakdown Voltage |  | $(I_C = 1.0 \text{ mA}, I_F = 0)$                          | All                          | $BV_{CEO}$ | 30    | 100 | V             |               |
| Collector-Base Breakdown Voltage    |  | $(I_C = 10 \mu\text{A}, I_F = 0)$                          | All                          | $BV_{CBO}$ | 70    | 120 | V             |               |
| Emitter-Base Breakdown Voltage      |  | $(I_E = 10 \mu\text{A}, I_F = 0)$                          | All                          | $BV_{EBO}$ | 7     | 10  | V             |               |
| Emitter-Collector Breakdown Voltage |  | $(I_F = 100 \mu\text{A}, I_F = 0)$                         | TIL111-M<br>TIL117-M         | $BV_{ECO}$ | 7     | 10  | V             |               |
| Collector-Emitter Dark Current      |  | $(V_{CE} = 10 \text{ V}, I_F = 0)$                         | TIL111/TIL111-M/<br>TIL117-M | $I_{CEO}$  |       | 1   | 50            | nA            |
|                                     |  | $(V_{CE} = 5 \text{ V}, T_A = 25^\circ\text{C})$           | MOC8100-M                    | $I_{CEO}$  |       | 0.5 | 25            | nA            |
|                                     |  | $(V_{CE} = 30 \text{ V}, I_F = 0, T_A = 70^\circ\text{C})$ | TIL117-M/<br>MOC8100-M       | $I_{CEO}$  |       | 0.2 | 50            | $\mu\text{A}$ |
| Collector-Base Dark Current         |  | $(V_{CB} = 10 \text{ V})$                                  | TIL111/TIL111-M/<br>TIL117-M | $I_{CBO}$  |       |     | 20            | nA            |
|                                     |  | $(V_{CB} = 5 \text{ V})$                                   | MOC8100-M                    | $I_{CBO}$  |       |     | 10            | nA            |
| Capacitance                         |  | $(V_{CE} = 0 \text{ V}, f = 1 \text{ MHz})$                | All                          | $C_{CE}$   |       | 8   | pF            |               |

**ISOLATION CHARACTERISTICS**

| Characteristic                 | Test Conditions  | Symbol    | Min       | Typ* | Max | Units    |
|--------------------------------|--|-----------|-----------|------|-----|----------|
| Input-Output Isolation Voltage | (Non '-M', Black Package) ( $f = 60 \text{ Hz}, t = 1 \text{ min}$ ) | $V_{ISO}$ | 5300      |      |     | Vac(rms) |
|                                | ('-M', White Package) ( $f = 60 \text{ Hz}, t = 1 \text{ sec}$ )     |           | 7500      |      |     | Vac(pk)  |
| Isolation Resistance           | $(V_{I-O} = 500 \text{ VDC})$  | $R_{ISO}$ | $10^{11}$ |      |     | $\Omega$ |
| Isolation Capacitance          | $(V_{I-O} = 0, f = 1 \text{ MHz})$                                   | $C_{ISO}$ |           |      | 2   | pF       |

Note

\* Typical values at  $T_A = 25^\circ\text{C}$  unless otherwise noted

**TIL111**

**TIL111-M**

**TIL117-M**

**MOC8100-M**

| <b>TRANSFER CHARACTERISTICS</b> ( $T_A = 25^\circ\text{C}$ Unless otherwise specified.) |   |   |               |            |             |               |               |               |
|---|---|---|---------------|------------|-------------|---------------|---------------|---------------|
| <b>DC Characteristic</b>  | <b>Test Conditions</b>  | <b>Symbol</b>   | <b>Device</b> | <b>Min</b> | <b>Typ*</b> | <b>Max</b>    | <b>Unit</b>   |               |
| Current Transfer Ratio, Collector to Emitter  | ( $I_F = 10\text{ mA}$ , $V_{CE} = 10\text{ V}$ )                                       | $CTR_{CE}$  | TIL117-M      | 50         |             |               | %             |               |
|   | ( $I_F = 1\text{ mA}$ , $V_{CE} = 5\text{ V}$ )   |   | MOC8100-M     | 50         |             |               | %             |               |
|   | ( $I_F = 1\text{ mA}$ , $V_{CE} = 5\text{ V}$ , $T_A = 0\text{ to }+70^\circ\text{C}$ ) |   |               | 30         |             |               |               |               |
| On-State Collector Current (Phototransistor Operation)                                  | ( $I_F = 16\text{ mA}$ , $V_{CE} = 0.4\text{ V}$ )                                      | $I_{C(ON)}$   | TIL111        | 2          |             |               | mA            |               |
| On-State Collector Current (Photodiode Operation)                                       | ( $I_F = 16\text{ mA}$ , $V_{CB} = 0.4\text{ V}$ )                                      |   | TIL111-M      | 7          |             |               | $\mu\text{A}$ |               |
| Collector-Emitter Saturation Voltage  | ( $I_C = 500\text{ }\mu\text{A}$ , $I_F = 10\text{ mA}$ )                               | $V_{CE(SAT)}$   | TIL117-M      |            |             | 0.4           | V             |               |
|   | ( $I_C = 2\text{ mA}$ , $I_F = 16\text{ mA}$ )  |   | TIL111        |            |             | 0.4           |               |               |
|   | ( $I_C = 100\text{ }\mu\text{A}$ , $I_F = 1\text{ mA}$ )                                |   | TIL111-M      |            |             | 0.4           |               |               |
| AC Characteristic   | $(I_C = 2\text{ mA}$ , $V_{CC} = 10\text{ V}$ , $R_L = 100\Omega$ ) (Fig. 20)           | $T_{ON}$  | MOC8100-M     |            |             | 20            | $\mu\text{s}$ |               |
|   |   |   | TIL117-M      |            |             | 10            |               |               |
| $T_{OFF}$   |   | MOC8100-M   |               |            | 20          | $\mu\text{s}$ |               |               |
|   |   | TIL117-M  |               |            | 10          |               |               |               |
| Rise Time   |   | $t_r$   | MOC8100-M     |            | 2           |               | $\mu\text{s}$ |               |
| Fall Time   |   | $t_f$   | TIL117-M      |            | 2           |               |               |               |
| Rise Time (Phototransistor Operation)   |   | $(I_{C(ON)} = 2\text{ mA}$ , $V_{CC} = 10\text{ V}$ , $R_L = 100\Omega$ ) (Fig. 20) | $t_r$         | TIL111     |             |               | 10            | $\mu\text{s}$ |
| Fall Time (Phototransistor Operation)   |   |   | $t_f$         |            | TIL111-M    |               |               |               |

\* Typical values at  $T_A = 25^\circ\text{C}$

TIL111


TIL111-M

TIL117-M


MOC8100-M

**TYPICAL PERFORMANCE CURVES**


**Fig. 1 LED Forward Voltage vs. Forward Current (Black Package)**




**Fig. 2 LED Forward Voltage vs. Forward Current (White Package)**




**Fig.3 Normalized CTR vs. Forward Current (Black Package)**




**Fig.4 Normalized CTR vs. Forward Current (White Package)**



**Fig. 5 Normalized CTR vs. Ambient Temperature (Black Package)**



**Fig. 6 Normalized CTR vs. Ambient Temperature (White Package)**




**TIL111**

**TIL111-M**


**TIL117-M**

**MOC8100-M**


**Fig. 7 CTR vs. RBE (Unsaturated)  
(Black Package)**




**Fig. 8 CTR vs. RBE (Unsaturated)  
(White Package)**




**Fig. 9 CTR vs. RBE (Saturated)  
(Black Package)**




**Fig. 10 CTR vs. RBE (Saturated)  
(White Package)**



**Fig. 11 Collector-Emitter Saturation Voltage vs Collector Current  
(Black Package)**



**Fig. 12 Collector-Emitter Saturation Voltage vs Collector Current  
(White Package)**




**TIL111**

**TIL111-M**


**TIL117-M**

**MOC8100-M**


**Fig. 13 Switching Speed vs. Load Resistor  
(Black Package)**




**Fig. 14 Switching Speed vs. Load Resistor  
(White Package)**




**Fig. 15 Normalized  $t_{on}$  vs.  $R_{BE}$   
(Black Package)**




**Fig. 16 Normalized  $t_{on}$  vs.  $R_{BE}$   
(White Package)**



**Fig. 17 Normalized  $t_{off}$  vs.  $R_{BE}$   
(Black Package)**



**Fig. 18 Normalized  $t_{off}$  vs.  $R_{BE}$   
(White Package)**



TIL111

TIL111-M

TIL117-M

MOC8100-M

Fig. 19 Dark Current vs. Ambient Temperature





Figure 20. Switching Time Test Circuit and Waveforms



**TIL111**


**TIL111-M**

**TIL117-M**


**MOC8100-M**

**White Package (-M Suffix)**


**Package Dimensions (Through Hole)**




**Package Dimensions (Surface Mount)**



**Package Dimensions (0.4" Lead Spacing)**



**Recommended Pad Layout for  
Surface Mount Leadform**



**NOTE**

All dimensions are in inches (millimeters)





**TIL111**

**TIL111-M**

**TIL117-M**

**MOC8100-M**

**Black Package (No -M Suffix)**



**NOTE**  
All dimensions are in inches (millimeters)

**TIL111**

**TIL111-M**


**TIL117-M**

**MOC8100-M**


**ORDERING INFORMATION**

| Order Entry Identifier    |                           |                                      |
|---------------------------|---------------------------|--------------------------------------|
| Black Package (No Suffix) | White Package (-M Suffix) | Option                               |
| .S                        | S                         | Surface Mount Lead Bend              |
| .SD                       | SR2                       | Surface Mount; Tape and reel         |
| .W                        | T                         | 0.4" Lead Spacing                    |
| .300                      | V                         | VDE 0884                             |
| .300W                     | TV                        | VDE 0884, 0.4" Lead Spacing          |
| .3S                       | SV                        | VDE 0884, Surface Mount              |
| .3SD                      | SR2V                      | VDE 0884, Surface Mount, Tape & Reel |

**MARKING INFORMATION**



**Black Package, No Suffix**



**White Package, -M Suffix**

| Definitions |  |
|-------------|--|
| 1           | Fairchild logo   |
| 2           | Device number  |
| 3           | VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table)   |
| 4           | One or two digit year code<br>• Two digits for black package parts, e.g., '03'<br>• One digit for white package parts, e.g., '3' |
| 5           | Two digit work week ranging from '01' to '53'  |
| 6           | Assembly package code  |

\*Note – Parts built in the white package (M suffix) that do not have the 'V' option (see definition 3 above) that are marked with date code '325' or earlier are marked in the portrait format.


TIL111

TIL111-M


TIL117-M

MOC8100-M

**Carrier Tape Specifications (Black Package, No Suffix)**



**Carrier Tape Specifications (White Package, -M Suffix)**




**TIL111**

**TIL111-M**


**TIL117-M**

**MOC8100-M**

**Reflow Profile (White Package, -M Suffix)**



**Reflow Profile (Black Package, No Suffix)**



- Peak reflow temperature: 225°C (package surface temperature)
- Time of temperature higher than 183°C for 60-150 seconds
- One time soldering reflow is recommended

---

**TIL111**

**TIL111-M**

**TIL117-M**

**MOC8100-M**

---

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

