

## 74VHCT14A

### Hex Schmitt Inverter

#### General Description

The VHCT14A is an advanced high speed CMOS Hex Schmitt Inverter fabricated with silicon gate CMOS technology. The VHCT14A contains six independent inverters which are capable of transforming slowly changing input signals into sharply defined, jitter-free output signals.

Protection circuits ensure that 0V to 7V can be applied to the input pins without regard to the supply voltage and to the output pins with  $V_{CC} = 0V$ . These circuits prevent device destruction due to mismatched supply and input/output voltages. This device can be used to interface 3V to 5V systems and two supply systems such as battery backup.

#### Features


- High speed:  $t_{PD} = 5.0$  ns (typ) at  $T_A = 25^\circ C$
- High noise immunity:  $V_{IH} = 2.0V$ ,  $V_{IL} = 0.8V$
- Power down protection is provided on all inputs and outputs
- Low noise:  $V_{OLP} = 1.0V$  (max)
- Low power dissipation:  
 $I_{CC} = 2 \mu A$  (max) @  $T_A = 25^\circ C$
- Pin and function compatible with 74HCT14

#### Ordering Code:


Order Number	Package Number	Package Description
74VHCT14AM	M14A	14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-120, 0.150" Narrow
74VHCT14ASJ	M14D	14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide
74VHCT14AMTC	MTC14	14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
74VHCT14AN	N14A	14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide

Surface mount packages are also available on Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

#### Logic Symbol



#### Connection Diagram



#### Pin Descriptions

Pin Names	Description
$A_n$	Inputs
$\bar{O}_n$	Outputs

#### Truth Table

A	$\bar{O}$
L	H
H	L

<b>Absolute Maximum Ratings</b> <sup>(Note 1)</sup>							<b>Recommended Operating Conditions</b> <sup>(Note 5)</sup>	
Supply Voltage ( $V_{CC}$ )				-0.5V to +7.0V			Supply Voltage ( $V_{CC}$ )	4.5V to +5.5V
DC Input Voltage ( $V_{IN}$ )				-0.5V to +7.0V			Input Voltage ( $V_{IN}$ )	0V to +5.5V
DC Output Voltage ( $V_{OUT}$ ) (Note 2)				-0.5V to $V_{CC}$ + 0.5V			Output Voltage ( $V_{OUT}$ ) (Note 2)	0V to $V_{CC}$
(Note 3)				-0.5V to 7.0V			(Note 3)	0V to 5.5V
Input Diode Current ( $I_{IK}$ )				-20 mA			Operating Temperature ( $T_{OPR}$ )	-40°C to +85°C
Output Diode Current ( $I_{OK}$ ) (Note 4)				$\pm 20$ mA			<b>Note 1:</b> Absolute Maximum Ratings are values beyond which the device may be damaged or have its useful life impaired. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation outside databook specifications.	
DC Output Current ( $I_{OUT}$ )				$\pm 25$ mA			<b>Note 2:</b> HIGH or LOW state. $I_{OUT}$ absolute maximum rating must be observed.	
DC $V_{CC}$ /GND Current ( $I_{CC}$ )				$\pm 50$ mA			<b>Note 3:</b> $V_{CC} = 0V$ .	
Storage Temperature ( $T_{STG}$ )				-65°C to +150°C			<b>Note 4:</b> $V_{OUT} < GND$ , $V_{OUT} > V_{CC}$ (Outputs Active)	
Lead Temperature ( $T_L$ ) (Soldering, 10 seconds)				260°C			<b>Note 5:</b> Unused inputs must be held HIGH or LOW. They may not float.	
<b>DC Electrical Characteristics</b>								
Symbol	Parameter	$V_{CC}$ (V)	$T_A = 25^\circ C$			$T_A = -40^\circ C$ to $+85^\circ C$		Conditions
			Min	Typ	Max	Min	Max	
$V_P$	Positive Threshold Voltage	4.5 5.5		1.9 2.1		1.9 2.1	V	
$V_N$	Negative Threshold Voltage	4.5 5.5	0.5 0.6		0.5 0.6		V	
$V_H$	Hysteresis Voltage	4.5 5.5	0.4 0.4	1.4 1.5	0.4 0.4	1.4 1.5	V	
$V_{OH}$	HIGH Level Output Voltage	4.5	4.40 3.94	4.50		4.40 3.80	V	$V_{IN} = V_{IL}$ $I_{OH} = -50 \mu A$ $I_{OH} = -8 mA$
$V_{OL}$	LOW Level Output Voltage	4.5		0.0 0.36	0.1 0.44		V	$V_{IN} = V_{IH}$ $I_{OL} = 50 \mu A$ $I_{OL} = 8 mA$
$I_{IN}$	Input Leakage Current	0 – 5.5		$\pm 0.1$	$\pm 1.0$		$\mu A$	$V_{IN} = 5.5V$ or GND
$I_{CC}$	Quiescent Supply Current	5.5		2.0	20.0		$\mu A$	$V_{IN} = V_{CC}$ or GND
$I_{CCT}$	Maximum $I_{CC}$ /Input	5.5		1.35	1.50		$mA$	$V_{IN} = 3.4V$ Other Inputs = $V_{CC}$ or GND
$I_{OFF}$	Output Leakage Current (Power Down State)	0.0		0.5		5.0	$\mu A$	$V_{OUT} = 5.5V$
<b>Noise Characteristics</b>								
Symbol	Parameter	$V_{CC}$ (V)	$T_A = 25^\circ C$		Units	Conditions		
			Typ	Limits				
$V_{OLP}$ (Note 6)	Quiet Output Maximum Dynamic $V_{OL}$	5.0	0.8	1.0	V	$C_L = 50 pF$		
$V_{OLV}$ (Note 6)	Quiet Output Minimum Dynamic $V_{OL}$	5.0	-0.8	1.0	V	$C_L = 50 pF$		
$V_{IHD}$ (Note 6)	Minimum HIGH Level Dynamic Input Voltage	5.0		2.0	V	$C_L = 50 pF$		
$V_{ILD}$ (Note 6)	Maximum LOW Level Dynamic Input Voltage	5.0		0.8	V	$C_L = 50 pF$		
<b>Note 6:</b> Parameter guaranteed by design.								

**AC Electrical Characteristics**


Symbol	Parameter	V <sub>CC</sub> (V)	T <sub>A</sub> = 25°C			T <sub>A</sub> = -40°C to +85°C		Units	Conditions
			Min	Typ	Max	Min	Max		
t <sub>PHL</sub>	Propagation Delay	5.0 ± 0.5		5.0	7.6	1.0	9.0	ns	C <sub>L</sub> = 15 pF
t <sub>PLH</sub>				6.5	9.6	1.0	11.0	ns	C <sub>L</sub> = 50 pF
C <sub>IN</sub>	Input Capacitance			2	10		10	pF	V <sub>CC</sub> = OPEN
C <sub>PD</sub>	Power Dissipation Capacitance			11				pF	(Note 7)

**Note 7:** C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I<sub>CC</sub> (opr.) = C<sub>PD</sub> \* V<sub>CC</sub> \* f<sub>IN</sub> + I<sub>CC</sub>/6 (per gate).


EEBN 爱元件世界  
www.eebn.com.cn


### Physical Dimensions

inches (millimeters) unless otherwise noted



### Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)

N14A (REV F)

14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide  
Package Number N14A**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)