

**Models 7156, 7157**  
**1/4" Jacks W/Insulated Washer & Solder Lugs**



Model 7156 1/4" Phone Jack, Insulated Washers -Mono



Model 7157 1/4" Phone Jack, Insulated Washers-Stereo

Use to connect with standard commercial phone plugs.

**Features**

- Stereo and mono versions
- Panel mountable
- Low contact resistance

**Materials**

- Body is diecast zinc alloy with tarnish resistant nickel plating.
- Mounting bushing is nickel-plated copper alloy.
- Insulation: Rigid plastic.
- Springs: Copper alloy.
- Sleeve terminal: Copper alloy.
- Hardware includes one copper alloy nickel-plated hex nut, and one steel nickel-plated washer.

**Specifications**

Number of conductors	2 (7146), 3 (7157)
Contact resistance	$\leq 0.05 \Omega$
Dielectric strength	500 V dc
Insulation resistance	1000 M $\Omega$

**Maximum panel thickness:** .25 inch (6.35 mm) for .375 inch (9.5 mm) long bushing.

**Model 7156:** 2-Conductor (mono), .205" Faston terminals and .375" (9.5 mm) long bushing.

**Model 7157:** 3-Conductor (stereo), .375" long bushing.

**Ordering Information**

Model: 7156  
Model: 7157

**USA:** Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500

e-mail: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)

Where to Buy: [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02$ " (.51 mm), .xxx =  $\pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.