

54/74170
54LS/74LS170
 4 X 4 REGISTER FILE
 (With Open-Collector Outputs)

DESCRIPTION — The '170 contains 16 high speed, low power, transparent D-type latches arranged as four words of four bits each, to function as a 4 X 4 register file. Separate read and write inputs, both address and enable, allow simultaneous read and write operation. Open-collector outputs make it possible to connect up to 128 outputs in a wired-AND configuration to increase the word capacity up to 512 words. Any number of these devices can be operated in parallel to generate an n-bit length. The '670 provides a similar function to this device but it features 3-state outputs.

- **SIMULTANEOUS READ/WRITE OPERATION**
- **EXPANDABLE TO 512 WORDS OF n-BITS**
- **TYPICAL ACCESS TIME OF 20 ns**
- **LOW LEAKAGE OPEN-COLLECTOR OUTPUTS FOR EXPANSION**

ORDERING CODE: See Section 9


PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 \text{ V} \pm 5\%$, $T_A = 0^\circ \text{C to } +70^\circ \text{C}$	$V_{CC} = +5.0 \text{ V} \pm 10\%$, $T_A = -55^\circ \text{C to } +125^\circ \text{C}$	
Plastic DIP (P)	A	74170PC, 74LS170PC		9B
Ceramic DIP (D)	A	74170DC, 74LS170DC	54170DM, 54LS170DM	7B
Flatpak (F)	A	74170FC, 74LS170FC	54170FM, 54LS170DM	4L

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions


PIN NAMES	DESCRIPTION	54/74 (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
D ₁ — D ₄	Data Inputs	1.0/1.0	0.5/0.25
WA ₀ , WA ₁	Write Address Inputs	1.0/1.0	0.5/0.25
WE	Write Enable Input (Active LOW)	1.0/1.0	1.0/0.5
RA ₀ , RA ₁	Read Address Inputs	1.0/1.0	0.5/0.25
RE	Read Enable Input (Active LOW)	1.0/1.0	1.0/0.5
O ₁ — O ₄	Data Outputs	OC*/10	OC*/5.0 (2.5)

*OC — Open Collector


CONNECTION DIAGRAM
PINOUT A



LOGIC SYMBOL



LOGIC DIAGRAM



WRITE FUNCTION TABLE

WRITE INPUTS			D INPUTS TO
WE	WA1	WA0	
L	L	L	Word 0
L	L	H	Word 1
L	H	L	Word 2
L	H	H	Word 3
H	X	X	None (hold)

READ FUNCTION TABLE

READ INPUTS			OUTPUTS FROM
RE	RA1	RA0	
L	L	L	Word 0
L	L	H	Word 1
L	H	L	Word 2
L	H	H	Word 3
H	X	X	None (HIGH Z)

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

SYMBOL	PARAMETER		54/74		54/74LS		UNITS	CONDITIONS
			Min	Max	Min	Max		
I _{OH}	Output HIGH Current		30		20		μA	V _{CC} = Min, V _{OH} = 5.5 V
I _{CC}	Power Supply Current	X _C	150		40		mA	V _{CC} = Max; D _n , $\overline{WE}$, $\overline{RE}$ = 4.5 V; W _{A_n} , R _{A_n} = Gnd
		X _M	140		40			

AC CHARACTERISTICS: V_{CC} = +5.0 V, T_A = +25°C (See Section 3 for waveforms and load configurations)

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		C _L = 15 pF R _L = 400 Ω		C _L = 15 pF			
		Min	Max	Min	Max		
t _{PLH} t _{PHL}	Propagation Delay* RA ₀ or RA ₁ to O _n	35	40	35	35	ns	Figs. 3-1, 3-20
t _{PLH} t _{PHL}	Propagation Delay RE to O _n	15	30	30	30	ns	Figs. 3-1, 3-5
t _{PLH} t _{PHL}	Propagation Delay WE to O _n	40	45	35	35	ns	Figs. 3-1, 3-9
t _{PLH} t _{PHL}	Propagation Delay D _n to O _n	30	45	35	35	ns	Figs. 3-1, 3-5

*Measured at least 25 ns after entry of new data at selected location.

AC OPERATING REQUIREMENTS: V_{CC} = +5.0 V, T_A = +25°C

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max		
t _s	Setup Time HIGH or LOW D _n to rising $\overline{WE}$	10		10		ns	Fig. a
t _h	Hold Time HIGH or LOW D _n to rising $\overline{WE}$	15		5.0		ns	
t _s	Setup Time HIGH or LOW W _{A_n} to falling $\overline{WE}$	15		10		ns	
t _h	Hold Time HIGH or LOW W _{A_n} to rising $\overline{WE}$	5.0		5.0		ns	
t _w (L)	$\overline{WE}$ or $\overline{RE}$ Pulse Width LOW	25		25		ns	




Fig. a