



DB LECTRO[®]
COMPOSANTS ÉLECTRONIQUES
ELECTRONIC COMPONENTS

8022-1363-AU 808nm 200mW IR Laser Diodes AUTO PACKAGE

Specifications

Device Laser Diode
Package Type TO-5(9.0mm)



Absolute Maximum Ratings($T_c=25^\circ C$)

Characteristics	Symbols	Ratings	Units
Optical Output	Po	200	mW
Reverse Voltage	Laser	2	V
	PIN PD	10	V
Operating Temperature	Top	-10 +50	
Storage Temperature	Tstg	-40 +85	

Electrical and optical Characteristics($T_c=25^\circ C$)

Characteristics	Symbols	Conditions	Min.	Typ.	Max.	Units
Threshold Current	I _{th}	-	-	150	200	mA
Operating Current	I _{op}	Po=200mW	-	350	500	mA
Operating Voltage	V _{op}	Po=200mW	-	1.9	3	Volts
Slope Efficiency		100mW I(200mW)-I(100mW)	0.65	0.9	1.0	mW/mA
Monitor Current	I _m	Po=200mW	-	0.3	6.0	mA
Beam Divergence (FWHM)	Parallel	//	Po=200mW	12	17	deg.
	Perpendicular		Po=200mW	28	40	deg.
Parallel Deviation Angle		//	Po=200mW	-3	-	deg.
Perpendicular Deviation Angle			Po=200mW	-3	-	deg.
Emission Point Accuracy	X	Po=200mW	-50	-	50	μ m
	Y	Po=200mW	-50	-	50	μ m
	Z	Po=200mW	-50	-	50	μ m
Lasing Wavelength		Po=200mW	804	807	810	nm

I_m is sorting by custom's need

// and are defined as the angle within which the intensity is 50% of the peak value.