

$I_{F(AV)} = 8 \text{ Amp}$   
 $V_R = 80 - 100V$

**Major Ratings and Characteristics**

| Characteristics                         | Value      | Units            |
|---|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform        | 8          | A                |
| $V_{RRM}$ range                         | 80 - 100   | V                |
| $I_{FSM}$ @tp = 5 $\mu$ s sine          | 850        | A                |
| $V_F$ @8 Apk, $T_J = 125^\circ\text{C}$ | 0.58       | V                |
| $T_J$ range                             | -55 to 175 | $^\circ\text{C}$ |

**Description/ Features**

The 8TQ...G Schottky rectifier series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175 $^\circ\text{C}$  junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.


- 175 $^\circ\text{C}$   $T_J$  operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

**Case Styles**

8TQ...G



TO-220AC



## Voltage Ratings

| Part number                                     | 8TQ080G | 8TQ100G |
|---|---------|---------|
| $V_R$ Max. DC Reverse Voltage (V)               | 80      | 100     |
| $V_{RWM}$ Max. Working Peak Reverse Voltage (V) |         |         |

## Absolute Maximum Ratings

| Parameters  | 8TQ  | Units | Conditions   |
|---|------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current<br>* See Fig. 5                | 8    | A     | 50% duty cycle @ $T_C = 157^\circ\text{C}$ , rectangular wave form   |
| $I_{FSM}$ Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7 | 850  | A     | 5 $\mu\text{s}$ Sine or 3 $\mu\text{s}$ Rect. pulse  |
|   | 230  |       | 10ms Sine or 6ms Rect. pulse   |
| $E_{AS}$ Non-Repetitive Avalanche Energy                                | 7.50 | mJ    | $T_J = 25^\circ\text{C}$ , $I_{AS} = 0.50\text{Amps}$ , $L = 60\text{mH}$  |
| $I_{AR}$ Repetitive Avalanche Current                                   | 0.50 | A     | Current decaying linearly to zero in 1 $\mu\text{sec}$<br>Frequency limited by $T_J$ max. $V_A = 1.5 \times V_R$ typical |

## Electrical Specifications

| Parameters  | 8TQ   | Units            | Conditions  |
|---|-------|------------------|---|
| $V_{FM}$ Max. Forward Voltage Drop (1)<br>* See Fig. 1    | 0.72  | V                | @ 8A  |
|   | 0.88  | V                | @ 16A   |
|   | 0.58  | V                | @ 8A  |
|   | 0.69  | V                | @ 16A   |
| $I_{RM}$ Max. Reverse Leakage Current (1)<br>* See Fig. 2 | 0.28  | mA               | $T_J = 25^\circ\text{C}$  |
|   | 7     | mA               | $T_J = 125^\circ\text{C}$   |
| $C_T$ Max. Junction Capacitance                           | 500   | pF               | $V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) $25^\circ\text{C}$ |
| $L_S$ Typical Series Inductance                           | 8     | nH               | Measured lead to lead 5mm from package body                           |
| $dv/dt$ Max. Voltage Rate of Change (Rated $V_R$ )        | 10000 | V/ $\mu\text{s}$ |   |

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2%

## Thermal-Mechanical Specifications

| Parameters  | 8TQ        | Units              | Conditions                           |
|---|------------|--------------------|--------------------------------------|
| $T_J$ Max. Junction Temperature Range                   | -55 to 175 | $^\circ\text{C}$   |                                      |
| $T_{stg}$ Max. Storage Temperature Range                | -55 to 175 | $^\circ\text{C}$   |                                      |
| $R_{thJC}$ Max. Thermal Resistance Junction to Case     | 2.0        | $^\circ\text{C/W}$ | DC operation * See Fig. 4            |
| $R_{thCS}$ Typical Thermal Resistance, Case to Heatsink | 0.50       | $^\circ\text{C/W}$ | Mounting surface, smooth and greased |
| wt Approximate Weight                                   | 2 (0.07)   | g (oz.)            |                                      |
| T Mounting Torque                                       | Min.       | 6 (5)              | Kg-cm (lbf-in)                       |
|   | Max.       | 12 (10)            |                                      |
| Device Marking  | 8TQ...G    |                    |                                      |




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current





Fig. 8 - Unclamped Inductive Test Circuit

(2) Formula used:  $T_c = T_j - (Pd + Pd_{REV}) \times R_{thJC}$ ;


$Pd$  = Forward Power Loss =  $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);

$Pd_{REV}$  = Inverse Power Loss =  $V_{R1} \times I_{R1} (1 - D)$ ;  $I_{R1} @ V_{R1} = 80\%$  rated  $V_R$

Outline Table



Part Marking Information



Ordering Information Table

| Device Code |   |   |     |   |   |
|-------------|---|---|-----|---|---|
| 8           | T | Q | 100 | G | - |
| ①           | ② | ③ | ④   | ⑤ | ⑥ |

|  |   |
|--|---|
| <p><b>1</b> - Current Rating (8 = 8A)</p> <p><b>2</b> - T = TO-220</p> <p><b>3</b> - Q = Schottky Q Series</p> <p><b>4</b> - Voltage Ratings</p> <p><b>5</b> - G = Schottky Generation</p> <p><b>6</b> -</p> <ul style="list-style-type: none"> <li>• none = Standard Production</li> <li>• PbF = Lead-Free</li> </ul> | <div style="border: 1px solid black; padding: 5px; display: inline-block;">                 080 = 80V<br/>100 = 100V             </div> |
|--|---|

Tube Standard Pack Quantity : 50 pieces

```

8TQ100
*****
* This model has been developed by *
* Wizard SPICE MODEL GENERATOR (1999) *
* (International Rectifier Corporation) *
* Contain Proprietary Information *
*****
* SPICE Model Diode is composed by a *
* simple diode plus paralled VCG2T *
*****
.SUBCKT 8TQ100 ANO CAT
D1 ANO 1 DMOD (0.07089)
*Define diode model
.MODEL DMOD D(IS=1.15938021883115E-03A,N=1.95244918720315,BV=120V,
+ IBV=5.37891460505463A,RS= 0.00127602,CJO=9.9895753025115E-09,
+ VJ=2.30070034831946,XTI=2, EG=0.758916909331649)
*****
*Implementation of VCG2T
VX 1 2 DC 0V
R1 2 CAT TRES 1E-6
.MODEL TRES RES(R=1,TC1=-90.2420977904848)
GP1 ANO CAT VALUE={-ABS(I(VX))*(EXP(((1.635248E-02/-90.2421)*(V(2,CAT)*1E6)/(I(VX)+1E-6)-1))+1)*4.011038E-03*ABS(V(ANO,CAT))-1}}
*****
.ENDS 8TQ100

Thermal Model Subcircuit
.SUBCKT 8TQ100 5 1

CTHERM1 5 4 1.45E+00
CTHERM2 4 3 4.54E+00
CTHERM3 3 2 1.09E+01
CTHERM4 2 1 1.01E+02

RTHERM1 5 4 2.49E+00
RTHERM2 4 3 5.20E-04
RTHERM1 3 2 5.43E-01
RTHERM1 2 1 3.05E-02

.ENDS 8TQ100
    
```

EEPW 电子产品世界  
.com.cn

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 01/06