

# FDS8884

## N-Channel PowerTrench® MOSFET

30V, 8.5A, 23mΩ



### General Descriptions

This N-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low  $r_{DS(on)}$  and fast switching speed.



### Features

- Max  $r_{DS(on)}$  = 23mΩ at  $V_{GS} = 10V$ ,  $I_D = 8.5A$
- Max  $r_{DS(on)}$  = 30mΩ at  $V_{GS} = 4.5V$ ,  $I_D = 7.5A$
- Low gate charge
- 100%  $R_G$  Tested
- RoHS Compliant



### MOSFET Maximum Ratings $T_A = 25^\circ C$ unless otherwise noted

| Symbol         | Parameter                              | Rated      | Units          |
|----------------|--|------------|----------------|
| $V_{DS}$       | Drain to Source Voltage                | 30         | V              |
| $V_{GS}$       | Gate to Source Voltage                 | $\pm 20$   | V              |
| $I_D$          | Drain Current Continuous (Note 1a)     | 8.5        | A              |
|                | Pulsed                                 | 40         | A              |
| $E_{AS}$       | Single Pulse Avalanche Energy (Note 2) | 32         | mJ             |
| $P_D$          | Power dissipation                      | 2.5        | W              |
|                | Derate above $25^\circ C$              | 20         | mW/ $^\circ C$ |
| $T_J, T_{STG}$ | Operating and Storage Temperature      | -55 to 150 | $^\circ C$     |

### Thermal Characteristics

|                 |   |    |              |
|-----------------|---|----|--------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient (Note 1a) | 50 | $^\circ C/W$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Case (Note 1)     | 25 | $^\circ C/W$ |

### Package Marking and Ordering Information

| Device Marking | Device  | Package | Reel Size | Tape Width | Quantity   |
|----------------|---------|---------|-----------|------------|------------|
| FDS8884        | FDS8884 | SO-8    | 330mm     | 12mm       | 2500 units |

**Electrical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

**Off Characteristics**

|                                      |   |  |    |    |           |                      |
|--------------------------------------|---|--|----|----|-----------|----------------------|
| $BV_{DSS}$                           | Drain to Source Breakdown Voltage         | $I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$                                 | 30 |    |           | V                    |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$ , referenced to $25^\circ\text{C}$                  |    | 23 |           | mV/ $^\circ\text{C}$ |
| $I_{DSS}$                            | Zero Gate Voltage Drain Current           | $V_{DS} = 24\text{V}$<br>$V_{GS} = 0\text{V}$<br>$T_J = 125^\circ\text{C}$ |    |    | 1<br>250  | $\mu\text{A}$        |
| $I_{GSS}$                            | Gate to Source Leakage Current            | $V_{GS} = \pm 20\text{V}$  |    |    | $\pm 100$ | nA                   |

**On Characteristics (Note 3)**

|  |  |  |     |                |                |                      |
|--|--|--|-----|----------------|----------------|----------------------|
| $V_{GS(th)}$                           | Gate to Source Threshold Voltage                         | $V_{GS} = V_{DS}, I_D = 250\mu\text{A}$  | 1.2 | 1.7            | 2.5            | V                    |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate to Source Threshold Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$ , referenced to $25^\circ\text{C}$  |     | -4.9           |                | mV/ $^\circ\text{C}$ |
| $r_{DS(on)}$                           | Drain to Source On Resistance                            | $V_{GS} = 10\text{V}, I_D = 8.5\text{A}$ ,<br>$V_{GS} = 4.5\text{V}, I_D = 7.5\text{A}$ ,<br>$V_{GS} = 10\text{V}, I_D = 8.5\text{A}$ ,<br>$T_J = 125^\circ\text{C}$ |     | 19<br>23<br>26 | 23<br>30<br>32 | m $\Omega$           |

**Dynamic Characteristics**

|           |                              |  |  |     |     |          |
|-----------|------------------------------|--|--|-----|-----|----------|
| $C_{iss}$ | Input Capacitance            | $V_{DS} = 15\text{V}, V_{GS} = 0\text{V}$ ,<br>$f = 1\text{MHz}$ |  | 475 | 635 | pF       |
| $C_{oss}$ | Output Capacitance           |  |  | 100 | 135 | pF       |
| $C_{rss}$ | Reverse Transfer Capacitance |  |  | 65  | 100 | pF       |
| $R_G$     | Gate Resistance              |  |  | 0.9 | 1.6 | $\Omega$ |

**Switching Characteristics (Note 3)**


|              |                            |  |   |     |     |    |
|--------------|----------------------------|--|---|-----|-----|----|
| $t_{d(on)}$  | Turn-On Delay Time         | $V_{DD} = 15\text{V}, I_D = 8.5\text{A}$<br>$V_{GS} = 10\text{V}, R_{GS} = 33\Omega$ |   | 5   | 10  | ns |
| $t_r$        | Rise Time                  |  |   | 9   | 18  | ns |
| $t_{d(off)}$ | Turn-Off Delay Time        |  |   | 42  | 68  | ns |
| $t_f$        | Fall Time                  |  |   | 21  | 34  | ns |
| $Q_g$        | Total Gate Charge          |  | $V_{DS} = 15\text{V}, V_{GS} = 10\text{V}$<br>$I_D = 8.5\text{A}$ |     | 9.2 | 13 |
| $Q_g$        | Total Gate Charge          | $V_{DS} = 15\text{V}, V_{GS} = 5\text{V}$<br>$I_D = 8.5\text{A}$                     |   | 5.0 | 7   | nC |
| $Q_{gs}$     | Gate to Source Gate Charge |  |   | 1.5 |     | nC |
| $Q_{gd}$     | Gate to Drain Charge       |  |   | 2.0 |     | nC |

**Drain-Source Diode Characteristics**


|          |                               |  |  |     |      |    |
|----------|-------------------------------|--|--|-----|------|----|
| $V_{SD}$ | Source to Drain Diode Voltage | $I_{SD} = 8.5\text{A}$                               |  | 0.9 | 1.25 | V  |
|          |                               | $I_{SD} = 2.1\text{A}$                               |  | 0.8 | 1.0  | V  |
| $t_{rr}$ | Reverse Recovery Time         | $I_F = 8.5\text{A}, di/dt = 100\text{A}/\mu\text{s}$ |  |     | 33   | ns |
| $Q_{rr}$ | Reverse Recovery Charge       |  |  |     | 20   | nC |

**Notes:**


1:  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $50^\circ\text{C}/\text{W}$  when mounted on a 1 in<sup>2</sup> pad of 2 oz copper



b)  $105^\circ\text{C}/\text{W}$  when mounted on a .04 in<sup>2</sup> pad of 2 oz copper



c)  $125^\circ\text{C}/\text{W}$  when mounted on a minimum pad

Scale 1 : 1 on letter size paper

2: Starting  $T_J = 25^\circ\text{C}$ ,  $L = 1\text{mH}$ ,  $I_{AS} = 8\text{A}$ ,  $V_{DD} = 27\text{V}$ ,  $V_{GS} = 10\text{V}$ .  
3: Pulse Test: Pulse Width <math><300\mu\text{s}</math>, Duty Cycle <math><2\%</math>.

**Typical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted




Figure 1. On Region Characteristics




Figure 2. Normalized On-Resistance vs Drain current and Gate Voltage




Figure 3. Normalized On Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

**Typical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs Ambient Temperature




Figure 11. Forward Bias Safe Operating Area





Figure 12. Single Pulse Maximum Power Dissipation

**Typical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted



EEPW 电子产品世界 .com.cn

**TRADEMARKS**

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|  |                                 |                           |                                 |                             |
|--|---------------------------------|---------------------------|---------------------------------|-----------------------------|
| ACE <sup>x</sup> <sup>™</sup>                    | FAST <sup>®</sup>               | ISOPLANAR <sup>™</sup>    | PowerSaver <sup>™</sup>         | SuperSOT <sup>™</sup> -6    |
| ActiveArray <sup>™</sup>                         | FAST <sup>r</sup> <sup>™</sup>  | LittleFET <sup>™</sup>    | PowerTrench <sup>®</sup>        | SuperSOT <sup>™</sup> -8    |
| Bottomless <sup>™</sup>                          | FPST <sup>™</sup>               | MICROCOUPLER <sup>™</sup> | QFET <sup>®</sup>               | SyncFET <sup>™</sup>        |
| Build it Now <sup>™</sup>                        | FRFET <sup>™</sup>              | MicroFET <sup>™</sup>     | QS <sup>™</sup>                 | TCM <sup>™</sup>            |
| CoolFET <sup>™</sup>                             | GlobalOptoisolator <sup>™</sup> | MicroPak <sup>™</sup>     | QT Optoelectronics <sup>™</sup> | TinyLogic <sup>®</sup>      |
| CROSSVOLT <sup>™</sup>                           | GTO <sup>™</sup>                | MICROWIRE <sup>™</sup>    | Quiet Series <sup>™</sup>       | TINYOPTO <sup>™</sup>       |
| DOME <sup>™</sup>                                | HiSeC <sup>™</sup>              | MSX <sup>™</sup>          | RapidConfigure <sup>™</sup>     | TruTranslation <sup>™</sup> |
| EcoSPARK <sup>™</sup>                            | I <sup>2</sup> C <sup>™</sup>   | MSXPro <sup>™</sup>       | RapidConnect <sup>™</sup>       | UHC <sup>™</sup>            |
| E <sup>2</sup> CMOS <sup>™</sup>                 | i-Lo <sup>™</sup>               | OCX <sup>™</sup>          | μSerDes <sup>™</sup>            | UltraFET <sup>®</sup>       |
| EnSigna <sup>™</sup>                             | ImpliedDisconnect <sup>™</sup>  | OCXPro <sup>™</sup>       | ScalarPump <sup>™</sup>         | UniFET <sup>™</sup>         |
| FACT <sup>™</sup>                                | IntelliMAX <sup>™</sup>         | OPTOLOGIC <sup>®</sup>    | SILENT SWITCHER <sup>®</sup>    | VCX <sup>™</sup>            |
| FACT Quiet Series <sup>™</sup>                   |                                 | OPTOPLANAR <sup>™</sup>   | SMART START <sup>™</sup>        | Wire <sup>™</sup>           |
|  |                                 | PACMAN <sup>™</sup>       | SPM <sup>™</sup>                |                             |
| Across the board. Around the world. <sup>™</sup> |                                 | POP <sup>™</sup>          | Stealth <sup>™</sup>            |                             |
| The Power Franchise <sup>®</sup>                 |                                 | Power247 <sup>™</sup>     | SuperFET <sup>™</sup>           |                             |
| Programmable Active Droop <sup>™</sup>           |                                 | PowerEdge <sup>™</sup>    | SuperSOT <sup>™</sup> -3        |                             |

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

| Datasheet Identification | Product Status         | Definition  |
|--------------------------|------------------------|---|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.  |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.   |

Rev. 118