


BZX2.5C

SILICON PLANAR POWER ZENER DIODES

for use in stabilizing and clipping circuits with high power rating. The Zener voltages are graded according to the international E 24 standard. Other tolerances and higher Zener voltage upon request.



Glass Case DO-41
Dimensions in mm

Absolute Maximum Ratings ($T_a = 25\text{ }^{\circ}\text{C}$)


Parameter	Symbol	Value	Unit
Power Dissipation	P_{tot}	2.5 ¹⁾	W
Junction Temperature	T_j	200	$^{\circ}\text{C}$
Storage Temperature Range	T_s	- 55 to + 200	$^{\circ}\text{C}$

¹⁾ Valid provided that leads at a distance of 8 mm from case are kept at ambient temperature.

Characteristics at $T_a = 25\text{ }^{\circ}\text{C}$

Parameter	Symbol	Max.	Unit
Thermal Resistance Junction to Ambient Air	R_{thA}	130 ¹⁾	K/W

¹⁾ Valid provided that leads at a distance of 8 mm from case are kept at ambient temperature.



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 12/06/2007


BZX2.5C

Characteristics at $T_j = 25\text{ }^{\circ}\text{C}$

Type	Zener Voltage Range ¹⁾			Maximum Dynamic Resistance			Maximum Reverse Leakage Current	
	V_{Znom} V	I_{ZT} mA	for V_{ZT} V	r_{ZJT} Ω	r_{ZJK} Ω	at I_{ZK} mA	I_R ²⁾ μA	at V_R V
BZX2.5C5V1	5.1	45	4.8...5.4	10	500	1	1	1.5
BZX2.5C5V6	5.6	45	5.2...6	7	400	1	1	2
BZX2.5C6V2	6.2	35	5.8...6.6	4	300	1	1	3
BZX2.5C6V8	6.8	35	6.4...7.2	3.5	300	1	1	4
BZX2.5C7V5	7.5	35	7...7.9	3	200	0.5	1	4.5
BZX2.5C8V2	8.2	25	7.7...8.7	5	200	0.5	1	6.2
BZX2.5C9V1	9.1	25	8.5...9.6	5	200	0.5	1	6.8
BZX2.5C10	10	25	9.4...10.6	7	200	0.5	0.5	7
BZX2.5C11	11	20	10.4...11.6	8	300	0.5	0.5	8.2
BZX2.5C12	12	20	11.4...12.7	9	350	0.5	0.5	9.1
BZX2.5C13	13	20	12.4...14.1	10	400	0.5	0.5	10
BZX2.5C15	15	15	13.8...15.6	15	500	0.5	0.5	11
BZX2.5C16	16	15	15.3...17.1	15	500	0.5	0.5	12
BZX2.5C18	18	15	16.8...19.1	20	500	0.5	0.5	13
BZX2.5C20	20	10	18.8...21.2	24	600	0.5	0.5	15
BZX2.5C22	22	10	20.8...23.3	25	600	0.5	0.5	16
BZX2.5C24	24	10	22.8...25.6	25	600	0.5	0.5	18
BZX2.5C27	27	8	25.1...28.9	30	750	0.25	0.5	20
BZX2.5C30	30	8	28...32	30	1000	0.25	0.5	22
BZX2.5C33	33	8	31...35	35	1000	0.25	0.5	24
BZX2.5C36	36	8	34...38	40	1000	0.25	0.5	27
BZX2.5C39	39	6	37...41	50	1000	0.25	0.5	30
BZX2.5C43	43	6	40...46	50	1000	0.25	0.5	33
BZX2.5C47	47	4	44...50	90	1500	0.25	0.5	36

¹⁾ Tested with pulses $t_p = 20\text{ ms}$.

²⁾ Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case.



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949:2002
Certificate No. 05103






ISO 14001:2004
Certificate No. 7116




ISO 9001:2000
Certificate No. 0506098

Dated : 12/06/2007



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company
 listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 12/06/2007