

C-13/15-FXXM-PX-XXXX/XXX-XX



## Features

- Single fiber bi-directional operation
- Laser diode with multi-quantum- well structure
- Low threshold current
- InGaAs/InP PIN Photodiode with trans-impedance amplifier
- High sensitivity with AGC\*
- Differential ended output
- Single +3.3V Power Supply
- Integrated WDM coupler
- Un-cooled operation from -40°C to +85°C
- Hermetically sealed active component
- SM/MM fiber pigtailed packaging with optional FC/ST/SC/MU/LC/- connector
- Design for fiber optic networks application
- RoHS Compliant available

## Absolute Maximum Rating (Tc=25°C)

| Parameter                | Symbol    | Value              | Unit |
|--------------------------|-----------|--------------------|------|
| Fiber Output Power L/M/H | $P_f$     | 1(L)/1.5(M)/2.5(H) | mW   |
| LD Reverse Voltage       | $V_{RLD}$ | 2                  | V    |
| PIN-TIA Voltage          | $V_{CC}$  | 4.5                | V    |
| Operating Temperature    | $T_{opr}$ | -40 to +85         | °C   |
| Storage Temperature      | $T_{stg}$ | -40 to +85         | °C   |

(All optical data refer to a coupled 9/125μm SM fiber & 50/125μm MM fiber)

## Optical and Electrical Characteristics( Tc=25°C)

| Parameter            | Symbol             | Min             | Typical             | Max           | Unit | Test Condition                               |
|----------------------|--------------------|-----------------|---------------------|---------------|------|----------------------------------------------|
| <b>Laser Diode</b>   |                    |                 |                     |               |      |                                              |
| Optical Output Power | L<br>M<br>H        | 0.2<br>0.5<br>1 | 0.35<br>0.75<br>1.6 | 0.5<br>1<br>- | mW   | CW, $I_{th} + 20mA$ , kink free              |
| Peak Wavelength      | $\lambda$          | 1290            | 1310                | 1330          | nm   | CW, $P_f = P_f(\text{Min})$                  |
| Spectrum Width (RMS) | $\Delta\lambda$    | -               | -                   | 5             | nm   | CW, $P_f = P_f(\text{Min})$                  |
| Threshold Current    | $I_{th}$           | -               | 10                  | 15            | mA   | CW                                           |
| Forward Voltage      | $V_f$              | -               | 1.2                 | 1.5           | V    | CW, $P_f = P_f(\text{Min})$                  |
| Rise/Fall Time       | $t_r / t_f$        | -               | -                   | 0.5           | ns   | $I_{bias} = I_{th}$ , 10% to 90%             |
| <b>Monitor Diode</b> |                    |                 |                     |               |      |                                              |
| Monitor Current      | $I_m$              | 100             | -                   | -             | μA   | CW, $P_f = P_f(\text{Min})$ , $V_{RPD} = 2V$ |
| Dark Current         | $I_{DARK}$         | -               | -                   | 0.1           | μA   | $V_{RPD} = 5V$                               |
| Capacitance          | $C_t$              | -               | 6                   | 15            | pF   | $V_{RPD} = 5V$ , $f = 1MHz$                  |
| <b>Module</b>        |                    |                 |                     |               |      |                                              |
| Tracking Error       | $\Delta P_f / P_f$ | -1.5            | -                   | 1.5           | dB   | APC, -40 to +85°C                            |
| Optical Crosstalk    | CRT                | < -40           |                     |               | dB   |                                              |

## Note:

1.Pin assignment can be customized.

2.Specifications subject to change without notice.

**Detector  $\lambda=1480-1600\text{nm}$** **DC Electrical Characteristics(  $T_c=25^\circ\text{C}$  )**

| Parameter                   | Symbol   |     | Min | Typical | Max  | Unit | Test Condition |
|-----------------------------|----------|-----|-----|---------|------|------|----------------|
| Power Supply                | $V_{CC}$ |     | 3.0 | 3.3     | 3.6  | V    |                |
| Differential Output Voltage | $V_d$    | F02 | -   | -       | 1000 | mV   |                |
|                             |          | F04 | -   | 260     | 450  |      |                |
|                             |          | F06 | 185 | 250     | 415  |      |                |
| Supply Current (no load)    | $I_{CC}$ | F02 | -   | -       | 35   | mA   |                |
|                             |          | F04 | -   | 21      | 30   |      |                |
|                             |          | F06 | -   | 26      | 50   |      |                |

**AC/Optical and Electrical Characteristics(  $T_c=25^\circ\text{C}$  )**


| Parameter                   | Symbol |     | Min  | Typical | Max  | Unit | Test Condition                                                  |
|-----------------------------|--------|-----|------|---------|------|------|-----------------------------------------------------------------|
| Detection Range             |        |     | 1480 | 1550    | 1600 | nm   | -                                                               |
| Gain @ 10 Mbps Differential | G      | F02 | 52   | -       | 70   | V/mW | Measure differentially, AC coupled, $R_L=50\Omega$              |
|                             |        | F04 | 6    | 7       | -    |      | Measure differentially, AC coupled, $R_L=50\Omega$              |
|                             |        | F06 | 1.92 | 2.5     | 3.4  |      | Measure differentially with 30uAp-p signal                      |
| Bandwidth                   | BW     | F02 | 120  | 140     | -    | MHz  |                                                                 |
|                             |        | F04 | 404  | 470     | -    |      |                                                                 |
|                             |        | F06 | 700  | 920     | 1100 |      |                                                                 |
| Saturation Power            | Psat   | F02 | -3   | 0       | -    | dBm  | BER<10 <sup>-10</sup> @155Mbps PRBS 2 <sup>23</sup> -1, Er=10dB |
|                             |        | F04 | -7   | -6      | -    |      | BER<10 <sup>-10</sup> @622Mbps PRBS 2 <sup>23</sup> -1, Er=10dB |
|                             |        | F06 | -3   | -       | -    |      | BER<10 <sup>-12</sup> @1.25Gbps PRBS 2 <sup>7</sup> -1, Er=10dB |
| Sensitivity                 | Sens.  | F02 | -    | -38     | -35  | dBm  | BER<10 <sup>-10</sup> @155Mbps PRBS 2 <sup>23</sup> -1, Er=10dB |
|                             |        | F04 | -    | -33     | -30  |      | BER<10 <sup>-10</sup> @622Mbps PRBS 2 <sup>23</sup> -1, Er=10dB |
|                             |        | F06 | -    | -26     | -23  |      | BER<10 <sup>-12</sup> @1.25Gbps PRBS 2 <sup>7</sup> -1, Er=10dB |
| Output Resistance           | Rout   | F02 | -    | 50      | -    | ohm  |                                                                 |
|                             |        | F04 | 48   | 50      | 52   |      |                                                                 |
|                             |        | F06 | 48   | 50      | 62   |      |                                                                 |

## Pin Assignment

### LD Pin Assignment


#### A Type

Pin 1 : Laser Cathode  
Pin 2 : Laser Anode and Case Gnd  
Pin 3 : Monitor Diode Anode  
Pin 4 : Monitor Diode Cathode




#### D Type

Pin 1 : Laser Anode and Monitor Diode Cathode  
Pin 2 : Case Gnd  
Pin 3 : Laser Cathode  
Pin 4 : Monitor Diode Anode




### PIN-TIA Pin Assignment



F02

#### Pin Assignment


1~Dout  
2~Vcc  
3~GND(CASE)  
4~Imon  
5~Dout



F04

#### Pin Assignment

1~Dout  
2~Vcc  
3~GND(CASE)  
4~Imon  
5~Dout



F06


#### Pin Assignment

1~Dout  
2~Vcc  
3~GND(CASE)  
4~Imon  
5~Dout

Outline Dimensions


Units in mm.

C-13/15-FXXM-PX-SXXX/XXX-XX




DIMENSION: A:7.0~7.6 mm (Low & Middle power)  
A:9.3~9.9 mm (High power)


SC:SC/PC




ST:ST/PC



MU:MU/PC



C-13/15-FXXM-PX-MXXX/XXX-XX



DIMENSION: A:7.2~9.2 mm

C-13/15-FXXM-PX-XXXX/XXX-XX

## Ordering Information

## C-13/15-FXXM-PX-XXXX/XXX-XX

1310nm Transmitter  
1550nm Receiver

M = with 5 pinout

Pin Assignment  
"-" = A Type  
D = D Type

Connector  
FC/ST/SC/MU/LC/-

Fiber Output Power  
L/M/H

" - " = PC Fiber  
APC = APC Fiber  
(for single mode)

02: 155 Mb/s PIN-TIA+3.3V  
04: 622 Mb/s PIN-TIA+3.3V  
06: 1250 Mb/s PIN-TIA+3.3V

Fiber Application  
S=SM 9/125μm  
M=MM 50/125μm

RoHS Compliant  
-/G5/GR  
Blank = RoHS non-compliant product  
G5 = RoHS 5/6-compliant product (lead exemption)  
GR = Full RoHS compliant product (no exemption)

## Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

## Legal Notice

## IMPORTANT NOTICE!

All information contained in this document is subject to change without notice, at LuminentOIC's sole and absolute discretion. LuminentOIC warrants performance of its products to current specifications only in accordance with the company's standard one-year warranty; however, specifications designated as "preliminary" are given to describe components only, and LuminentOIC expressly disclaims any and all warranties for said products, including express, implied, and statutory warranties, warranties of merchantability, fitness for a particular purpose, and non-infringement of proprietary rights. Please refer to the company's Terms and Conditions of Sale for further warranty information.

LuminentOIC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents, services, or intellectual property described herein. No license, either express or implied, is granted under any patent right, copyright, or intellectual property right, and LuminentOIC makes no representations or warranties that the product(s) described herein are free from patent, copyright, or intellectual property rights. Products described in this document are NOT intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. LuminentOIC customers using or selling products for use in such applications do so at their own risk and agree to fully defend and indemnify LuminentOIC for any damages resulting from such use or sale.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. Customer agrees that LuminentOIC is not liable for any actual, consequential, exemplary, or other damages arising directly or indirectly from any use of the information contained in this document. Customer must contact LuminentOIC to obtain the latest version of this publication to verify, before placing any order, that the information contained herein is current.

© LuminentOIC, Inc. 2006  
All rights reserved