

## TECHNICAL DESCRIPTION / APPLICATION

### MULTI-MIX<sup>®</sup> FILTERS


Merrimac's FBGI Series bandpass filters combine the features of Merrimac's patented Multi-Mix<sup>®</sup> multilayer fabrication technology with the ability to operate to three times their center frequency without reentrant spurious passbands. They typically offer better overall performance than filters designed to the same specification with conventional filter fabrication techniques.



## GENERAL SPECIFICATIONS

FILTER TYPE	CENTER FREQUENCY	1 dB OPERATING BANDWIDTH (MHz MIN)	INSERTION LOSS @ CENTER FREQUENCY	REJECTION	VSWR (MAX)
BANDPASS	3100 MHz Nominal	400	2.0 dB (MAX)	40 dB MIN. @ DC-1000 MHz 65 dB MIN. @ 1000-2000 MHz 65 dB MIN @ 4500 - 5000 MHz	1.7:1 @ Fc ± 0.1 GHz
SIZE (INCHES)		WEIGHT (GRAMS/OZ.)	RF INTERFACE/ CONNECTIONS	OPERATING TEMPERATURE	
0.50 x 0.65 x 0.06		0.85 / 0.03	SMT	-55° - +85° C	

## PACKAGE OUTLINE



FBGI-3.1G

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. TOLERANCES: -3 PLACE DECIMALS; ±.005.



THE MULTI-MIX MICROTECHNOLOGY<sup>®</sup> GROUP IS ISO 9001:2000 REGISTERED



U.S. patent 6,099,677 and other patents pending.

# TYPICAL PERFORMANCE

FBGI-3.1G



THE MULTI-MIX MICROTECHNOLOGY® GROUP IS ISO 9001:2000 REGISTERED

Merrimac Industries / 41 Fairfield Place, West Caldwell, NJ 07006  
Tel: 1.888.434.MMFM / Fax: 973.882.5990 / Email: MMFM@merrimacind.com / www.Multi-Mix.com