


Application Notes:

1. Dummy receptacle stowage fitting protects the plug connector when not in use.
2. Standard materials configuration consists of aluminum alloy with cadmium olive drab finish (Symbol G-3).
3. Other types of front and rear connector accessories are available.
See our website and/or contact the factory for complete information.



**ITS 05-XX
Dummy Plug Stowage Receptacle**



TABLE I: DUMMY PLUG RECEPTACLE SHELL SIZE & DIMENSIONS

| Shell Size | ØA +0 -0.1 | K ±0.2 | M +0.2 -0 | R ±0.1 | S +0.2 | ØT +0.1 -0 |
|--------------|------------------|-----------|-----------------|-----------|-----------|------------------|
| 10 SL | 18.2 | 2.8 | 14.3 | 18.25 | 25.4 | 3.2 |
| 14 S | 24.5 | 3.3 | 14.5 | 23.00 | 30.4 | 3.2 |
| 16 S | 27.2 | 3.3 | 14.5 | 24.60 | 32.5 | 3.2 |
| 16 | 27.2 | 3.3 | 19.1 | 24.60 | 32.5 | 3.2 |
| 18 | 30.7 | 4.0 | 19.1 | 27.00 | 35.0 | 3.2 |
| 20 | 34.0 | 4.0 | 19.1 | 29.40 | 38.0 | 3.2 |
| 22 | 37.3 | 4.0 | 19.6 | 31.75 | 41.0 | 3.2 |
| 24 | 40.9 | 4.0 | 20.6 | 34.90 | 44.5 | 3.7 |
| 28 | 46.7 | 4.0 | 20.7 | 39.70 | 50.9 | 3.7 |
| 32 | 53.4 | 4.0 | 22.3 | 44.45 | 57.0 | 4.3 |
| 36 | 59.6 | 4.0 | 22.3 | 49.20 | 63.5 | 4.3 |
| 40 | 65.5 | 4.0 | 22.3 | 55.55 | 69.9 | 4.3 |

TABLE II: MODIFICATION CODES

| FINISH OPTIONS | |
|----------------|---------------------------------------|
| Sym | Description |
| F2 | Bright Nickel Plating |
| F6 | Black Electrodeposited Paint |
| F7 | Black Zn-Co Plating |
| F8 | Olive Drab Zn-Co Plating |
| G3 | Olive Drab Cadmium Plating (Standard) |

