



MASTER INSTRUMENT CORPORATION

SINGLE-PHASE BRIDGE RECTIFIER KBU6A THRU KBU6M


VOLTAGE RANGE 50 to 1000 Volts
CURRENT 6.0 Amperes

FEATURES

- l Low cost
- l This series is UL recognized under component index , file number E127707
- l High forward surge current capability
- l Ideal for printed circuit board
- l High temperature soldering guaranteed:
260°C/10 second, 0.375" (9.5mm) lead length at 5 lbs. (2.3kg) tension.

MECHANICAL DATA

- l Case: Transfer molded plastic
- l Terminal: Lead solderable per MIL-STD-202E method 208C
- l Polarity: Polarity symbols marked on case
- l Mounting: Thru hole for #6 screw, 5 in.-lbs torque max
- l Weight: 0.27 ounce, 7.59 gram



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load derate current by 20%.

| | SYMBOLS | KBU6A | KBU6B | KBU6D | KBU6G | KBU6J | KBU6K | KBU6M | UNITS |
|--|----------------------------------|-------------|-------|-------|-------|-------|-------|-------|---------------------------|
| Maximum Repetitive Peak Reverse Voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum RMS Voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | Volts |
| Maximum DC Blocking Voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum Average Forward Rectified Output Current, at | $T_C=100^\circ\text{C}$ (Note 2) | 6.0 | | | | | | | Amps |
| | $T_A=40^\circ\text{C}$ (Note 3) | 4.0 | | | | | | | |
| Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) | I_{FSM} | 250 | | | | | | | Amps |
| Rating for Fusing ($t < 8.3\text{ms}$) | I^2t | 260 | | | | | | | A^2s |
| Maximum Instantaneous Forward Voltage Drop per bridge element at 6.0A | V_F | 1.0 | | | | | | | Volts |
| Maximum DC Reverse Current at rated DC blocking voltage per element | $T_A=25^\circ\text{C}$ | 5.0 | | | | | | | μAmps |
| | $T_A=100^\circ\text{C}$ | 1.0 | | | | | | | mAmps |
| Typical Junction Capacitance (Note 1) | C_J | 200 | | | | | | | pF |
| Typical Thermal Resistance (Note 2) | $R_{\theta JC}$ | 4.7 | | | | | | | $^\circ\text{C}/\text{W}$ |
| Operating and Storage Temperature Range | T_J, T_{STG} | -55 to +150 | | | | | | | $^\circ\text{C}$ |

NOTES:

1. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts.
2. Unit mounted on 2.6"x1.4"x0.06" thick (6.3x3.5x0.15cm) Al. plate.
3. Unit mounted in free air, no heatsink, P.C.B at 0.375" (9.5mm) lead length with 0.5"x0.5" (12x12cm) copper pads



MASTER INSTRUMENT CORPORATION

SINGLE-PHASE BRIDGE RECTIFIER
KBU6A THRU KBU6M

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 6.0 Amperes

RATINGS AND CHARACTERISTIC CURVES KBU6A THRU KBU6M

FIG.1-DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER ELEMENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG.4-TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT




FIG.5-TYPICAL JUNCTION CAPACITANCE PER BRIDGE ELEMENT

