

AZ920

ULTRA-SENSITIVE SUBMINIATURE RELAY

FEATURES

- Extremely small footprint utilizing only 0.16 square inch of PCB area
- Thin vertical profile only 0.2" wide
- Slim SIP package
- 1 Form A contact with up to 5 Amp switching capability
- High sensitivity, 58 mW pickup
- Dielectric strength 2500 Vrms contact to coil
- Epoxy sealed
- UL, CUR file E43203
- TÜV file R50018790



CONTACTS

Arrangement	SPST (1 Form A) Single button contact or bifurcated
Ratings	Resistive load: Max. switched power: 150 W or 1250 VA Max. switched current: 5 A Max. switched voltage: 150* VDC or 250 VAC *Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL, CUR	5 A at 30 VDC or 250 VAC General Use, 100k cycles [1]
TÜV	5 A at 30 VDC or 250 VAC Resistive, 100k cycles [1] 3 A at 30 VDC or 250 VAC General Use, 75k cycles[2] 3 A at 30 VDC or 250 VAC Resistive, 75k cycles [2] [1] Single button contacts [2] Bifurcated contacts
Material	Silver nickel (single button or bifurcated contacts), or silver tin oxide (single button contacts), gold plating available
Resistance	< 50 milliohms initially

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 20 million operations 1 X 10 ⁵ at 5 A, 30 VDC or 250 VAC
Operate Time (typical)	6 ms at nominal coil voltage
Release Time (typical)	3 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	1000 Vrms between open contacts 2500 Vrms contact to coil
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 85°C (185°F) -40°C (-40°F) to 105°C (221°F)
Vibration	0.062" (1.5 mm) DA at 10–55 Hz
Shock	15 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	3 grams
Packing unit in pcs	100 per plastic tube / 1000 per carton box

COIL

Power At Pickup Voltage (typical)	58 mW (5-18 V coils) 88 mW (24 V coil)
Max. Continuous Dissipation	1.3 W at 20°C (68°F) ambient
Temperature Rise at nominal coil voltage	12°C (22°F) 5-18 V coils 17°C (31°F) 24 V coil
Temperature	Max. 130°C (266°F) Class B Max. 155°C (311°F) Class F

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0
Fax +49 89 800 97 200

office@ZETTLERelectronics.com
www.ZETTLERelectronics.com


AZ920

RELAY ORDERING DATA

COIL SPECIFICATIONS				
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm $\pm 10\%$	ORDER NUMBER*
5	3.5	16.5	208	AZ920-1A-5DE
6	4.2	19.9	300	AZ920-1A-6DE
9	6.3	29.8	675	AZ920-1A-9DE
12	8.4	39.8	1,200	AZ920-1A-12DE
18	12.6	59.6	2,700	AZ920-1A-18DE
24	16.8	65.0	3,200	AZ920-1A-24DE

* Substitute "-1AB" in place of "-1A" for bifurcated silver nickel contacts. Substitute "-1AH" in place of "-1A" for silver tin oxide contacts. Add suffix "A" for gold plated contacts. Add suffix "K" for .3 inch terminal spacing. Add suffix "F" for Class F insulation.

MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance: $\pm .010$ "

ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0

Fax +49 89 800 97 200

office@ZETTLERelectronics.com

www.ZETTLERelectronics.com