

# AZ723

## MINIATURE POWER RELAY

### FEATURES

- AC coils
- Dielectric strength 5000 Vrms
- Low cost
- Flux tight package
- 5 Amp switching - double pole contacts
- Isolation spacing greater than 8mm
- Molded materials: all 94V-0
- UL and Canadian file E43203



### CONTACTS

<b>Arrangement</b>	DPST (2 Form A) DPDT (2 Form C)
<b>Ratings</b>	<b>Resistive load:</b> Max. switched power: 150 W, 1250 VA Max. switched current: 5 A Max. switched voltage: 150 VDC/400 VAC  <b>Inductive load: (<math>\cos\phi = 0.4</math>)</b> Max. switched power: 90W or 500VA Max. Switched current: 5A Max. switched voltage: 125VDC or 400 VAC  <small>Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.</small>
<b>Rated Load UL, CUR</b>	5 A 250 VAC, resistive 5 A 30VDC resistive 1/3 HP 240 VAC
<b>Min. Load</b>	5 VDC, .01A
<b>Material</b>	Silver alloy
<b>Resistance</b>	30 milliohms initially (6V, 1A method)

### COIL

<b>Power At Pickup Voltage (typical)</b>	576 mW
<b>Max. Continuous Dissipation</b>	1.5 W at 20°C (68°F) ambient 1.2 W at 40°C (104°F) ambient
<b>Temperature Rise</b>	36°C (97°F) at nominal coil voltage
<b>Temperature</b>	Max. 105°C (221°F)

### NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

### GENERAL DATA

<b>Life Expectancy</b> <b>Mechanical</b> <b>Electrical</b>	Minimum operations 1 x 10 <sup>7</sup> 1 x 10 <sup>5</sup> at rated load
<b>Operate Time (typical)</b>	8 ms at nominal coil voltage
<b>Release Time (typical)</b>	5 ms at nominal coil voltage (with no coil suppression)
<b>Dielectric Strength (at sea level for 1 min.)</b>	5000 Vrms coil to contact 3000 Vrms between contact sets 1000 Vrms between open contacts
<b>Insulation Resistance</b>	1000 megohms min. at 20°C, 500 VDC 50% RH
<b>Dropout</b>	Greater than 30% of nominal coil voltage
<b>Ambient Temperature Operating Storage</b>	At nominal coil voltage -40°C (-40°F) to 70°C (158°F) -40°C (-40°F) to 105°C (221°F)
<b>Vibration</b>	0.062" DA at 10–55 Hz
<b>Shock</b>	10 g
<b>Enclosure</b>	PC (94V-0)
<b>Terminals</b>	Tinned copper alloy, P.C.
<b>Max. Solder Temp.</b>	270°C (518°F)
<b>Max. Solder Time</b>	5 seconds
<b>Weight</b>	17 grams

**ZETTLER** electronics

Logistic Design (UK) Limited. Unit 3, Eagle Centre Way, Luton LU4 9US www.zettlerrelay.com sales@zettlerrelay.com  
Telephone +44 (0) 1582 599 600 Fax +44 (0) 1582 599 700

# AZ723

## RELAY ORDERING DATA

COIL SPECIFICATIONS - AC Coil					ORDER NUMBER	
Nominal Coil VAC	Must Operate VAC	Max. Continuous VAC	Nominal Current mA $\pm 10\%$	Coil Resistance $\pm 10\%$	Form A (DPST)	Form C (DPDT)
6	4.8	7.8	150.0	16	AZ723-2A-6A	AZ723-2C-6A
12	9.6	15.6	75.0	65	AZ723-2A-12A	AZ723-2C-12A
24	19.2	31.2	37.5	260	AZ723-2A-24A	AZ723-2C-24A
50	40.0	65.0	18.0	1130	AZ723-2A-50A	AZ723-2C-50A
110	88.0	143.0	10.6	4600	AZ723-2A-110A	AZ723-2C-110A
220	176.0	286.0	5.3	20200	AZ723-2A-220A	AZ723-2C-220A
230	184.0	299.0	3.6	24900	AZ723-2A-230A	AZ723-2C-230A

## MECHANICAL DATA

**Form A and C**

1.14 (29)

.5 (13)

.99 (25)

.01 (.26)

.04 (1.0)

Terminal number

Terminal number	Dimension	Tol.
1	0.23 (0.58)	$\pm 0.005$ (0.13)
2	0.23 (0.58)	$\pm 0.005$ (0.13)
3	0.015 (0.38)	$\pm 0.001$ (0.025)
4	0.040 (1.015)	$\pm 0.001$ (0.025)
5	0.015 (0.38)	$\pm 0.001$ (0.025)
6	0.040 (1.015)	$\pm 0.001$ (0.025)
7	0.015 (0.38)	$\pm 0.001$ (0.025)
8	0.040 (1.015)	$\pm 0.001$ (0.025)

Total XX  $\pm 0.010$  (0.26)

**WIRING DIAGRAM (Bottom View)**

**Form A**

**Form C**

**PC BOARD LAYOUT (Bottom View)**

.035 Dia. (0.9)  
2 places

.197 (5) .197 (5)

.590 (15)

.295 (7.5)

.08 (2.1)

.05 DIA. (1.3)

(Form C only) (4 places Form A)  
(6 places Form C)

Dimensions in inches with metric equivalents in parentheses. Tolerance:  $\pm 0.010$ "

**ZETTLER electronics**

Logistic Design (UK) Limited. Unit 3, Eagle Centre Way, Luton LU4 9US [www.zettlerrelay.com](http://www.zettlerrelay.com) [sales@zettlerrelay.com](mailto:sales@zettlerrelay.com)  
Telephone +44 (0) 1582 599 600 Fax +44 (0) 1582 599 700