


Part Number: SL22 30006

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL22 30006-A



Electrical Specifications:

Resistance @ 25°C	30.0 Ω \pm 20%
Max Steady State Current Up to 65°C	6.0 A
Max Recommended Voltage	265 VAC
Max Recommended Energy Rating (Joules)	63.0 J
Actual Failure Point of Instantaneous Energy (Joules)	275.0 J
Resistance @ 100% of Max Current	0.300 Ω
Resistance @ 50% of Max Current	0.820 Ω
Body Temperature @ 100% Current Rating	173 °C
Dissipation Constant	62.0mW/°C
Thermal Time Constant	104 seconds
Material Type	"H"
Max Recommended Capacitance @ 265 VAC	900 μ F

Mechanical Specifications:

D	20.0 \pm 1.0 mm
T	5.0 \pm 0.2 mm
Lead Diameter	1.0 \pm 0.1 mm
S	7.8 \pm 2.0 mm
L	38.0 \pm 9.0 mm
Straight Leads Coating Run Down	5.0 \pm 1.0 mm
B	9.35 \pm 0.85 mm
C	3.82 \pm 1.0 mm

Revision Date: Dec. 19, 2005

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com