

FAIRCHILD

A Schlumberger Company

BA217/BA218 T-01-09
General Purpose Diodes

- WIV... 10 V to 100 V
- t_{rr} ... 4ns (MAX) BA216-218

PACKAGES
BA217 DO-35
BA218 DO-35

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature Range -65°C to +200°C
Maximum Junction Operating Temperature +175°C
Lead Temperature +260°C

Power Dissipation (Note 2)

Maximum Total Power Dissipation at 25°C Ambient 600 mW
Linear Power Derating Factor (from 25°C) 3.33 mW/°C

Maximum Voltage and Currents

WIV Working Inverse Voltage BA218 50 V BA217 30 V
I_F Continuous Forward Current 100 mA
I_F Peak Repetitive Forward Current 300 mA
I_F(surge) Peak Forward Surge Current 400 mA
Pulse Width = 1 s 1.0 A
Pulse Width = 1 μs 4.0 A

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	BA217 - BA218		UNITS	TEST CONDITIONS
		MIN	MAX		
V _F	Forward Voltage		1.50 1.00 0.70		I _F = 100 mA I _F = 50 mA I _F = 15 mA I _F = 10 mA I _F = 3.0 mA I _F = 1.0 mA I _F = 0.2 mA
I _R	Reverse Current		50 50 200 200	nA nA nA nA nA nA	V _R = 10 V V _R = 10 V V _R = 25 V V _R = 30 V V _R = 50 V V _R = 50 V V _R = 100 V
C	Capacitance		3.0	pF	V _R = 0, f = 1 MHz
t _{rr}	Reverse Recovery Time		4.0	ns ns	I _F = 10 mA, I _R = 60 mA R _L = 100 Ω (Note 3) I _F = 30 mA, I _R = 30 mA R _L = 100 Ω (Note 4)

NOTES:

1. These ratings are limiting values above which the serviceability of the diode may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty-cycle operation.
3. Recovery to I_R = 1 mA.
4. Recovery to I_R = 3 mA.
5. For product family characteristic curves, refer to Chapter 4, D4